



**Hale Trailer Brake & Wheel**  
**A009214-A009263**  
**VIN: 036051-036100**



Product : , , , ,

**GVWR**

GVWR: Trailer to meet 68,000 Pound GVWR  
 VIN PLATE: US - VIN Plate to Read in English (Standard)  
 Product Type: HT Composite  
 Composite New Design: Composite New Design

**GEOMETRY**

Length - Exterior: 53'-0"  
 \*\* Length - Interior: 52'-6" Nominal Lining To Lining  
 Width - Exterior: 102.36"  
 \*\* Width - Interior: 101.5" Nominal Lining To Lining  
 Height - Exterior: 13'-6"  
 Height - Interior: 110" Nominal  
 Deck Height: Standard application  
 Fifth Wheel Height: 47"  
 King Pin Location: 36"  
 Landing Gear Location: 107" from King Pin (+ 1"/-1/4")

**TIRES & WHEELS**

Tire Furnished: Factory Furnished  
 \* Tire Manufacturer: Hankook TL21(G), Low Rolling Resistance Tire  
 Tire Size: 295/75R22.5  
 Wheel Furnish: Factory Furnished  
 Wheel Material: All Steel Wheel  
 Wheel Manufacturer: HT Standard (TCC 361)  
 Wheel Size: 8.25 x 22.5, 5-Hand Hole (Steel, Inner & Outer)  
 \* Wheel Finish for Steel: Hot Dip Galvanized.  
 Tire Stem Valve Position: Dual Wheel Steel / Aluminum / Combo (STD 180°outboard & straight inboard)  
 Wheel Finish for Aluminum: None (Due to All Steel Wheel Application)  
 \* Valve Stem & Cap: TR-572 Valve Stem# 8900HALNC for use w/PSI; w/o Cap

**UPPER COUPLER**

Approach Plate: 1/4" thick 80,000 Lb Yield - 6 Support Channels  
 King Pin (BTM Main) Plate: 1/4" thick 80,000 Lb Yield  
 King Pin & Manufacturer: Standard (Jost) AAR Cruciform King Pin  
 \* Front Bottom Rail: Galvanized-Whole Upper Coupler section, w/ Pick-Up plate Striker Angle  
 Upper Coupler Tube Qt'y: (1) Tubing Application - Joggled

**BODY/BASE**

Forward Crossmember: Steel Hat Shaped Upper Coupler to Landing Gear : 12" C/L  
 Landing Gear Crossmember: 4" Steel I-Beams (80,000 PSI) : 12" C/L (5ea)  
 Bay Area Crossmember: 4" Steel I-Beams (80,000 PSI) : 12" C/L  
 Running Gear C/M Size: 4" High  
 Running Gear Crossmember: 4" Steel I-Beams (80,000 PSI) : 12" C/L with 8" C/L Last 3.4'  
 Slider Body Rail (VT): 208" Rail Length

**FLOOR**

Upper Coupler Type: 3.40" Joggled with Exposed Coupler Top Plate (New STD)  
 Floor Specification: 1.38" (1-3/8") Nominal Domestic Laminated Oak Hardwood

Floor Ratings - VT: 18,000 lbs Rated Floor per TTMA- Standard HT Dry Van Floor Rating  
Floor- Assembly Method: Wood Floor Assembly  
Floor Screws: (3) 0.31" Dia. screws per Board on I beams  
Threshold-Finish: Hot Dip Galvanized  
Threshold Plate: 0.13" X 12" Deep Steel Diamond Plate w/ Screws and Nuts  
Threshold-Application: Standard Application

**FRONT**

Front Corner Radius: 4" Extruded Aluminum  
Front Panel & Color - Dry: 0.05" Aluminum Prepainted White w/ natural color rivets  
Front Corner Mat'l - Dry: Extruded Aluminum  
Front Posts: (4) 2.5" Deep (16Ga) Steel Hats - Non AAR  
Gladhands: Phillips Qwik-E with Filters Control Line Only. Overlaid  
Front Receptacle(7-Way): Phillips 7-Way without Circuit Breakers, Split Pins with QCS plug  
Front Receptacle(7-Way) - Options: Phillips QCS Plug connector  
Gladhand/7-Way Location: Overlaid on Lower Roadside Front  
\* Corner Radius Protector: (2) 0.125" X 12" Alum Diamond Plate Each Side at Top

**SIDE**

Composite Side Material: 6.5 mm thick (0.5 outer/inner skin) Composite Panel, Pre-painted White, Both Sides, with natural color rivets  
Side Posts: 14 Gauge Galv Steel 'A' Slotted Logistic Insets with Composite Panel color matching Outer Closure (For Composite New STD)  
Side Post Centers: 48.5" C/L Stiffener (Side Closure) - For Composite  
Side Top Rail: Side Top Rail for Composite (New STD)  
Side Bottom Rail: Side Bottom Rail for Composite (New STD)  
\* Skylight-General Spec.: Cluster Sky Light Lens on side wall for 24" or bigger post pitch (Single lens on two panels, next to each other, for 16" or less post pitches.)  
\* Skylight-Quantity: Total 5. Both Side Wall Panel. (3) on Roadside and (2) on Curbside  
\* Skylight-Location: Composite Both Side Wall Panel Location from Front, Specifically on panels #5, #9 on C/S & #3, #7, #11 on R/S  
Fasteners to Bottom Rail: Standard Rivets to attach C/Members to the Side Bottom Rail

**REAR**

Rear Frame: Swing Door, 2.5" New Door Header Standard Trailers (with 1 Lock Rod Per LH & RH Door)  
Rear Door Opening Spec.: Standard Application  
Floor Level: Door to be Flush with Floor (STD)  
Door Type for Dry Van - SW: 0.5" Composite Swing Door. Galvanized Prepainted White Interior & Exterior Skin  
Option - Door Install Instruct: Standard Door Installation per Manufacturer's Recommendation  
Option - Door & Hardware: One(1) Rubber Door Bumper Standard (1" Deep) on Hinge of each Swing Door  
Door Holder Type for Swing Door: Standard Door Holdback  
\* Hinges: Four (4) Aluminum Hinges per Door  
\* Additional Hinge Option: Additional One(1) Aluminum Hinge (Total 5 Per Door)  
\* Rear Underride Guard: 4" Tube Bolt on Assembly w/ Welded Perforated(Pooched) Horizontal. Rear Impact Guard (RIG) 30  
Option - Horiz Member/Other: One piece roll formed w/continuous welding  
Underide Bolt Spec.: Zinc plated bolts & nuts - Standard  
Dock Bumper: Pair 3" X 6" Mold Bolted Bumper  
Rubber Bumper Location: Inboard of Light Protector Bars (Standard)

**LIFT GATE**

Roof Panel: 0.040" Aluminum  
Roof Bow: 16 Gauge Galvanized Steel Anti-Snag  
Roof Bow Centers: 24" Centers Full Length

**LINING/SQUEE**

Front Lining: 0.25" Top and 0.5" Bottom plywood Mounted to Front Posts Full Height

- \* Base Side Scuff: 6.0" High Integral Alum (New Composite STD) with Additional scuff (Plastic, Corrugated or Wood)
- \* Additional Side Scuff: 18Ga x 6.5"H Corrugated Steel Butted to Intergral Aluminum
- \* Front Scuff: 0.63" x 12" High White Recycled Plastic Mounted Over Lining to Front Posts (Overlaid)

**LANDING GEAR**

- L/Gear Spec.: Jost HT421.G3.17.157 5 Year Warranty Full HDG
- L/Gear Mt'g Method: Inboard Mounting (Standard)
- L/Gear Shoes: 10" X 10" RCF (Removable Cushion Foot) Low Profile
- L/Gear Ground Clearance: Nom. 12" Ground Clearance
- L/Gear Mt'g Bracket: Hot Dip Galvanized Large Wing Plate
- L/Gear Crank Handle: Roadside
- L/Gear Options: None (HT STD)
- L/Gear Cross Brace Design: HT Standard Cross Brace attachment Design

**RUNNING GEAR**

- Bogie Type: Sliding Tandem(2) Axle Bogie
- Axle Spacing: 49" Axle Spacing
- Axle ABS System: Tandem Axle w/2S1M ABS System
- Bogie & Axle Location: Location to be Sliding Tandem Axle for specified slider Length w/Stop Bars @ Front & Rear
- Option-Related Bogie Stopper Feature: STD plug stopper
- Susp. Manufacturer: Hendrickson
- Suspension Capacity: Standard Duty
- Hendrickson Susp. Specification: Hendrickson Vantraxx HKANT40K Air Ride
- Surelok (Anti-Dock): Surelok (Anti-Dock) Installed
- Locking Pin Mechanism: Air-Assist Pin Puller or Quik Draw
- Susp. Sub-Frame: Hendrickson K-2 STD Duty
- Type of Susp Spring: Air Bag
- Spring Specification: Air Bag
- \* Axle Diameter: 5.75"
- Axle Supplier: Hendrickson
- Axle-General Spec.: Axle - Tandem (2) Axle included in Suspension (For 2S1M or 2S2M System)
- Axle-Track Length: 77-1/2"
- Axle-Spindle Type: Tapered Spindle
- Brake Lining Size: 16.5" X 7"
- Brake Lining Spec.: Hendrickson Extended Service (Abex-3030-197)
- Brake Control System: 2S/1M Wabco ABS
- Spring Brake Control: Sealco 110500 Springbrake Priority
- Brake Cont-Hose & etc.: Standard Air Line & Hose Application (US&Canada)
- \* Slack Adjuster Spec.: Wabco Auto-5.5", 28 Spline EasyFit (No Grease)
- \* Brake Chamber Spec.: Wabco Premium Chamber
- \* Stroke Length: 3" Long Stroke Length
- Hub Specification: HT Standard (KIC) 10 Stud Hub Piloted Outboard Iron Hub
- Drum Specification: HT Standard (KIC) Cast Drum
- Hub/Drum-Opt(Nut&Other): Standard
- Bearing Specification: Stemco
- \* Lubrication Spec.: Chev Delo (Syn) Grease
- \* Wheel Seals Spec.: Stemco Discover Seals, Hub Cap included in tire inflation system, Pro-Torq Nut
- \* Tire Inflation Spec.: Hendrickson Tire Maax Inflation System for Undressed Axle (This kit include Hendrickson Hub Cap for TireMaax)
- Tire Inflation Pressure: 100 PSI
- \* Tire Inflation Lamp Location: Indicator PSI Light at Roadside Mounted over corner radius. (STD location)
- \* Tire Inflation Lamp Spec.: 33 Series Lamp

**ELECTRICAL**

- Harness-General Spec.: Molded Color Code Phillips Harness with QCS Plug

Harness-Special Feature:	Manufacturer's Standard Feature
Front Light:	(2) Trucklite 33275Y LED PC Rated Mounted with Grommet
* Rear ID Header Light:	(5) Trucklite Dual Function 33204R LED (Cluster of 3 & 1 Each Outboard)
* Rear ID-Special Feature:	Dual Function Rear Header Lights - 3 Lamps at center with Marker & Stop functionality, 2 Lamps outboard with Marker & Turn functionality
Rear Side Marker Type(Shape):	Mini Button Style Lamp with Antitheft Bracket
Rear Side Marker Detail Spec:	(2) Trucklite 33275R LED PC Rated Flush w/ Grommet 33725 w/ anti-theft hardware
Rear Side Marker MT'G Location:	Mounted on Standard Location on Rear Corner Post - HT STD
S/T/Tail Light-Quantity & Type:	(4) Trucklite 40 or 44 Series (Round Style) or Equivalent
S/T/Tail Light-Detail Spec:	(4) Trucklite 44331R LED (Super 44 Grey) Flange Mounted w/ Stainless Steel Rivets
Main Mid-Turn Light:	Install the Mid turn lamp
Mid-Turn Mounting Method:	Mounting Bracket
* Main Mid-Turn Light-Detail Spec:	(2) Trucklite 60272Y LED Gray Flange Mounted with Stainless Steel Rivets & Anti-theft brackets
ABS Light Detail Spec:	(1) Trucklite 33275Y LED PC Rated w/ Grommet 33725 w/ anti-theft hardware
ABS Light MT'G Location:	Mounted on Standard Location on Rear Corner Post - HT STD
License Light:	(1) Trucklite 33210C LED with 33815 Anti-Theft Flange
Option Related Harness/Wiring:	Standard
Electrical Related Regulation:	Standard Application

**MARKING/DECALS**

HT & Product Type Decal Package:	Hyundai Logo & Product Type Decals Application(For not having pre-painted white panels for side/door/front, Apply white HT Corporate decals)
Decal Package:	Factory Furnished Hyundai Information & Regulatory Decal Package with FMCSA Specified in Notes
Decal Opt 2-Decal Location:	Standard Application
Decal Opt 3-Decal Installation:	Standard Application
* Conspicuity Vendor:	Avery
Conspicuity Markings:	Hyundai Standard Conspicuity with Logo Applied to Side Bottom Rail
License Plate:	Temporary For Delivery. Fasten On HDG Mounting Plate
License Plate Brk't Install:	Standard Install Location - Roadside Below Door Sill
Furnish Document Holder:	Factory Furnished
Document Holder Detail Spec:	(1) Phillips 16-802
* Document Holder/Manifest Loc.:	Overlaid on Lower R/S Front. 18" from the bottom of the front sheet between the front post & corner radius on the roadside

**PAIN/FINISH**

* Upper Coupler Finish:	Galvanized-Whole upper coupler section
* Crossmembers Finish:	HDG : ALL Steel Crossmembers including Hat C/M, L/G & Bogie Area (Except any Aluminum)
* Axle & Components Finish:	Black Undercoating
* Susp. Sub-Frame Finish:	Black Undercoating
L/Gear(K-Bracing) Finish:	Hot Dip Galvanized
* L/Gear(Upper Leg) Finish:	Hot Dip Galvanized
Rear Frame-Finish:	Hot Dip Galvanized
Rear Frame-Paint Color:	None (For Galvanized or Stainless Steel)
Rear Underride-Finish & Spec.:	Hot Dip Galvanized & Welded Horizontal Member
Rear Underride-Paint Color:	None (For Galvanized or Stainless Steel)

**MISCELLANEOUS**

Mudflap Provider:	Factory Furnished Mudflaps
Mudflap Specification:	24"x30" White Plain Plastic with Hyundai Logo
Mudflap Mounting Loc.:	Suspension Frame
Mudflap Mounting:	STD Location w/ H.D Washer Retainer
* Lift Pad Spec.:	Install HT Occasional use lift pads for delivery, with HYUZ decals

**DISCLAIMER**

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.