



Hale Trailer Brake & Wheel
A009538-A009560
VIN: 53544-53566



Velocity Flat 48 Spring Slider (HAVSF12SST)

Detailed Specifications		General
Model	HAVSF12SST	
Length x Width	48 feet x 102 inches	
Suspension	Sliding Spring Tandem	
Frame Rating	80,000 lbs Distributed - GAWR and Tire Ratings Determine Legal Payloads	
Kingpin Setting	30 inches	
Fifth Wheel Height	49 inches	
Axle Spread	49 inches	
VIN Plate	Bilingual US/Canadian VIN plate	
Estimated Weight	Est. Weight: 11880 lbs. +/-3%	
Structural		
Main Beams	130K Load Bearing Flanges	
Crossmembers	12 inch Centers - 4 inch Jr. I-Steel	
Knee Braces	Fabricated on Approx. 60 inch C/C	
Side Rails	6 inch Structural Channel @ 6.5 lbs/ft	
Stake Pockets	3/16 inch Steel on 24 inch Centers	
Pipe Spools	Double Between Stake Pockets	
Rubrail	3/8 inch x 2 1/2 inch Steel	
Front Corners	Tapered	
Bumper	Weld-On; Meets U.S. Underride Requirements	
Winch Track	Steel on Road Side	
Bulkhead Pockets	4 - F-5 DOT-Type Steel	
Landing Gear		
Landing Gear	Jost A400G19 Steel Landing Gear with Forward and Rear Bracing	
Flooring		
Flooring	1 1/8 inch Apitong Wood	
Suspension		
Suspension Detail	OEM Standard 3-leaf spring slider - 60 inches adjustable	
Number of Axles	2	
Axle Spindle	Tapered	
Brakes	Spring Brakes, Auto Slacks	
Hubs and Drums	10-Hole Hub-Piloted with Outboard Cast Drums	
Wheel Ends	Oil in Hubs	
Tire Inflation System	None Standard	
Wheels and Tires		
Wheels	22.5 x 8.25 Steel Disc Wheels - Pre-Painted White - STANDARD	
Tires	11R 22.5 14PR OEM Standard tires	
Air System		
Air Line Filters	(2) Meritor In-line Type Installed	
ABS	4S/2M - No Cable or Tool	
Gladhand Position	Front Gladhands and Electrical Connections in Center of Trailer	



Detailed Specifications

Electrical System	
Tailskirt Lights	LED: 2 Lights/Side on Rear
Side Marker Lights	LED: 3 Lights/Side
Paint and Decal	
Paint	Black Urethane with Velocity Decals
Conspicuity Tape	Per NHTSA Specs - Installed on Rubrails
Unit Number & Decals	Fontaine Standard Decals Installed
Miscellaneous	
Mudflaps	1 Set OEM Standard
Sliding Winches	12 standard
Winch Location	All Road Side
27' Winch Straps	None Standard
30' Winch Straps	None Standard
Dock Bumpers	1 Pair Rubber on Rear
Registration Holder	Install Registration Holder - OEM Standard
Options	
Bulkhead	None Standard
Spare Tire Carrier	None Standard
Hubodometer	None Standard
Tool Box	None Standard
Literature	
Trailer Literature	Velocity Brochure

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.