

HALE

TRAILER

BRAKE & WHEEL

GENESIS FRAMELESS DUMP



A009660-A009661

VIN: 81356-81357

SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Jacksonville, FL:	800-828-3055
Baltimore, MD:	888-601-7500	Little Rock, AR:	833-424-8944
Boston, MA:	800-854-5310	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Richmond, VA:	866-839-3495
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235

HaleTrailer.com | @haletrailer



800-232-6535 *FINANCING AVAILABLE

Length	40'	BODY SPECIFICATIONS		Body	* FRONT TARP CAP W/ 12" RISE
Width	102" INBOARD	Tarp	NONE	Accessories	AND 10 MARKER LIGHTS
Side Height	78" SOLID	Bow Holders	NONE		* REAR ALUM CAP W/ 12" RISE
Top Rail	9" DUMP	Tarp Bows	NONE		BOLTED TO GATE & W/ 10 LIGHTS
Side Mat'l-front	20' - .100" WALL	Tarp Basket	NONE		WIRED AS CLEARANCE.
-middle	10' - .140" WALL	Tarp Hooks	NONE	TAILGATE	
-rear	10' - .180" WALL	Bulkhead Mat'l	3/16"	Height	FULL - GENESIS
Side Options	NONE	Bulkhead	D/S-MANDOOK	Mat'l Thkness	.140 WALL
Floor Mat'l	1/4"	Options	GRATED STEP SEE PICTURE	Slope	NONE
		Body Fenders	SQUARE OFF	Hinges	OVERSLUNG
Crsmbr Spacing	12"	Ladders (Out)	NONE	Side Swing	YES-INTRL GRND CTRL-P/S HINGE
				Gate Seal	RUBBER
Floor Options	ADD 1/4" X 8" CLEANOUT	Inside	NONE	Safety Latch	ONE EACH SIDE
	FLOOR STRINGERS- 4 ROWS	Shovel Hgr	NONE	Coal/Grain Door	20"
	OF 2" PLATES FULL LENGTH	Light Panel	FULL - LED; X=LED BACK UP	Coal Chute	NONE
Tailgate Control	AIR FRAME+ ELEC CC (1)(9)(10)		OOOXXOOXXOOXX (8)	Gate Options	NONE
Body Pkg	NONE	Marker Lights	LED - 12 PR BOTTOM		
Options		MMTS	OVAL LED - PIVOT BRACKET		
Vibrator	PREP FOR FUTURE COUGER DC3200	Apron	NONE		
Mudflaps	STD (2)(3)(4)(5)(6)				
	ACROSS REAR CHASSIS				

CHASSIS SPECIFICATIONS

Model	TANDEM - SPREAD (7)	ABS	2S / 1M	Tire Carrier	NONE
Length	PER ENGINEERING			Landing Gear	2 SPEED JOST ALUMILIGHT X
Width	102"				D/S CRANK
Draft Arms	ALUMINUM	Independ. Susp(s)			
Hoist	85-285		NONE		
5TH WP		Distance:		Elec Coupler	7 WAY + 7 WAY ISO
King Pin Setting	16"	From:			LABELLED 'AUXILIARY'
5th Whl Ht	49"	Controls		Hyd Hose Fitting	WINGNUT
				Hyd Hose Length	108"
Rear Axle Setting	21.5"	Location		Tow Hooks	NONE
K/P To Rear Axle	442-1/2"	Axle(s)		Paint	BLACK
Suspension	AAT30K / E2 / L- LIFT (9)(10)(11)				
Susp Control	FRAME + ELEC CC (9)(10)	Accessories		Chassis	BOLT ON TRANSPORT
Susp Spacing	121"			Options:	STRAPS
Susp Options	GALVANIZED HANGERS(12)				
Springs	AIR	Brakes			
Axles	TP SPINDLES	Drums			
Accessories	NONE				
Brakes	16-1/2" x 7"	Hubs			
Drums	CAST				
Hubs	10 STUD LWSTEEL	Wheels			
Wheels	8.25 X 24.5 8 HIGH POLISHED	Tires			
Tires	11R 24.5 RA H 16 PLY GEN.				

REMARKS:

CHANGE 1, 2 WEIGHT: 13,408

1. LATCH BAR GREASE: REMOTE ZERKS (073-70003-00) REMOTE FITTINGS TO THREE BEARINGS.
2. 40" ALUM FLAP W/ 3" LIP AND 10" BLACK RUBBER ON BOTTOM AND THREE 4" MODEL 40 LIGHTS WIRED AS MARKER AHEAD OF EACH AXLE. REF PIC BELOW.
3. CENTER ALUMINUM CHASSIS FLAP AHEAD OF EACH AXLE W/ BLACK RUBBER ON BOTTOM AND FIVE 4" MODEL 40'S WIRED AS MARKERS-REF PIC BELOW.
4. 40" ALUM FLAP W/ 3" LIP AND 10" BLACK RUBBER ON BOTTOM AND THREE 4" MODEL 40 LIGHTS WIRED AS BRAKE REARWARD OF FORWARD AXLE-REF PIC BELOW.
5. CENTER ALUMINUM CHASSIS FLAP REARWARD OF FORWARD AXLE W/ BLACK RUBBER ON BOTTOM AND FIVE 4" MODEL 40'S WIRED AS BRAKES-REF PIC BELOW.
6. ALL ALUMINUM OUTWARD FLAPS AND CENTER FLAPS TO BE FLUSH HORIZONTALLY AND VERTICALLY.
7. BOLT ON SUBFRAME COVER.
8. LIGHT PANEL TO BE ALL 4" LED AND SPACED EVENLY
9. TAILGATE, SUSPENSION EXHAUST, LIFT AXLE (W/ BRAKE RELEASE) ALL TO BE FRAME SWITCHES AND ELECTRIC CAB CONTROL WIRED TO AUXILIARY PLUG.
10. ALL FRAME SWITCHES TO BE IN POLYCARBONATE BOX (AMP1086LF) ON D/S BETWEEN SPREAD.
11. AIR GAUGE (LBS.) PLUMBED TO SUSPENSION AND MOUNTED AT COUPLER PLATE.
12. STRAP STOPS ON FRONT AXLE ONLY.

13. 80K GVWR



DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.