Hale Trailer Brake & Wheel A009745-A009764 081534-081553





EAST GENESIS TIPPER TRAILER

| В | ODY: "GENESIS" | TAILG | ATE: | CHASS | SIS: |
|-----------------------------------|-------------------|-----------------|--------------|--------------------|---------------------|
| WIDTH (INCHES) | 102 | HEIGHT | FULL | MODEL | TANDEM |
| LENGTH (FEET) | 48 | TYPE | SINGLE | TYPE | ALUM SUB FRAME |
| HEIGHT (INCHES) | 104 | STYLE | GENESIS | AXLE TO AXLE | 49" |
| SIDE MAT'L (OUTBOARD |) GENESIS | MAT'L THICKNESS | 0.150 | REAR AXLE SETTING | 26.5" |
| FF | RONT 0.150 | HINGES | OVERSLUNG | 5TH WHEEL HT | 49" (STD) |
| MI | DDLE 0.150 | SIDE SWING | NO | PIN SETTING | 36" + 3/8" KP PLATE |
| I | REAR 0.150 | GATESEAL | NO | SUSPENSION | REYCO 21B |
| POLISHED SIDES | NONE | GATE LADDER | CAST -CENTER | SPRINGS | SINGLE LEAF |
| ROOF | NONE | TARP HOOKS | NONE | AXLES | TP SPINDLES (5) |
| ROOF MAT'L | NONE | WINDERS | ONE EA. SIDE | BRAKES | 16-1/2" x 7" |
| BULKHEAD | 3/16" (1) | GATE GUIDE | NONE | DUST SHIELDS | YES |
| TARP HOOKS | NONE | GATE CONTROL | AIR | BRAKE CHAMBERS | TOP OF AXLE |
| TARP BASKET | NONE | POCKETS | EXTRUDED | ABS | 4S/2M |
| TARP | NONE | CROSSPIPE(S) | ONE - MIDDLE | HUBS | 10 S STEEL |
| CATWALK | YES | | TUBE TYPE | DRUMS | CAST |
| B.H. LADDER | D/S-COMMERCIAL | | | WHEELS | 8.25 X 24.5 |
| G. H. PROTECTIVE SHIELD YES - D/S | | COMPACTOR: | | | STEEL DISC |
| CROSSME | MBER TYPE: | SIDE LATCH | N/A | TIRES | 11R 24.5 RA 16 PLY |
| "V" STYLE ON 9" SPACE | YES (2) | CENTER LATCH | | | GENERAL |
| "I" BEAM ON 12" C/L | NO | PIN DIA. | | DOLLIES | 2 SPD JOST A450 |
| FLOOR MAT'L | 1/4" | | | LOCATION | D/S CRANK |
| ADD 1/4" x 5" CLEANOUT | | | | DISTANCE FROM REAR | APPROX 34' 6" |
| TAPE COLOR | BLUE | _ | | BUMPER | STEEL |
| LIGHT PANEL | LED - ON BODY | | | TIPPER PADS | STEEL 'T' |
| MARKER LIGHTS | LED - (3) | | | TOW HOOK(S) | TWO |
| MIDMOUNT SIGNALS | LED - MODEL 60 | | | PAINT | SILVER |
| MUDFLAPS | YES | | | | |
| TIRE CARRIER | YES-P/S ACCESS | | | | |

REMARKS:

| 1 | FOUR CAST | STEPS | INISIDE | BI II KHEAD | ח/פ |
|----|--------------|-------|---------|-------------|------|
| ι. | 1 0011 0/101 | | IIIOIDL | DOLINILAD | D/O. |

- 2. WELD ENDS OF ALL CROSSMEMBERS TO BOTTOM RAIL.
- 3. 3 PAIR PER SIDE TOP & BOTTOM WITH PROTECTORS. RUBBER GROMMETS IN ALL LOCATIONS THAT WIRE PASSES THROUGH ALUMINUM.
- 4. FILTERED GLAND HANDS.
- 5. 23,000# GAWR FOR NEW YORK 'R' PERMIT 46,000#

| 6. | ALUMINUM AIR | TANKS TO HAVE | CABLE OPERATED | DRAINS EXTENDED | TO D/S BOTTOM RAIL |
|----|---------------------|---------------|----------------|-----------------|--------------------|

OVERALL HEIGHT (FT) 13.25

EMPTY WEIGHT (#) 14,660

CUBIC YARDS 125

(EMPTY WEIGHT VARIANCE +/- 3%)
DISCLAIMER