



# Hale Trailer Brake & Wheel

A009798-A009801

VINS: 81348-81351



## GENESIS FRAME DUMP

Length	33'	BODY SPECIFICATIONS		Body	
Width	96" INBOARD	Tarp	NONE	Accessories	
Side Height	64" SOLID	Bow Holders	NONE		
Top Rail	9" DUMP	Tarp Bows	NONE		
Side Mat'l-front	4' - .100 WALL	Tarp Basket	NONE		
-middle	23' - .140 WALL	Tarp Hooks	NONE		
-rear	6' - .180 WALL	Bulkhead Mat'l	3/16"	TAILGATE	
Side Options	NONE	Bulkhead	D/S-MANDOOK	Height	FULL - GENESIS
Floor Mat'l	1/4" FULL LENGTH	Options	5" SLOPE PLATES	Mat'l Thkness	.140 WALL
Crsmbr Spacing	12"	Body Fenders	18"	Slope	NONE
Floor Options	STUB LONGITUDINALS	Ladders (Out)	D/S-REAR	Hinges	OVERSLUNG
		Inside	NONE	Side Swing	YES -W / GRD CNTRL-P/S HINGE
Tailgate Control	AIR / FRAME + ELEC CC (4)	Shovel Hgr	INSIDE P/S OF DOGHOUSE	Gataseal	RUBBER
Body Pkg	NONE	Light Panel	FULL - LED; X=LED B/U LIGHTS	Safety Latch	ONE EACH SIDE
Options			OOOX ooo XOOO	Coal/Grain Door	NONE
Vibrator	NONE	Marker Lights	LED - 13 PR TOP & BOTTOM	Coal Chute	NONE
Mudflaps	STD + ACROSS REAR (1)	MMTS	BELOW RAIL - LED	Gate Options	REMARK (9)
		Apron	NONE		

### CHASSIS SPECIFICATIONS

Model	TRIAxLE-2 FIXED-FRONT LIFT	ABS	2S/1M	Tire Carrier	NONE
Beam Mat'l	ALUMINUM			Landing Gear	2 SPEED JOST HX150
Length	34'				D/S CRANK
Width	96"	Independ. Susp(s)		Chassis Lights	NONE
Hoist	85-265 (2)(12)			Elec Coupler	7 WAY + ISO 7 WAY LABELED
Chassis Neck	STD	Distance:			'AUXILIARY'
King Pin Setting	18"	From:		Hyd Tank	NONE
5th Whl Plate	3/8" W/ 3/8"X 3" X 7" MNT			Hyd Hose Fitting	WINGNUT
5th Whl Ht	50"	Controls		Hyd Hose Length	108"
Overhang	6"			Tow Hooks	TWO-ONE EACH SIDE
Rear Axle Setting	21.5"	Location		Paint	BLACK SOFTCOAT
K/P To Rear Axle	411.5"	Axle(s)			NONE
Suspension	AAT30K / E3-2 L LIFT-E1 (3)(5)	Accessories		Chassis	CHASSIS REAR CM: TAPERED
Susp Control	FRAME + ELEC CC (4)(10)			Options:	W/ DIAMOND PLATE COVER
Susp Spacing	52" - 52" (6)	Brakes			
Susp Options	GALVANIZED HANGERS	Drums			REMARK (13)(14)
Springs	AIR	Hubs			
Axles	TP SPINDLES	Wheels			
Accessories	NONE	Tires			
Brakes	MAXX 22T ADB				
Drums	N/A				
Hubs	10 STUD STEEL - PILOT				
	W/ HXL-5; GREASED HUBS				
Wheels	8.25 x 24.5 6 HP/ 6 MP				
Tires	11R 24.5 HSR2 16 PLY CONT.(11)				

REMARKS: PRICING SUBJECT TO CHANGE 12 WEEKS PRIOR TO ESTIMATED BUILD TIME.

1. BLACK RUBBER FLAP AHEAD OF AXLE #1 IN THE CENTER.-MUDFLAP 4" FORWARD OF STANDARD POSITION.
2. REMOTE GREASE ZERK FROM TOP PIN TO BOTTOM D/S FACING FORWARD.
3. RIGHT WEIGH OIL FILLED GAUGE (LBS.)(FLUSH MOUNT) ON FRONT CHASSIS CROSSMEMBER.
4. WIRED TO AUXILIARY ISO 7 WAY PLUG
5. HEIGHT CONTROL VALVE ON AXLE #2.
6. LIFT AXLE TO BE CONTROLLED THROUGH FRAME SWITCH & ELEC CC (WIRED TO AUX. PLUG) AND TO HAVE BRAKE RELEASE (LIFT AXLE TO SPIN FREELY).
7. ALL FRAME SWITCHES TO BE IN BOX ON D/S NEAR LANDING GEAR. **CHANGE 1**
8. PLASTIC INSULATORS BETWEEN WHEEL/DRUM & WHEEL/HUB ALL AXLES.
9. REMOTE GREASE ZERKS FOR LATCH BAR **WEIGHT: 14,019**
10. CROSSOVER KITS

11. TIREMAXX PRO INFLATION SYSTEM ON ALL THREE AXLES
12. NO ACCESS ON OUTSIDE OF BULKHEAD OR FLAP, ACCESS ONLY ON DOGHOUSE IN INSIDE.
13. HINGE SHOE GREASE ZERKS-REMOTE ZERKS TO D/S MANIFOLD
14. REAR PIN BUSHING LUBE-REMOTE GREASE ZERKS TO D/S MANIFOLD
15. ALL EAST LOGOS TO BE DECALS ONLY-NOT RIVETTED OR WELDED

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.