



Hale Trailer Brake & Wheel A009866-A009893 VIN: 60095-60122

Velocity Drop Deck 48' Wide Spread Air (Model: HAVSD12WSA)

Overall Length: 48 feet x 102 inches
Suspension Type: Wide spread air
Deck Lengths: 10 feet front and 38 fee

Deck Lengths: 10 feet front and 38 feet rear **Frame Rating:** 80,000 lbs distributed - GAWR and tire ratings determine legal payloads

Rear Deck Height: 40 inches - loaded

Flooring: 1 1/8 inch Apitong wood

Crossmembers: 18 inch centers front deck / 12 inch centers rear deck - 4 inch jr. I-steel

Side Rails: 6 inch structural channel @ 6.5 lbs/ft

Stake Pockets: 3/16 inch steel on 24 inch centers

Pipe Spools: Double between stake pockets

Rubrail: 3/8 inch x 2 1/2 inch steel **Main Beams:** 130K load bearing flanges **Kingpin:** 18 inches

Loaded Fifth Wheel Height: 49 inches

Landing Gear: OEM standard

Knee Braces: Fabricated on approx. 60 inch C/C

Bulkheads: None standard

Bulkhead Pockets: 4 - F-5 DOT-type steel

Number of Axles: 2 Axle Spindle: Tapered

Brakes: Spring brakes, auto slacks

Air Line Filters: (2) Meritor In-line type installed

ABS: 4S/2M - no cable or tool
Axle Spread: 122 inches - set at rear

Hub and Drums: 10-hole hub-piloted with outboard cast drums **Wheel Ends:** Grease in hubs - *** 5-year wheel end warranty ***

Wheels: 22.5 x 8.25 steel disc wheels - pre-painted white - STANDARD

Tires: 255/70R 22.5 16PR OEM standard
Tire Inflation System: None standard
Suspension Detail: AANL23K Intraax air ride

Auto Glad Hand Dump: Installed

Electric Dump Valve: Wired to 7-way auxiliary socket to dump rear axle

Air Lift: None Standard Front Corners: Tapered

Electrical System: LED: 3 lights/side, 2 lights/side on rear- STANDARD

Paint: Black urethane with Velocity decals - STANDARD Conspicuity Tape: Per NHTSA specs - installed on rubrails Bumper: Weld-on type - meets underride requirements

Mudflaps: 2 sets OEM standard; Spring loaded brackets behind front axle

Winch Track: Steel on road side: 8-foot front deck and full length on rear deck where possible

Sliding Winches: 12 standard: 2 front deck and 10 rear deck

27' Winch Straps: None standard 30' Winch Straps: None standard Dock Bumpers: 1 pair rubber on rear

 $\textbf{Spare Tire Carrier:} \ 1 \ \text{standard - mounted between lower gooseneck beams}$

Hubodometer: None standard

Registration Holder: Install registration holder - OEM standard

Tool Box: None standard

VIN Plate: Bilingual US/Canadian VIN plate
Please Note: Price includes commodity surcharges
Unit Numbers & Decals: Not available