

Hale Trailer Brake & Wheel A009932-A009981 VIN: A2203-A2252



Detailed Specifications

XTP4880SS2 (Model: XCA4880	NSSYT8/18/192)
X11 4000332 (Flodel: ACA4000	
2141	General
SKU	XCA4880SSXT848492
Capacity	80,000# Distributed - Self-Supporting, Properly Blocked
Length	48 feet 0 inches
Width	8 feet 6 inches
Weight	Est. Configured Weight: 16230# +/- 3%
	Gooseneck
Kingpin	24 inches
	Deck
Loaded Fifth Wheel Height	49 inches
Landing Gear	OEM Standard
Bulkheads	None
Bulkhead Pockets	4 - F-5 DOT-Type Steel
Main Beams	Minimum Grade 80 Flanges
Crossmembers	12 inch Centers - 4 in Jr I-Steel
Deck Lock	Approx. Every 5 feet
Front Corners	Tapered
Side Rails	6 inch Structural Channel @ 6.5lbs/ft
Stake Pockets	3/16 inch Steel on 24 inch Centers
Pipe Spool	Single Pipe Spool
Rubrail	2 1/2 inch x 3/8 inch Thick HD Mill Formed Steel
Flooring	1 1/8 inch Wood
Winch Track	Full-Length Steel on Roadside
Sliding Winches	12 - without Straps
Winch Straps	None
Air and Electrical at Extension Locks	Inside Track System
Toolbox	None
Bumper	Meets Underride Requirements
Mudflaps	1 Set - Fontaine
VIN Plate	Bilingual VIN Plate
Registration/Document Holder	Install Registration/Document Holder
	Rear Bridge: Axles
Number of Axles	2
Axle Spread	49 inches
Brakes	Spring Brakes, Auto Slacks
Dust Shield	None
Hub and Drums	10-Hole Hub-Piloted with Outboard Cast Drums
	Rear Bridge: Suspension
Suspension	Sliding Spring Tandem Hutch H-9700 3 Leaf Spring Slider - 96 inch Adjustable CAL LEGAL
ABS	2S/1M - No Cable or Tool
Manual Dump Valve	None
Liquid Filled Gauge	None
Load Scale	None
	-



Detailed Specifications

Detailed Specifications	
	Wheels and Tires
Wheels	22.5 x 8.25 Steel Disc Wheels - Pre-painted White
Tires	11R 22.5 OEM Economical
Hubodometer	None
Inflation	None
Wheel Ends	Grease in Hubs
	Lighting
Electrical System	Sealed Harness and LED Lights with 4 inch Flush Mounted Amber Strobes (No Battery Backup)
Tail Lights	3 Lights/Side, 3 Lights/Side on Rear
	Paint
Paint	Fontaine Black Polyurethane Enamel
	Terms
Please Note	Price Includes Commodity Surcharges
Commercial Terms	Ex Works- Springville, AL, USA
	XTP4880SS2
17 17 18 18	*・・・・・・・・・・・・・・・・・・・・・・・・・・・・・・・・・・・・

XTP4880SS2 Base Model (Note: Options not shown)



