



Hale Trailer Brake & Wheel

A010034-A010042

VIN: Q33424-Q33432



Series: HYDRAULIC DETACHABLE GOOSENECK

Model: RTN55TD3-PS

Item	Description
MODEL	RTN55TD3-PS
TONS CAPACITY	55 TONS IN ANY 16'
CONSTRUCTION	(4) I-BEAM, CAMBERED, T-1 STEEL
CUSTOM/PAVER SPECIAL	TAPERED FRONT BEAMS (8-3/8" DEEP)
PLATFORM WIDTH	8'-6"
PLATFORM LENGTH	24' (HOLD 53' OAL) NOT TO EXCEED 43'-0" FROM THE 84" KINGPIN TO THE CENTER OF THE 2ND AXLE
PLATFORM HEIGHT/ROAD CLEARANCE	22"/6" LOADED (ADJUSTABLE)
CROSSMEMBER SPACING	ON 20" CENTERS
AUXILIARY CROSSMEMBERS	OUTSIDE OF MAINBEAMS BETWEEN CROSSMEMBERS
FRONT FOLDING RAMPS	41" LONG-WOOD FILLED-ADJUSTABLE
FRAME REINFORCEMENT	FOR 4 CLOSED COUPLE AXLES ONLY
BUCKET TROUGH	40" FORWARD OF SLOPE AND CLEAR THROUGH THE 1ST AXLE
HYDRAULIC SYSTEM	FROM TRACTOR WETLINE
GOOSENECK	NON-GROUND ENGAGING REMOVABLE-HI LIFT
GOOSENECK SUPPORT CYLINDER	HYDRAULIC
GOOSENECK CONNECTION	PIN & STIRRUP TYPE W/ VERTICAL AIR LOCK PIN
SWING CLEARANCE	108" & 84"
FIFTH WHEEL HEIGHT	48"-50"-52"-54"-56" LOADED (ADJUSTABLE)
1/8" ALUMINUM TOP COVER	OVER GOOSENECK AREA
AIR BRAKES	16.5" X 7" W/ AUTO SLACKS & OUTBOARD DRUMS
ANTI-LOCK BRAKES	NONE (TRAILER GVWR EXCEEDS 120,000#)
SPRING BRAKES	ON ONE AXLE
AXLES	(3) 25,000# 3/4" WALL W/ 23,000# BRAKES AND LIMITED CHAINS
TIRES	(12) 275/70R22.5 (H)
WHEELS	ACCURIDE EXTRA POLISHED OUTERS, STEEL DISC INNERS
SUSPENSION	AIR RIDE W/ 50" AXLE SPACING
SUSPENSION	AIR LIFT 3RD AXLE ONLY
SUSPENSION	+3/-3 HEIGHT CONTROL, AUTO/MANUAL
RAISING AND LOWERING VALVE	AT REAR OF TRAILER
LIGHTS	L.E.D. TRUCK-LITE RUBBER SEALED SYSTEM
BATTERY BACK-UP	AMBER STROBE LIGHTS ON BATTERY-BACK UP
3RD TAILLIGHT PACKAGE	AMBER L.E.D. STROBE WARNING LAMPS
LASH RINGS	(18) TOTAL- 6-PER SIDE (BENT STYLE), 1-EACH SIDE FRONT OF DECK FLAT STYLE ON 45 DEGREE ANGLE, 1-EACH BOLSTER END (FLAT STYLE)
EXTENSION BRACKETS (OUTIGGERS)	12" SWINGING/REMOVABLE OUTRIGGERS WITHOUT PLANKS; INCLUDES 12" DOUBLE HOOK-ON OUTRIGGERS AT FRONT OF DECK
DECKING	1-1/2" APITONG FULL WIDTH
PAINT	GLOSS BLACK (2-PART URETHANE) STEEL PARTS TO MATCH PAINT COLOR



FLAG HOLDER SLOTS	IN BOLSTERS
REAR DECK	OPEN BOOMWELL WITH EXTRA LOW FIRST CROSSMEMBER AND WITH 1 1/2" APITONG OVER TIRES ONLY (NO COVER PLATE)
REAR SLOPE (MAIN TO REAR DECK)	21 DEGREE W/ OPEN CENTER
ROLLER STOP@REAR	4" HIGH, WIDTH OF MAIN BEAMS
FLAG HOLDER W/ THUMB SCREWS	1-PAIR FRONT CORNER OF DECK, 1-PAIR ENDS OF LIGHT PANEL
ALUMINUM STORAGE BASKETS BOLT-IN	(1) 2ND SECTION FROM FRONT OF DECK
AIR AND ELECTRICAL CONNECTIONS	FOR FUTURE FLIP/REMOVABLE AXLE

Etnyre reserves the right to modify pricing on all quotes and orders with material and labor surcharges as needed

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.