



Hale Trailer Brake & Wheel  
011001 - 011050

Product : , , , ,

**GVWR**

GVWR: Trailer to meet 68,000 Pound GVWR  
VIN PLATE: US - VIN Plate to Read in English (Standard)  
Product Type: HT Composite

**GEOMETRY**

Length - Exterior: 53'-0"  
\*\* Length - Interior: 52'-1.5" Nominal Lining To Lining  
Width - Exterior: 102.36"  
\*\* Width - Interior: 101.5" Nominal Lining To Lining  
Height - Exterior: 13'-6"  
Height - Interior: 110" Nominal  
Deck Height: Standard application  
Fifth Wheel Height: 47"  
King Pin Location: 36"  
Landing Gear Location: 107" from King Pin (+ 1"/-1/4")

**TIRES & WHEELS**

Tire Furnished: Factory Furnished  
\* Tire Manufacturer: Hankook TL01(G), Low Rolling Resistance Tire  
Tire Size: 295/75R22.5  
Wheel Furnish: Factory Furnished  
Wheel Material: All Steel Wheel  
Wheel Manufacturer: HT Standard (TCC 361)  
Wheel Size: 8.25 x 22.5, 5-Hand Hole (Steel, Inner & Outer)  
\* Wheel Finish for Steel: Hot Dip Galvanized.  
Wheel Finish for Aluminum: None (Due to All Steel Wheel Application)  
\* Valve Stem & Cap: TR-572 Valve Stem for use w/PSI

**UPPER COUPLER**

Approach Plate: 1/4" thick 80,000 Lb Yield - 6 Support Channels  
King Pin (BTM Main) Plate: 1/4" thick 80,000 Lb Yield  
King Pin & Manufacturer: Standard (Jost) AAR Cruciform King Pin  
\* Front Bottom Rail: Galvanized-Whole Upper Coupler section, w/ Pick-Up plate Striker Angle  
Upper Coupler Tube Qt'y: (1) Tubing Application - Joggled

**BODY/BASE**

Forward Crossmember: Steel Hat Shaped Upper Coupler to Landing Gear : 12" C/L  
Landing Gear Crossmember: 4" Steel I-Beams (80,000 PSI) : 12" C/L (5ea)  
Bay Area Crossmember: 4" Steel I-Beams (80,000 PSI) : 12" C/L  
Bay Area Crossmember Material: Steel Crossmember  
Running Gear C/M Size: 4" High  
Running Gear Crossmember: 4" Steel I-Beams (80,000 PSI) : 12" C/L with 8" C/L Last 3.4'  
Slider Body Rail (VT): 208" Rail Length

**FLOOR**

Upper Coupler Type: 3.40" Joggled with Exposed Coupler Top Plate (New STD)  
Floor Specification: 1.38" (1-3/8") Nominal Domestic Laminated Oak Hardwood  
Floor Ratings - VT: 18,000 lbs Rated Floor per TTMA- Standard HT Dry Van Floor Rating

'\*' = non-standard option

Floor- Assembly Method:	Wood Floor Assembly
Floor Screws:	(3) 0.31" Dia. screws per Board on I beams
Threshold-Finish:	Hot Dip Galvanized
Threshold Plate:	0.13" X 12" Deep Steel Diamond Plate w/ Screws and Nuts
Threshold-Application:	Standard Application

**FRONT**

Front Corner Radius:	4" Extruded Aluminum
Front Panel & Color - Dry:	0.05" Aluminum Prepainted White w/ natural color rivets
Front Corner Mat'l - Dry:	Extruded Aluminum
Front Posts:	(4) 2.5" Deep (16Ga) Steel Hats - Non AAR
Gladhands:	Phillips Qwik-E with Filters Control Line Only. Overlaid
Front Receptacle(7-Way):	Phillips 7-Way without Circuit Breakers, Split Pins with QCS plug
Front Receptacle(7-Way) - Options:	Phillips QCS Plug connector
Gladhand/7-Way Location:	Overlaid on Lower Roadside Front
* Corner Radius Protector:	(2) 0.125" X 12" Alum Diamond Plate Each Side at Top

**SIDE**

Side Material:	6.5 mm thick Composite Panel, 80K PPW Galv. Steel, Both Sides w/ natural color rivets
Side Posts:	14 Gauge Galv Steel 'A' Slotted Logistic Insets with Composite Panel color matching Outer Closure (For Composite)
Side Post Centers:	48" C/L Stiffener (Side Closure) - For Composite
Side Top Rail:	Side Top Rail for Composite Trailer
Side Bottom Rail:	Side Bottom Rail for Composite (STD)
* Skylight-General Spec.:	Cluster Sky Light Lens on side wall for 24" or bigger post pitch (Single lens on two panels, next to each other, for 16" or less post pitches.)
* Skylight-Quantity:	Total 5. Both Side Wall Panel. (3) on Roadside and (2) on Curbside
* Skylight-Location:	Composite Both Side Wall Panel Location from Front, Specifically on panels #5, #9 on C/S & #3, #7, #11 on R/S
Fasteners to Bottom Rail:	Standard Rivets to attach C/Members to the Side Bottom Rail

**REAR**

* Rear Frame:	Roll-Up Door, 6" Roll-Up Header (New Design)
Rear Door Opening Spec.:	Standard Application
Floor Level:	Door to be Flush with Floor (STD)
* Dry Van -WHITING RU:	Whiting Roll-Up Door. Premium Plate
Option - Door Install Instruct:	Standard Door Installation per Manufacturer's Recommendation
* Rear Underride Guard:	4" Tube Bolt on Assembly w/ Welded Perforated(Pooched) Horizontal. Rear Impact Guard (RIG) 30
Option - Horiz Member/Other:	Construction of two pieces standard stitch welding
Underide Bolt Spec.:	Zinc plated bolts & nuts - Standard
Dock Bumper:	Pair 3" X 6" Mold Bolted Bumper
Rubber Bumper Location:	Inboard of Light Protector Bars (Standard)
* Track Protector:	12Ga x 36" High Galvanized Steel Roll-Up Door Track Protector

**LIFT GATE**

**ROOF**

Roof Panel:	0.040" Aluminum
Roof Bow:	16 Gauge Galvanized Steel Anti-Snag
Roof Bow Centers:	24" Centers Full Length

**LINING/SCUFF**

Front Lining:	0.25" Top and 0.5" Bottom plywood Mounted to Front Posts Full Height
* Base Side Scuff:	6.5" High Integral Alum (Composite STD) with Additional scuff (Plastic, Corrugated or Wood)
* Additional Side Scuff:	18Ga x 6.5"H Corrugated Steel Butted to Intergral Aluminum
* Front Scuff:	0.63" x 12" High White Recycled Plastic Mounted Over Lining to Front Posts (Overlaid)

**LANDING GEAR**

L/Gear Spec.:	Jost HT421.G3.17.157 5 Year Warranty Full HDG
L/Gear Mt'g Method:	Inboard Mounting (Standard)
L/Gear Shoes:	10" X 10" RCF (Removable Cushion Foot) Low Profile
L/Gear Ground Clearance:	Nom. 12" Ground Clearance
L/Gear Mt'g Bracket:	Hot Dip Galvanized Large Wing Plate
L/Gear Crank Handle:	Roadside
L/Gear Options:	None (HT STD)
L/Gear Cross Brace Design:	HT Standard Cross Brace attachment Design

#### RUNNING GEAR

Bogie Type:	Sliding Tandem(2) Axle Bogie
Axle Spacing:	49" Axle Spacing
Axle ABS System:	Tandem Axle w/2S1M ABS System
Bogie & Axle Location:	Location to be Sliding Tandem Axle for specified slider Length w/Stop Bars @ Front & Rear
Option-Related Bogie Stopper Feature:	STD plug stopper
Susp. Manufacturer:	Hendrickson
Suspension Capacity:	Standard Duty
Hendrickson Susp. Specification:	Hendrickson Vantraxx HKANT40K Air Ride
Surelok (Anti-Dock):	Surelok (Anti-Dock) Installed
Locking Pin Mechanism:	Air-Assist Pin Puller or Quik Draw
Susp. Sub-Frame:	Hendrickson K-2 STD Duty
Type of Susp Spring:	Air Bag
Spring Specification:	Air Bag
Axle Supplier:	Hendrickson
Axle-General Spec.:	Axle - Tandem (2) Axle included in Suspension (For 2S1M or 2S2M System)
Axle-Track Length:	77-1/2"
Axle-Spindle Type:	Tapered Spindle
Brake Lining Size:	16.5" X 7"
Brake Lining Spec.:	Hendrickson Extended Service (Abex-3030-197)
Brake Control System:	2S/1M Wabco ABS
Spring Brake Control:	Sealco 110500 Springbrake Priority
Brake Cont-Hose & etc.:	Standard Air Line & Hose Application (US&Canada)
* Slack Adjuster Spec.:	Wabco Auto-5.5", 28 Spline EasyFit (No Grease)
* Brake Chamber Spec.:	Wabco Premium Chamber
* Stroke Length:	3" Long Stroke Length
Hub Specification:	HT Standard (KIC) 10 Stud Hub Piloted Outboard Iron Hub
Drum Specification:	HT Standard (KIC) Cast Drum
Hub/Drum-Opt(Nut&Other):	Standard
Bearing Specification:	Stemco
* Lubrication Spec.:	Chev Delo (Syn) Grease
* Wheel Seals Spec.:	Stemco Discover Seals, Hub Cap included in tire inflation system, Pro-Torq Nut
* Tire Inflation Spec.:	Hendrickson Tire Maax Inflation System for Undressed Axle (This kit include Hendrickson Hub Cap for TireMaax)
Tire Inflation Pressure:	100 PSI
* Tire Inflation Lamp Location:	Indicator PSI Light at Roadside Mounted over corner radius. (STD location)
* Tire Inflation Lamp Spec.:	33 Series Lamp

#### ELECTRICAL

Harness-General Spec.:	Molded Color Code Phillips Harness with QCS Plug
Harness-Special Feature:	Manufacturer's Standard Feature
Front Light:	(2) Trucklite 33275Y LED PC Rated Mounted with Grommet
* Rear ID Header Light:	(5) Vision CL11120R3 LED PC Mounted with Grommet (Dual Function)
* Rear ID-Special Feature:	Dual Function Rear Header Lights - 3 Lamps at center with Marker & Stop functionality, 2 Lamps outboard with Marker & Turn functionality
Rear Side Marker Type(Shape):	Mini Button Style Lamp

Rear Side Marker Detail Spec: (2) Trucklite 33275R LED PC Rated Flush w/ Grommet 33725 w/ anti-theft hardware  
Rear Side Marker MT'G Location: Mounted on Standard Location on Rear Corner Post - HT STD  
S/T/Tail Light-Quantity & Type: (4) Trucklite 40 or 44 Series (Round Style) or Equivalent  
S/T/Tail Light-Detail Spec: (4) Trucklite 44322R LED (Super 44 Grey) Flange Mounted w/ Stainless Steel Rivets  
Main Mid-Turn Light: Install the Mid turn lamp  
Mid-Turn Mounting Method: Mounting Bracket  
\* Main Mid-Turn Light-Detail Spec: (2) Trucklite 60272Y LED Gray Flange Mounted with Stainless Steel Rivets & Anti-theft brackets  
ABS Light Detail Spec: (1) Trucklite 33275Y LED PC Rated w/ Grommet 33725 w/ anti-theft hardware  
ABS Light MT'G Location: Mounted on Standard Location on Rear Corner Post - HT STD  
License Light: (1) Trucklite 33010C LED  
Option Related Harness/Wiring: Standard  
Electrical Related Regulation: Standard Application

**MARKING/DECALS**

HT & Product Type Decal Package: Hyundai Logo & Product Type Decals Application(For not having pre-painted white panels for side/door/front, Apply white HT Corporate decals)  
Decal Package: Factory Furnished Hyundai Information & Regulatory Decal Package with FMCSA Specified in Notes  
Decal Opt 2-Decal Location: Standard Application  
Decal Opt 3-Decal Installation: Standard Application  
Conspicuity Vendor: Avery  
Conspicuity Markings: Hyundai Standard Conspicuity with Logo Applied to Side Bottom Rail  
License Plate: Temporary For Delivery. Fasten On HDG Mounting Plate  
License Plate Brk't Install: Standard Install Location - Roadside Below Door Sill  
Furnish Document Holder: Factory Furnished  
Document Holder Detail Spec: (1) Phillips 16-802  
\* Document Holder/Manifest Loc.: Overlaid on Lower R/S Front. 18" from the bottom of the front sheet between the front post & corner radius on the roadside

**PAINT/FINISH**

\* Upper Coupler Finish: Galvanized-Whole upper coupler section  
\* Crossmembers Finish: HDG : ALL Steel Crossmembers including Hat C/M, L/G & Bogie Area (Except any Aluminum)  
\* Axle & Components Finish: Black Undercoating  
\* Susp. Sub-Frame Finish: Black Undercoating  
L/Gear(K-Bracing) Finish: Hot Dip Galvanized  
\* L/Gear(Upper Leg) Finish: Hot Dip Galvanized  
Rear Frame-Finish: Hot Dip Galvanized  
Rear Frame-Paint Color: None (For Galvanized or Stainless Steel)  
Rear Underride-Finish & Spec.: Hot Dip Galvanized & Welded Horizontal Member  
Rear Underride-Paint Color: None (For Galvanized or Stainless Steel)

**MISCELLANEOUS**

Mudflap Provider: Factory Furnished Mudflaps  
Mudflap Specification: 24"x30" White Plain Plastic with Hyundai Logo  
Mudflap Mounting Loc.: Suspension Frame  
Mudflap Mounting: STD Location w/ H.D Washer Retainer  
\* Lift Pad Spec.: Install HT Occasional use lift pads for delivery, with HYUZ decals

**DISCLAIMER**

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.