

Hale Trailer Brake & Wheel A011051-A011052



VIN: 001703-001704

20ART

20 Ton Tandem Air Tilt/Air Ramp

Tags

Base Weight: 11,020

TRAILER		
	Overall Length	<u>38 ft. 6 in.</u>
	Overall Width	102 in.
	Weight lbs +/- 2%	12381, including options
	A-Frame	6 ft. 11 in. Hi-Tensile Cold Formed Wide Flange Beam
	Hitch	3 in. pintle eye, adjustable 5 position 17 in. to 28 in.
DECK		
	Deck Length	<u>25 ft.</u>
	Loaded Deck Height	34 in.
	Main Frame	Hi-Tensile Wide Flange 14 in. @ 26
	Cross Members	Hi-Tensile 6 in. Channel @ 8.2
	Side Rail	Hi-Tensile 8 in. Channel @ 11.5 open on inside
	Air Tilt Deck	4 Air Bags
	Floor	1 3/8 in. x 7 in. Keruing Shiplapped
	Landing Gear	Dual Holland Mark V 2 Speed
SUSPENSION/	/AXLES	
	Axles	25,000 lbs Capacity 77.5 in. Track
	Spread	49 in.
	Suspension	Hutch 9700 spring ride
	Alum Air Tank	*NPO*: c/w drain plug and cable
	Brakes	Quick Change 12 1/4 in. x 7 in.
	Brake Chamber	#3030, All Axles
	Air Brake System	2S/1M
	Bearings	Oil Bath
	Slack Adjusters	Automatic
	Hubs & Drums	8 Stud Unimount C / W Cast Drums
	Tires	235/75R17.5 16 ply
	Wheels	Alum. Wheel Pkg. 17.5 (4 steel, 4 polished)
BEAVERTAIL		
	Length	6 ft. @ 6 degree slope, Planked in
RAMPS	-	
	Length	*NPO*: 45 in. x 96 in. Air Operated Planked
	Width Extension	*NPO*: No more than 2 in. Between ramps
	Brackets	*NPO*: To hold ramp brace when not in use, 1 per side
GENERAL SPE	CIFICATIONS	
	Electrical System	Modular, Vapor Proof GROTE Ultra Blue
	Lights	LED CMVSS 108 / FMVSS 108
	Front Connector	SAE J560 7 Pin
	Finishing	Preparation by Steel Shot Blast, Commercial / Industrial Topcoat, Oven Baked
	Color	Black
	Mudflaps	1 set of BWS at rear
	Toolbox	Full A Frame mounted with solid bottom and cover
	Load Securement	8 pair of D-rings: 7 pr on main deck, evenly spaced, 1 pr on top of main beam at headboard
	Fenders	3/16 in. deck plate
	Ladder	*NPO*: Ladders; 1 step at front on driver's side

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.