



## Hale Trailer Brake & Wheel

A011104-A011105

VIN: 072062-072063



### Trailer Model:

**Kalyn Hydraulic Sliding Axle (KHSA) 2 Axle, 40 Ton, 50' Model**

<u>2 Axle, 40 Ton, 50' Model</u>		<u>Standard Equipment</u>	
Net Capacity:	40 Tons	80,000 lbs Distributed in 50 ft, 50,000 lbs Concentrated in 10 ft	
Nominal:	50 feet OAL	Kingpin to center of rear axle 40 feet in Transport Mode	
	8 feet 6 inches Wide	Dump angle 16 °	Loading angle 7 °
<b>GOOSENECK:</b>		<b>SUSPENSION:</b>	
10'-8" Gooseneck Length (48' & 50') / 11'-6" (53')		25,000 lb nominal capacity with Oil seals, 5/8" wall, tapered spindles	
48" Loaded 5th Wheel Height, 18" Kingpin Setting		50" axle spacing 71" track	
86" Swing Radius (48' & 50') / 96" Swing Radius (53')		12-1/4" x 7-1/2" Brakes ABS Module: 2S1M	
20,000# Planetary Winch With Air Clutch; 100' of 5/8" Cable		Auto Slack Adjusters and Spring Brakes on all Axles	
Work lights on the winch 2 Tool compartments		6.75 x 17.5 Hub Piloted Disc Wheels	
Wet Kit: Trailer Operation; 3/4" Hydraulic Couplings		235/75 R 17.5 16PR Tires Manual Dump Valve	
Integrated Tool Box in Neck W/ Stainless Hinges and Alum. Door		Suspension: Ridewell or Equivalent Air ride Air Ride	
2-Speed Landing Gear , Crank Handle Roadside		Alignment Bracket for Sliding Suspension	
<b>DECK:</b>		<b>GENERAL:</b>	
Nominal Deck Length: 39.34 feet		12 Volt System with 7 way Sealed Harness	
Nominal Deck Width: 102 in		DOT Rubber Mounted Sealed Beam LED Lights	
Loaded Deck Height: 37 in		Epoxy Primer & Black Polyurethane Paint	
4 Beam design - 100,000 psi yield flanges & 80,000 web minimum		2 Function Wireless Remote for Winch	
14" tall main beams and 15" tall side rails		Heavy Duty DOT Approved Bumper	
4" I-beam cross members on 9" Centers, 1-3/8" Apitong Deck (full width)		Red & White Conspicuity tape KS Mud Flaps	
Double Key Hole Chain Slots in Upper Flange on 36" Centers		3 LED marker lights each side including mid turn	
Double Key Hole Chain Slots Along Center of Deck on 36" Centers		Strobe light with toggle switch on rear	
Reinforced Rear Approach Plate with 6 Chain Slots			
Cable Roller Centered at Front of Lower Deck			

  

<u>Kalyn Hydraulic Sliding Axle (KHSA)</u>		<u>Optional Equipment</u>	
Models		<input checked="" type="checkbox"/> Aluminum Wheels OS (Polished) all Axle	
<input checked="" type="radio"/> 2 Axle, 40 Ton, 50' Model		<input checked="" type="radio"/> OEM 235/75 R 17.5 16PR Tires	
		<input type="radio"/> Michelin 245/17.5 Tires	
Options		<input checked="" type="checkbox"/> AirWeigh Load Scale	
<input checked="" type="checkbox"/> 6 Function Wireless Remote		<input checked="" type="checkbox"/> Tire Inflation	
		<input checked="" type="checkbox"/> 74,000 lb Dock Levelers (Independent Controls)	
		<input checked="" type="checkbox"/> Central Lube - 18 Point Manual	

Estimated Weight of the Equipment with the options :

18,402 lbs.

± 3% For trailers other than standard specification, weight and dimensional drawing will be provided by plant after order is received and accepted.

#### DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.