



Hale Trailer Brake & Wheel

A011208-A011213

VINS: 61522-61527

Revolution 52 Alum Flat 48' Wide Spread Air (Model: HAR5212WSA)

Length / Width: 48 feet x 102 inches

Suspension Type: Wide spread air

Frame Rating: 80,000 lbs distributed - 52,000 lbs concentrated in 4 feet- GAWR and tire ratings determine legal payloads

Flooring: Knurled extruded 3-1/8 aluminum, **StirLITE Friction Stir Welded Floor** with 2 wood nailer strips; Heavy wall extrusions in single coil area; Heavy wall extrusion at rear

Side Rails: Exclusive **Revolutionary RASR Rail Technology** -- one piece routed aluminum designed for strength and impact

Stationary Chain Cargo Tie Downs: 15 pair - recessed in siderails

Stake Pockets: Routed Aluminum on 24 inch centers (2 load securement openings in between stake pockets)

Rubrail: Integrated with side rail

Main Beams: Extruded aluminum - 8.25 inch flange

Kingpin: 30 inches

Loaded Fifth Wheel Height: 49 inches

Landing Gear: Jost AX100G19 **ALUMILIGHT Aluminum Landing Gear** with forward & rear bracing

Bulkheads: None standard

Number of Axles: 2

Axle Spindle: Tapered

Brakes: Spring brakes, auto slacks, Aluminum air tank

Air Line Filters: (2) Meritor In-line type installed

ABS: 4S/2M - no cable or tool

Axle Spread: 122 inches - set at rear

Hub and Drums: 10-hole hub-piloted with outboard cast drums - STANDARD

Wheel Ends: Grease in hubs - *** 5-year wheel end warranty ***

Wheels: **22.5 x 8.25 aluminum LvL One buffed wheels**

Tires: **11R 22.5 14PR economical OEM standard tires**

Tire Inflation System: None standard

Suspension Detail: Hendrickson AANT23K Intraax air ride

Auto Glad Hand Dump: Installed

Electric Dump Valve: Wired to 7-way auxiliary socket to dump rear axle

Air Lift: None standard

Front Corners: Tapered

Electrical System: LED: 5 Lights/Side; Rear with 3 4-inch Round Lights/Side, 3 Round Lights Center Cluster

Other Electrical Specifications: 4 way socket on rear with one hot/one ground pin for wide load and strobe light connections

Paint: Black urethane on steel parts with Revolution decals - STANDARD

Conspicuity Tape: Per NHTSA specs - installed in recess on rubrails

Bumper: Bolt-On; Meets underride requirements

Mudflaps: 2 sets OEM standard; Spring loaded brackets behind front axle

Spare Tire Carrier: None standard

Winch Track: Dual full-length integrated aluminum -- double L design

Sliding Winches: 12 standard; 6 each side; sliding rope hook/ winch strap hook retainers - STANDARD

27' Winch Straps: None standard

30' Winch Straps: None standard

Sliding J-Hook for Ring vs. Flat Hook on 4" Strap: None standard

Dock Bumpers: 1 pair rubber on rear

Hubodometer: None standard

Registration Holder: Install registration holder - OEM standard

Tool Box: None standard

VIN Plate: Bilingual US/Canadian VIN plate

Please Note: Price includes commodity surcharges

Unit Numbers & Decals: Not available

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.