



Hale Trailer Brake & Wheel

A011241-A011246

VINS: 001723-001728



20NTT

20 Ton Tandem Non Tilt

Tags

Base Weight: 7,960

TRAILER

Overall Length 34 ft. 8 in.
Overall Width 102 in.
Weight lbs +/- 2% 9093, including options
A-Frame 6 ft. 11 in. Hi-Tensile Cold Formed Wide Flange Beam
Hitch 3 in. pintle eye, adjustable 5 position 23 1/2 in. to 32 1/2 in.

DECK

Deck Length 21 ft.
Loaded Deck Height 34 in.
Main Frame Hi-Tensile Wide Flange 14 in. @ 22
Cross Members Hi-Tensile 5 in. Channel @ 6.7
Side Rail Hi-Tensile 7 in. Channel @ 9.8 open on inside
Floor 1 3/8 in. x 7 in. Keruing Shiplapped
Landing Gear *NPO*: Dual Holland Mark V 2 Speed

SUSPENSION/AXLES

Axles 25,000 lbs Capacity 77.5 in. Track
Spread 49 in.
Suspension Hutch 9700 spring ride
Alum Air Tank *NPO*: c/w drain plug and cable
Brakes Quick Change 12 1/4 in. x 7 in.
Brake Chamber #3030, All Axles
Air Brake System 2S/1M
Bearings Oil Bath
Slack Adjusters Automatic
Hubs & Drums 8 Stud Unimount C / W Cast Drums
Tires 235/75R17.5 16 ply
Wheels 6.75 x 17.5 Steel Disc - Painted White

BEAVERTAIL

Length 6 ft. Beavertail, Planked

RAMPS

Length * 38 in. x 76 in. Wood Filled Air Operated Ramp
Ramp Support *NPO*: Ramp Support
Brackets *NPO*: To hold ramp brace when not in use, 1 per side

GENERAL SPECIFICATIONS

Electrical System Modular, Vapor Proof GROTE Ultra Blue
Lights LED CMVSS 108 / FMVSS 108
Front Connector SAE J560 7 Pin
Finishing Preparation by Steel Shot Blast, Commercial / Industrial Topcoat, Oven Baked
Color Black
Mudflaps 1 set of BWS at rear
Toolbox Full A Frame mounted with solid bottom and cover
Load Securement 7 pair of D-rings: 6 pr main deck, evenly spaced; 1 pr on main beam at headboard
Fenders 3/16 in. deck plate
Ladder *NPO*: Ladders; 1 step at front on driver's side
GVWR Rating is based on standard configuration and a 15% Tongue weight distribution

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.