



Hale Trailer Brake & Wheel A011287-A011291 VIN: 37831-37835

Base Model: DF53x102 3 Axle 100K Serial #: 37831 - 37835 components description CAPACITY Heavy Duty Beam Package - 100,000 lbs. GVWR (80,000 in 10' Span Closed) OVERALL LENGTH 53' - Base Weight 12,900# UPPER DECK LENGTH 10'6" LOWER DECK LENGTH 42'6" **OVERALL WIDTH 8'6"** KING PIN SETTING 24" - Tapered Front **UPPER COUPLER PLATE 1/4" UPPER COUPLER HEIGHT 48" BULKHEAD None** MAIN FRAME 26"-PreCamb.I-Beams-(100K Pkg 1/2"x 5" Top & 3/4" x 5" Bottom & 1/4"Web & TRP) SIDE RAILS 6" - 6.5# Per Foot TOP DECK FLOOR SILLS 4" Steel I-Beam - 18" O.C. LOWER DECK FLOOR SILLS 4" Steel I-Beam 12" O.C. HD Pkg **COIL HAUL PACKAGE None** FLOOR DECKING 1-1/8" Apitong WINCHES 12 STRAPS None WINCH TRACK Steel Slide Entire Length of Drivers Side LANDING GEAR Two Speed SUSPENSIONS Air Ride - Hendrickson Intraax - 23K - 3 Axles SUSPENSION LOCATION Set at Rear most Position - 32.5" Center of Rear Axle to Rear of Trailer AXLES (3) 23K Capacity - Type 30 Chambers - Auto Slacks - ABS - 22.5 Tires AXLE SPACING 61" Spread LIFT AXLE Air Lift 1 Axle - Rear (+195#) DUMP VALVE Manual-Position In Front of 1st Axle D/S No Box-Dump All Axles(+5#) SCALES None PARKING BRAKES All Axles ABS SYSTEM Wabco ABS system 4S/2M **DUST SHEILDS None** WHEELS Disc - Hub Piloted - 22.5 - Steel (672#) TIRES 255/70R 22.5 - 41" Loaded Deck Height - Double Coin TIRE INFLATION SYSTEM None ANTI-SAIL MUD FLAPS Behind Rear Axle STAKE POCKETS 24" O.C. Sides & 4 Across Front, 5 Across Rear **PIPE SPOOLS Double** RUB BAND STEEL 3/8" X 2-1/2" Recessed for DOT Tape **OILFIELD FRONT None** DOCK BUMPERS Rubber Inboard OILFIELD REAR NECK None **OILFIELD - PIN POCKETS None DECK ROLLERS None** TAILROLLERS None CARGO TIE DOWN None CONTAINER TWIST LOCKS NONE TIRE CARRIERS Tire Carrier Positioned In Front of Main Beams Between Landing Gear TOOLBOX MATERIAL None **TOOLBOX TYPE None TOOLBOX LOCATION None** LIGHTS Grote Ultra Blue Sealed Wiring Harness- 2 Micros Per Side & Mid Turn-3/3/3 Rear **CUSTOM LIGHTS None** PAINT Mack Green HSX952865

DISCLAIMER