



Hale Trailer Brake & Wheel
 A011313-A011314
 VIN: 001742-001743



42ET2X	
42 ft. Tandem	
Equipment	
	Base Weight: 12,100
TRAILER	
Overall Length	42 ft.
Overall Width	102 in.
Weight lbs +/- 2%	13336, including options
GOOSENECK	
Coupler	Weld in King Pin
Coupler Plate	5/16 in. Hi-Tensile, 48 in. Height
Coupler Location	18 in.
Length	10 ft. 6 in.
Cross Members	Hi-Tensile 4 in. Jr. I-beam @ 16 in. O/C
Swing Clearance	83 in.
Floor	*NPO*: 1 3/8 in. Apitong
Web	1/4 in. Hi-Tensile
DECK	
Deck Length	25 ft. 7 in.
Loaded Deck Height	40 in.
Main Frame	3/8 in. x 5 in. Top and Bottom Flanges 100 KSI
Cross Members	Hi-Tensile Standard 4 in. I-beam @ 12 in. O/C on Lower Deck w/ Knee Braces
Side Rail	6 in. @ 8.2 Channel
Web	3/16 in. Hi-Tensile
Floor	*NPO*: 1 3/8 in. Apitong
Landing Gear	Dual 2 Speed
Load Securement	16, Pair of side mounted D-rings: evenly spaced
SUSPENSION/AXLES	
Axles	25,000 lbs Capacity
Spread	49 in.
Suspension	Ridewell RAR 260 U/S 6 1/2 in. Air Ride 25,000 lbs - includes air gauge and dump valve in enclosure
Brakes	16 1/2 in. x 7 in.
Brake Chamber	#3030, All Axles
Air Brake System	2S/1M
Camshafts	28 Spline Enclosed
Slack Adjusters	Automatic
Hubs & Drums	10 Stud, long Stud c/w Drums
Tires	255/70R22.5
Wheels	Alum. Wheel Pkg. 17.5 (4 steel, 4 polished)
Pressure equalization	*NPO*: 2, Crossfire Dual tire pressure equalization system
BEAVERTAIL	
Length	5 ft. @ 8 degree slope, Planked
Traction Bar	*NPO*: Traction Bar on the wood filled B/T
RAMPS	



42ET2X

42 ft. Tandem

Equipment

Base Weight: 12,100

RAMPS

Rear 38 in. x 76 in. Air Operated Self Cleaning
Front *NPO*: Alum. 5 ft. Long Self Cleaning to access Gooseneck, with under deck storage on Gooseneck

GENERAL SPECIFICATIONS

Electrical System Modular, Vapor Proof GROTE Ultra Blue
Front Connector SAE J560 7 Pin
Rear Connector 4 Pin Plug
Lights LED CMVSS 108 / FMVSS 108
Lights LED Light Enhancement Package (6 additional lights per side)
Finishing Preparation by Steel Shot Blast, Commercial / Industrial Topcoat, Oven Baked
Color Black
Mudflaps 1 set of BWS at rear
Fenders 5/16 in. heavy duty smooth plate fenders - WITH traction bars

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.