

Hale Trailer Brake & Wheel A011318-A011319 VIN: T10001-T10002

Model: Aluminum-ARA/3A

| Item | Description |
|----------------------|---|
| MODEL | ALUMINUM-ARA/3A |
| TANK CONSTRUCTION | ARA |
| CAPACITY | 9500 GALLONS |
| OUTAGE | 1 PERCENT (MINIMUM) |
| CODE | 49 CFR 173.247 |
| DESIGN PRESSURE | ATMOSPHERIC |
| VENTING | ASPHALT TYPE, LIGHT WEIGHT STYLE |
| TEMPERATURE RATING | 400 DEGREE |
| MATERIAL-BARREL | 5454-H32 ALUMINUM |
| SURGE PLATES | (2) ALUMINUM |
| COMPARTMENTS | ONE |
| CAPACITY MARKERS | 3-DISC |
| INSULATION | 4" FIBERGLASS, 1# DENSITY, NOT COMPRESSED |
| ALUMINUM JACKETING | 0.040" SIDE SHEETS/0.060" HEADS |
| REAR DISCHARGE VALVE | 6" VALVE W/ 3" LINE & CAMLOCK CAP. INCLUDES 3/4" PORT FOR WASHOUT CONNECTION. |
| FRONT PUMP-OFF VALVE | 3" VALVE W/ SWIVEL & INTERNAL LINE, OUTLET TERMINATING WITH A 3" CAMLOCK ADAPTER & CAP. INCLUDES 3/4" PORT FOR WASHOUT CONNECTION AND 8' HOSE TROUGH ON RH FRONT FENDER. |
| GATE VALVE | 4" AT REAR UNLOADING LINE |
| THERMOMETER | 3" DIAL IN WELL W/ PLEXIGLASS COVER |
| MANHOLE | 20" ASPHALT TYPE |
| MANHOLE PLATFORM | 4 SIDED, ALUMINUM |
| DEFLECTOR PAN | BENEATH MANHOLE |
| MANHOLE OVERFLOW | 2" EXTERNAL |
| HEATING SYSTEM | NONE |
| LADDER | ALUMINUM-CURBSIDE |
| WALKWAY | NONE |
| HOSE TROUGH | 20' ALUMINUM, CURBSIDE |
| TIRE CARRIER | NONE |
| FENDERS | ALUMINUM, FRONT & REAR WITH MUDFLAPS ON REAR FENDERS. MANUAL HOLDER ON FRONT ROADSIDE FENDER |
| LIGHTS | L.E.D. TYPE WITH ALUMINUM LIGHT BOXES @ REAR |
| GLAD HANDS | LOW MOUNT |
| BUMPER-SPLIT TYPE | WITH SLOPING OUTLET |
| CONSPICUITY MARKING | PER DOT REQUIREMENTS |
| UPPER COUPLER | ADJUSTABLE |
| LANDING LEGS | 2-SPEED, CURBSIDE CRANK WITH HORIZONTAL BRACE BETWEEN LANDING LEGS |
| LANDING LEGS | HEAVY DUTY LANDING LEG FRAME |
| LANDING LEGS | MARK V HEAVY DUTY |





| BOGIE | ALUMINUM |
|---------------------------------|--|
| SUSPENSION | INTRAAX AAT25K AIR RIDE TRIDEM W/MANUAL EXHAUST ON REAR CROSSMEMBER. |
| OIL SEALS | HXS EXTENDED SERVICE PACKAGE |
| AIR BRAKES | HALDEX DBLT, 25,000 LBS. RATING |
| ANTI-LOCK BRAKES | 2S/2M SYSTEM (2 SENSORS/2 MODULATORS) |
| AXLES | 25,000# BEAM RATING WITH HP BEARINGS, 77 1/2" TRACK |
| HUBS | DUCTILE IRON |
| ALUMINUM DISC WHEELS | ACCURIDE 10-HOLE, HUB PILOTED, STANDARD POLISH |
| TIRES | 11R22.5-H |
| AUTOMATIC TIRE INFLATION SYSTEM | AXLES PREPARED FOR TIREMAAX PRO, SYSTEM NOT INSTALLED |
| PAINT | STEEL PARTS ONLY-BLACK |
| CENTER PAINT BAND | 14" WIDE BAND-BLACK |
| PLACARD KIT | SLIDE-IN TYPE W/ " HOT" PLACARD, 4 SIDES |
| SAMPLE VALVE | 3/4" |
| HUBODOMETER | ON DRIVER SIDE REAR AXLE |

Etnyre reserves the right to modify pricing on all quotes and orders with material and labor surcharges as needed