



Hale Trailer Brake & Wheel

A011324-A011325

VINS: T10005-T10006

Model: Aluminum-ARA/3A



Item	Description
MODEL	ALUMINUM-ARA/3A
TANK CONSTRUCTION	ARA
CAPACITY	8500 GALLONS
OUTAGE	1 PERCENT (MINIMUM)
CODE	49 CFR 173.247
DESIGN PRESSURE	ATMOSPHERIC
VENTING	ASPHALT TYPE, LIGHT WEIGHT STYLE
TEMPERATURE RATING	400 DEGREE
MATERIAL-BARREL	5454-H32 ALUMINUM
SURGE PLATES	(2) ALUMINUM
COMPARTMENTS	ONE
CAPACITY MARKERS	3-DISC
INSULATION	4" FIBERGLASS, 1# DENSITY, NOT COMPRESSED
ALUMINUM JACKETING	0.040" SIDE SHEETS/0.060" HEADS
REAR DISCHARGE VALVE	6" VALVE W/ 3" LINE & CAMLOCK CAP. INCLUDES 3/4" PORT FOR WASHOUT CONNECTION.
FRONT PUMP-OFF VALVE	3" VALVE W/ SWIVEL & INTERNAL LINE, OUTLET TERMINATING WITH A 3" CAMLOCK ADAPTER & CAP. INCLUDES 3/4" PORT FOR WASHOUT CONNECTION AND 8' HOSE TROUGH ON RH FRONT FENDER.
GATE VALVE	4" AT REAR UNLOADING LINE
THERMOMETER	3" DIAL IN WELL W/ PLEXIGLASS COVER
MANHOLE	20" ASPHALT TYPE
MANHOLE PLATFORM	4 SIDED, ALUMINUM
DEFLECTOR PAN	BENEATH MANHOLE
MANHOLE OVERFLOW	2" EXTERNAL
HEATING SYSTEM	NONE
LADDER	ALUMINUM-CURBSIDE
WALKWAY	NONE
HOSE TROUGH	20' ALUMINUM, CURBSIDE
TIRE CARRIER	NONE
FENDERS	ALUMINUM, FRONT & REAR WITH MUDFLAPS ON REAR FENDERS. MANUAL HOLDER ON FRONT ROADSIDE FENDER
LIGHTS	L.E.D. TYPE WITH ALUMINUM LIGHT BOXES @ REAR
GLAD HANDS	LOW MOUNT
BUMPER-SPLIT TYPE	WITH SLOPING OUTLET
CONSPICUITY MARKING	PER DOT REQUIREMENTS
UPPER COUPLER	ADJUSTABLE
LANDING LEGS	2-SPEED, CURBSIDE CRANK WITH HORIZONTAL BRACE BETWEEN LANDING LEGS
LANDING LEGS	HEAVY DUTY LANDING LEG FRAME
LANDING LEGS	MARK V HEAVY DUTY



BOGIE	ALUMINUM
SUSPENSION	INTRAAX AAT25K AIR RIDE TRIDEM W/MANUAL EXHAUST ON REAR CROSSMEMBER.
AUTO LIFT FRONT AXLE	FRONT AXLE TO LIFT WHEN TANK IS EMPTY
OIL SEALS	HXS EXTENDED SERVICE PACKAGE
AIR BRAKES	HALDEX DBLT, 25,000 LBS. RATING
ANTI-LOCK BRAKES	2S/2M SYSTEM (2 SENSORS/2 MODULATORS)
AXLES	25,000# BEAM RATING WITH HP BEARINGS, 77 1/2" TRACK
HUBS	DUCTILE IRON
ALUMINUM DISC WHEELS	ACCURIDE 10-HOLE, HUB PILOTED, STANDARD POLISH
TIRES	11R24.5-H
AUTOMATIC TIRE INFLATION SYSTEM	AXLES PREPARED FOR TIREMAAX PRO, SYSTEM NOT INSTALLED
PAINT	STEEL PARTS ONLY-BLACK
CENTER PAINT BAND	14" WIDE BAND-BLACK
PLACARD KIT	SLIDE-IN TYPE W/ " HOT" PLACARD, 4 SIDES
SAMPLE VALVE	3/4"
HUBODOMETER	ON DRIVER SIDE REAR AXLE

Etnyre reserves the right to modify pricing on all quotes and orders with material and labor surcharges as needed

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.