



Hale Trailer Brake & Wheel  
A011358-A011363  
VIN: 022022-022027  
**XL SPECIALIZED TRAILERS**

**XL 70 HDG: Mini-Deck**

<b>OVERALL LENGTH</b>	53'
<b>OVERALL WIDTH</b>	102"
<b>CAPACITY</b>	70,000 LB DISTRIBUTED; 60,000 LB IN 16'
<b>WEIGHT +/- 3%</b>	20,850 LB
<b>GOOSENECK</b>	
<b>LENGTH</b>	11' FULL-WIDTH SCRAPER NECK
<b>KINGPIN SETTING</b>	16"
<b>SWING CLEARANCE</b>	86"
<b>5TH WHEEL HEIGHT</b>	49" W/ 5 VARIABLE RIDE HEIGHT POSITIONS
<b>DECKING</b>	1 1/8" APITONG DECKING FLUSH
<b>D-RINGS</b>	2 BENT D-RINGS PER SIDE- ONE PAN STYLE IN EACH CORNER
<b>HYDRAULICS</b>	13 HP HONDA POWER UNIT WITH ALUMINUM COVER - DUAL HYDRAULICS
<b>MAIN DECK</b>	
<b>LENGTH</b>	3 BEAM DESIGN
<b>LOADED DECK HEIGHT</b>	33' WITH 32' 6" OF CLEAR DECK
<b>DECKING</b>	12" W 4" GROUND CLEARANCE STEEL DECKING BETWEEN MAIN BEAMS WITH DURABAK 1 1/8" APITONG DECKING, FLUSH BETWEEN MAIN BEAMS AND OUTER BEAMS
<b>CROSSMEMBER</b>	4" JR. I-BEAM ON 18" CENTERS
<b>SIDE BEAMS</b>	FAB I-BEAMS 8"
<b>D-RINGS</b>	12 BENT D-RINGS PER SIDE- 24 TOTAL CHAIN DROPS ON 18" CENTERS
<b>OUTRIGGERS</b>	NONE
<b>RAMPS</b>	TAPERS TO 4"
<b>REAR DECK</b>	
<b>LENGTH</b>	9'
<b>LOADED DECK HEIGHT</b>	40"
<b>AXLES</b>	( 2 ) 25,000 NOMINAL, 77 1/2" TRACKING
<b>SUSPENSION</b>	HENDRICKSON / 25,000 AIR
<b>AXLE SPACING</b>	54"
<b>ABS</b>	4S2M WITH SPRING BRAKES ON 2 AXLES
<b>TIRES</b>	255 / 70R / 22.5
<b>WHEELS</b>	8.25 X 22.5 STEEL INSIDE, ALUMINUM POLISHED OUTSIDE DISC WHEELS
<b>BRAKES</b>	16 1/2" X 7"
<b>DRUMS</b>	HUB PILOT / OUTBOARD DRUMS
<b>ELECTRICAL</b>	12V SEALED GROTE SYSTEM WITH 3 TAIL LIGHT ALUMINUM PACKAGE 4" AMBER STROBE WITH SWITCH TO MAKE 3 STT
<b>DECKING</b>	1 1/8" APITONG DECKING, FLUSH
<b>D-RINGS</b>	2 BENT D-RINGS IN TAIL CHANNEL - ONE PAN STYLE IN EACH CORNER
<b>PAINT</b>	BLACK
<b>ADDITIONAL</b>	
	LIQUID FILLED AIR GAUGE WITH CHART 4-WAY PLUG AT REAR MANUAL RIDE HEIGHT CONTROL LED LIGHTING FRAME REINFORCEMENT, AIR, ELECTRIC AND BRACKETS FOR FLIP AXLE RAISE AND LOWER VALVE

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.