



# Hale Trailer Brake & Wheel

A011377-A011378

VIN: 072055-072056



**Trailer Model:** *VersaMAXX* *Extendable 53 Feet to 58 Feet Model*

<u>VersaMAXX</u>	<u>Extendable 53 Feet to 58 Feet Model</u>	<u>Standard Equipment</u>
<p>Net Capacity: 50 tons concentrated in 16 feet</p> <p>Nominal: OAL 53 feet Closed to 58 feet Open 8 feet 6 inches Wide</p> <p><b>GOOSENECK:</b></p> <p>Hydraulic Detachable Gooseneck 5 Position Adjustable Neck 50" Loaded 5th Wheel Height, 15" Setting, 2" King pin Narrow neck, Chain storage rack under gooseneck 2" King Pin 84" Swing Radius PTO powered: two main &amp; one lift arm cylinders Hydraulic Controls in a separate covered box Front lugs provisioned for flip neck Hydraulic connection on the side of neck for winching operation</p> <p><b>DECK:</b></p> <p>Nominal Deck Length: 22.5 feet Closed to 27.5 feet Open Loaded Deck Height: 22 in 6 in Loaded Ground Clearance 4 Beam design - 100,000 psi yield flanges &amp; 80,000 web minimum All 4 Beams same height &amp; Beams are tapered like Paver Models I-Beam Cross members on (approx.) 24" Centers Junior I-Beam Cross members alternating - Outside bay only 1.5" Nominal Apitong Decking - Full Width, Secured by Floor Screws D Rings: 14 Pairs(6 Deck, 1 Bolster, 1 Rear CM, 3 Porch, 1 Trans.) Tie Downs &amp; Chain Slots : Top Flange Outer beams 24" centers Outriggers: 10 Pair Swing out + 1 Pair Heavy duty hook on at front Front Flip Ramps (removable) for loading Two 6 ft AL. Bus Ramps (Front/Rear Lugs included), Stored on neck</p>		<p><b>REAR SECTION:</b></p> <p>Rear Deck 19 ft 7 in, Open Boom trough, brackets for Oversize Load Sign Axles: Three 5" round, 5/8" wall 25000# nominal capacity Suspension: Ridewell or Equivalent air ride with Oil Seals 60" axle spacing, Open wheel wells, axle chains with cut off valves Rear axle equipped with air lift, Auto Slack Adjusters 12-1/4" x 7-1/2" Air, Parking Brakes 1st &amp; 2nd Axles, ABS: 2S1M Hub: 8 Stud, Hub Piloted, Long studs, Cast Drums 235/75R17.5, 16PR (Low Profile) radial tires Aluminum Outer &amp; Steel Inner Wheels Tire inflation system 5 position ride height control with dump valve &amp; Air Gauge Air Ride Suspension With 5 Position Ride Height 10 Apitong riser boards installed on bolsters &amp; porch</p> <p><b>GENERAL:</b></p> <p>12V System with 7 way, Modular Harness, LED Sealed Beam Lights Strobe light package with toggle switch on rear Epoxy Primer &amp; Black Polyurethane Paint Flag and Flag Holders - 2 Pairs - front deck and rear of trailer Mid-Turn Signal/Clearance Light Tool Tray: 4' expanded metal at front of deck (approx.) Red &amp; White Conspicuity tape and KS Mud Flaps Winch: Two 20,000 lb. planetary hydraulic on neck &amp; rear deck 100' of 5/8" wire rope &amp; shackle, fairing rollers &amp; cable tensioner Four function wireless remote (controls both winches) LED-Work lights on both winches with covered toggle switch Battery Back-up w/ charger on rear for disconnected neck operation</p>

Models

VersaMAXX Optional Equipment

**Extendable 53' to 58' Model**

OEM 235/75R17.5, 16PR tires

Options

**AirWeigh Load Digital Scale**

Estimated Weight of the Equipment with the options : **25,105 lbs.**

± 3% For trailers other than standard specification, weight and dimensional drawing will be provided by plant after order is received and accepted.

**DISCLAIMER**

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.