

Hale Trailer Brake & Wheel A011462-A011463 VIN: P2590-P2591



Detailed Specifications

Detailed Specifications	VT40NE*024E42\
RENEGADE XN20 (Model: RENL	
	General
SKU	RENLXT40NF*834542
Capacity	40 Tons in 16-foot Length - GAWR and GVWR Determine Legal Loads
Length (Trailer Only)	55 feet 1 inches (closed); 89 feet 6 inches
Width	8 feet 6 inches
Compatibility	Designed to Accept Optional Third Flip Axle
Accent Package	Stainless Steel Bumper Insert
Weight	Est. Configured Weight: 24837# +/- 3%
	Gooseneck
Gooseneck Design	Narrow Hydraulic Removable Non-Ground Bearing - Swing Radius of 102 inches (11 feet 11 inches overall Gooseneck Length) Set Up for Wetline Operation
Loaded Fifth Wheel Height	50-inch Nominal Loaded Fifth Wheel Height with 5 Ride Height Positions
Power Source	Set Up for Wet Line Operation
VIN Plate	Bilingual VIN Plate
Registration/Document Holder	Install Registration/Document Holder
-	Deck
	All Main Longitudinal Members Fabricated with 100,000# Minimum Yield Steel Flanges with 50,000#
Framework	Webs
Deck Design	Flat Level Deck Design
Deck Length	34 feet 0 inches Clear Deck Length (closed) - 60 feet 0 inches (open) ** Trailer Overall Length is 55 feet**
Loaded Deck Height	20 inches with 6 inches Ground Clearance
Crossmembers	On 24 inch Centers
Deck Lock	First 5 Spaced Approx. 12 inches; Others Every 50 inches
Flooring	1 3/8 inch Nominal Wood (Full Width)
Recessed Floor Mounted D-Ring Package	None
Front Ramps	None - Front of Deck Sloped Top Down to Assist in Loading with Traction Cleats
Extension Brackets	Outriggers - 17 Pair - 34 Total Removable Swing Type, 1 Pair - 2 Total Removable Hook-On Type
	Rear Bridge: General
Front Bogie Ramp	Sloped Steel Bogie Ramp (Full Width)
Mini Boom Trough and Traction Cleats	None None
Deck to Bogie Connection	Fixed
Covered Rear Bogie	Rear Bogie Platform with 1 1/8 inch Wood Floor
Rear Bogie Height	41 inches
Connections for Future Axle Attachment	Air and Electrical Connections to Go Along with Connecting Ears
7.1.3.6.1.1.	Rear Bridge: Axles
Number of Axles	2
Axle Capacity	25,000 lb. Nominal Capacity Per Axle - NOTE: GAWR Determined By Suspension Type, Brakes, Tires and Other Components
Axle Spread	54.5 inches (Between Axles)
Spring Brakes	Spring Brakes (2 Axles)
Dust Shield	None
Hubodometer	None
	Rear Bridge: Suspension
Suspension	Air Ride with Automatic Controls
Suspension ABS	
Chain Lift	4S/2M System without Diagnostic Tool and Cable Chain Lift On First Axle
Ride Height Control	Automatic/Manual Raise/Lower Control
Liquid Filled Gauge	Included
Load Scale	None



Detailed Specifications

Wheels and Tires		
Wheels	8.25 x 22.5 LvL One Buffed Outside/Steel Inside - Hub-Piloted	
Tires	255/70R 22.5 H Ply OEM Standard	
Inflation	None	
	Lighting	
Electrical System	DOT Sealed Beam and Harness with LED Lights and 4-inch Flush Mounted Battery Powered Amber Strobes	
Tail Lights	3 Tail Light Package	
Marker Lights	7 Marker Lights Per Side Including Mid-Turn	
Special	Not Available on This Model	
Electrical Receptacle	J560 7-Pin Connector	
	Paint	
Paint	Fontaine Black Polyurethane Enamel	
	Miscellaneous	
Lash Rings	12 Pair - 24 Total	
Flag Holders	2 Pair Flag Holders	
	Additional Options	
Flip Axle	None	
Dust Shields on Flip Axle	None	
RENEGADE XN20		



RENEGADE XN20 Base Model (Note: Options not shown)



