

## Hale Trailer Brake & Wheel A011598-A011603 VIN: 5A2629-5A2634



**Detailed Specifications** 

Detailed Specifications	
MAGNITUDE 55H DSR 26 (Mode	· · · · · · · · · · · · · · · · · · ·
	General
SKU	MAG55H***D*826543
Capacity	55 Tons in 12-foot Length with 4 Axles Close Coupled or Single Axle Stinger - GAWR and GVWR Determine Legal Loads
Length (Trailer Only)	52 feet 5 inches
Width	8 feet 6 inches
Compatibility	Designed to Accept Optional 51/60 Rear Axle, Spreader, and/or 23 inch Flip Box
Accent Package	None
Weight	Est. Configured Weight: 22917# +/- 3%
	Gooseneck
Gooseneck Design	Narrow Hydraulic Removable Non-Ground Bearing - Swing Radius of 102 inches (11ft 11in overall Gooseneck Length) Set Up for Wetline Operation
Loaded Fifth Wheel Height	Dual Cam Pawl Arm Assembly with 7 Ride Height Positions (50 inches Nominal)
Kingpin	Dual Kingpin at 81 inch and 102 inch Radius
Power Source	Set Up for Wet Line Operation
VIN Plate	Bilingual VIN Plate
Registration/Document Holder	Install Registration/Document Holder
	Deck
Framework	All Main Longitudinal Members Fabricated with 100,000# Minimum Yield Steel Flanges with 50,000# Webs
Deck Design	Drop Side Rail (DSR) Design
Deck Length	26 feet 0 inches Clear Deck Length
Loaded Deck Height	14.5 inches at Side Rails, 22 inches at Main Beams with 6 inches of Ground Clearance
Crossmembers	On 24 inch Centers (Nominal)
Flooring	1.5 inch nominal wood-side rails only
Extension Brackets	13 Pair - 26 Total Removable Swing Type, 1 Pair - 2 Total Removable Heavy Duty Type
Toolbox	2 Fully Covered Trays in Front of Deck Between Mainbeams with Lockable Covers
Hammer Plate	None
	Rear Bridge: General
Front Bogie Ramp	Included
Boom Trough	V Crossmembers with Bolt-In V Pan
Deck to Bogie Connection	Fixed
Bolsters	Recessed
Covered Rear Bogie	None
Rear Bogie Height	40 7/8 inches
	ment Air and Electrical Connections to Go Along with Connecting Ears
	Rear Bridge: Axles
Number of Axles	3 Axles
Axle Capacity	25,000 lb. Nominal Capacity Per Axle NOTE: GAWR Determined by Suspension Type, Brakes, Tires and Other Components.
Axle Spread	54.5 inches (Between Axles)
Brakes	16.5 inches x 7 inches with 5.5 inches Autoslacks - Heavy Duty Brake Drums - Outboard Mount
Spring Brakes	None
Dust Shield	None
Hubodometer	None
	Rear Bridge: Suspension
Suspension	Air Ride
ABS	None
Third Lift Axle	Air Lift Installed on Third Axle
Chain Lift	None
Ride Height Control	7-Position Mechanical Ride Height Control System
Manual Dump Valve	Manual Dump Valve (Push Pull)
Liquid Filled Gauge	None
Load Scale	None
	Wheels and Tires
Wheels	8.25 x 22.5 LvL One Buffed Outside/Steel Inside - Hub-Piloted
Wheels Tires	
Inflation	275/70R 22.5 H Ply OEM Standard
macion	None




**Detailed Specifications** 

Lighting	
Electrical System	DOT Sealed Beam and Harness with LED Lights and 4-inch Flush Mounted Battery Powered Amber Strobes
Tail Lights	3 Tail Light Package
Marker Lights	3 Marker Lights Per Side Including Mid-Turn
Electrical Receptacle	J560 7-Pin Connector
	Paint
Paint	Fontaine Black Polyurethane Enamel
	Miscellaneous
Lash Rings	14 Pair - 28 Total
Flag Holders	2 Pair Flag Holders
	Additional Options
Flip Box	None
Accent Package Installed on Flip Box	None
Spreader	None
Accent Package Installed on Rigid Spreader	None
Flip Axle	None
Dust Shields on Flip Axle	None
Accent Package Installed on Flip Axle	None
	<u>l</u>

## **MAGNITUDE 55H DSR 26**









## Sales Drawing: MAGNITUDE 55H DSR 26

