

## Hale Trailer Brake & Wheel A011604-A011607 VIN: 5A2635-5A2638



**Detailed Specifications** 

Detailed Specifications		
MAGNITUDE 60 DSR 26 (Model:	MAG60****D**826543)	
	General	
SKU	MAG60***D**826543	
Capacity	60 Tons in 13-foot Length with 102-inch Swing and 4 Axles Close Coupled with Flipbox Deployed 125-inch Swing; 55 Tons in 16-foot Length with 125-inch Swing and 3+1 EQ1; 55 Tons in 10-foot with 102-inch Swing and 4 Axles Closed Coupled - GAWR and GVWR Determine Legal Payloads	
Length (Trailer Only)	52 feet 5 1/2 inches	
Width	8 feet 6 inches	
Compatibility	Designed to accept optional 51/60 rear axle, spreader, and/or 23 inch flip box	
Accent Package	None	
Weight	Est. Configured Weight: 25026# +/- 3%	
Gooseneck		
Gooseneck Design	Narrow hydraulic removable non-ground bearing - swing radius of 102 inches (11ft 11in overrall gooseneck length) set up for wetline operation	
Loaded Fifth Wheel Height	Dual Cam Pawl Arm Assembly with 7 ride height positions (50 inches nominal)	
Kingpin	Dual Kingpin at 81 inch and 102 inch Radius	
Power Source	Set Up for Wet Line Operation	
VIN Plate	Bilingual VIN plate	
Registration/Document Holder	Install registration/document holder	
5 ,	Deck	
Framework	All main longitudinal members fabricated with 100,000# minimum yield steel flanges with 50,000# webs	
Deck Design	Drop side rail (DSR) design	
Š	26 feet 0 inches Clear Deck Length	
Deck Length Loaded Deck Height	14.5 inches at siderails 23 inches at main beams with 6 inch ground clear	
	On 24 inch Centers (Nominal)	
Crossmembers	1.5 inch Nominal Wood (Side Rails Only)	
Flooring	None, Front of Deck Sloped Top Down to Assist in Loading with Traction Cleats	
Front Ramps Extension Brackets		
	13 pair - 26 total removable swing type, 2 pair - 4 total heavy duty removable hook-on type  2 Fully Covered Trays in Front of Deck Between Mainbeams with Lockable Covers	
Toolbox	Hammer Plate installed over recessed crossmembers. Preforated plate under hammer plate forming two storage	
Hammer Plate	areas. 2 pair lashing ring located in last two deck sections.	
	Rear Bridge: General	
Front Bogie Ramp	Included	
Boom Trough	V crossmembers with bolt-in V pan	
Deck to Bogie Connection	Fixed	
Bolsters	Recessed	
Covered Rear Bogie	None	
Rear Bogie Height	41 inches to top flanges- 37 inches to top of bolsters	
Connections for Future Axle Attachr		
Connections for rutare / Mic / teach	Rear Bridge: Axles	
Number of Auton		
Number of Axles  Axle Capacity	3 Axles 25,000 lb. Nominal Capacity Per Axle NOTE: GAWR Determined by Suspension Type, Brakes, Tires and Other Components.	
Axle Spread	54.5 inches (Between Axles)	
Brakes	16.5 inches x 7 inches with 5.5 inches autoslacks - heavy duty brake drums - outboard mount	
Spring Brakes Dust Shield	None None	
Hubodometer	None	
Trabodometel	Rear Bridge: Suspension	
	To any	
Suspension	Air Ride	
Suspension ABS	Air Ride None	
ABS	None	
ABS Third Lift Axle	None Air lift installed on third axle	
ABS Third Lift Axle Chain Lift	None Air lift installed on third axle None	
ABS Third Lift Axle Chain Lift Ride Height Control	None Air lift installed on third axle None 7-Position Mechanical Ride Height Control System	
ABS Third Lift Axle Chain Lift Ride Height Control Manual Dump Valve	None Air lift installed on third axle None 7-Position Mechanical Ride Height Control System Manual Dump Valve (Push Pull)	
ABS Third Lift Axle Chain Lift Ride Height Control Manual Dump Valve Liquid Filled Gauge	None Air lift installed on third axle None 7-Position Mechanical Ride Height Control System Manual Dump Valve (Push Pull) None	
ABS Third Lift Axle Chain Lift Ride Height Control Manual Dump Valve Liquid Filled Gauge Load Scale	None Air lift installed on third axle None 7-Position Mechanical Ride Height Control System Manual Dump Valve (Push Pull) None None Wheels and Tires	
ABS Third Lift Axle Chain Lift Ride Height Control Manual Dump Valve Liquid Filled Gauge Load Scale Wheels	None Air lift installed on third axle None 7-Position Mechanical Ride Height Control System Manual Dump Valve (Push Pull) None None Wheels and Tires  8.25 x 22.5 LvL One Buffed Outside/Steel Inside - Hub-Piloted	
ABS Third Lift Axle Chain Lift Ride Height Control Manual Dump Valve Liquid Filled Gauge Load Scale	None Air lift installed on third axle None 7-Position Mechanical Ride Height Control System Manual Dump Valve (Push Pull) None None Wheels and Tires	




**Detailed Specifications** 

Lighting			
Electrical System	DOT sealed beam and harness with LED lights and 4 inch flush mounted battery powered amber strobes		
Tail Lights	3 tail light package		
Electrical Receptacle	J560 7-pin connector		
Paint			
Paint	Fontaine Black Polyurethane Enamel		
Miscellaneous			
Lash Rings	19 pair - 38 total		
Flag Holders	2 pair flag holders		
Additional Options			
Flip Box	None		
Accent Package Installed on Flip Box	None		
Spreader	None		
Accent Package Installed on Rigid Spreader	None		
Flip Axle	None		
Dust Shields on Flip Axle	None		
Accent Package Installed on Flip Axle	None		
Custom Option #1	Suspension 30K GAWR 24,700		
Terms			

MAGNITUDE 60 DSR 26	
60 DSR 26 Race Model (Note: Options not shown)	







## Sales Drawing: MAGNITUDE 60 DSR 26

