



# Hale Trailer Brake & Wheel

A011809-A011812  
VIN: 61580-61583



**Revolution 52 Alum Flat 53' Rear Axle Slide (Model: HAR5222RSA)**

<b>Length / Width:</b> 53 feet x 102 inches	
<b>Suspension Type:</b> Rear axle slide; This Trailer Design Does NOT Meet Proposed GHG2 Compliance Requirements	
<b>Frame Rating:</b> 80,000 lbs distributed - 52,000 lbs concentrated in 4 feet- GAWR and tire ratings determine legal payloads	
<b>Flooring:</b> Knurled extruded 3-1/8 aluminum, <b>StirLITE Friction Stir Welded Floor</b> with 2 wood nailer strips; Heavy wall extrusions in single coil area; Heavy wall extrusion at rear	
<b>Side Rails:</b> Exclusive <b>Revolutionary RASR Rail Technology</b> -- one piece routed aluminum designed for strength and impact	
<b>Stationary Chain Cargo Tie Downs:</b> 17 pair - recessed in siderails	
<b>Stake Pockets:</b> Routed Aluminum on 24 inch centers (2 load securement openings in between stake pockets)	
<b>Rubrail:</b> Integrated with side rail	
<b>Main Beams:</b> Extruded aluminum - 8.25 inch flange	
<b>Kingpin:</b> 30 inches	
<b>Loaded Fifth Wheel Height:</b> 49 inches	
<b>Landing Gear:</b> Jost AX100G19 <b>ALUMILIGHT Aluminum Landing Gear</b> with forward & rear bracing	
<b>Bulkheads:</b> None standard	
<b>Number of Axles:</b> 2	
<b>Axle Spindle:</b> Tapered	
<b>Brakes:</b> Spring brakes, auto slacks, Aluminum air tank	
<b>Air Line Filters:</b> (2) Meritor In-line type installed	
<b>ABS:</b> 4S/2M - no cable or tool	
<b>Axle Spread:</b> 122 inches open - 54 inches closed - Meets California, Canadian RTAC and BC dimensional specifications in closed position	
<b>Hub and Drums:</b> 10-hole hub-piloted with outboard cast drums - STANDARD	
<b>Wheel Ends:</b> Grease in hubs - *** 5-year wheel end warranty ***	
<b>Wheels:</b> 22.5 x 8.25 aluminum Lvl One buffed wheels	
<b>Tires:</b> 11R 22.5 14PR economical OEM standard tires	
<b>Tire Inflation System:</b> None standard	
<b>Suspension Detail:</b> Hendrickson air ride	
<b>Air Assist Slide Box Pins:</b> Standard mount of controls on slider frame	
<b>Auto Glad Hand Dump:</b> Installed	
<b>Electric Dump Valve:</b> Wired to 7-way auxiliary socket to dump rear axle	
<b>Front Corners:</b> Tapered	
<b>Electrical System:</b> LED: 5 Lights/Side; Rear with 3 4-inch Round Lights/Side, 3 Round Lights Center Cluster	
<b>Other Electrical Specifications:</b> 4 way socket on rear with one hot/one ground pin for wide load and strobe light connections	
<b>Paint:</b> Black urethane on steel parts with Revolution decals - STANDARD	
<b>Conspicuity Tape:</b> Per NHTSA specs - installed in recess on rubrails	
<b>Bumper:</b> Bolt-On; Meets underride requirements	
<b>Mudflaps:</b> 1 set OEM standard behind rear axle only	
<b>Spare Tire Carrier:</b> None standard	
<b>Winch Track:</b> Dual full-length integrated aluminum -- double L design	
<b>Sliding Winches:</b> 12 standard; 6 each side; sliding rope hook/ winch strap hook retainers - STANDARD	
<b>27' Winch Straps:</b> None standard	
<b>30' Winch Straps:</b> None standard	
<b>Sliding J-Hook for Ring vs. Flat Hook on 4" Strap:</b> None standard	
<b>Dock Bumpers:</b> 1 pair rubber on rear	
<b>Hubodometer:</b> None standard	
<b>Registration Holder:</b> Install registration holder - OEM standard	
<b>Tool Box:</b> None standard	
<b>VIN Plate:</b> Bilingual US/Canadian VIN plate	
<b>Please Note:</b> Price includes commodity surcharges	
<b>Unit Numbers &amp; Decals:</b> Not available	

**DISCLAIMER**

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.