



Hale Trailer Brake & Wheel

A011832-A011840
VIN: 62072-62080



Infinity Flat 45' Closed Tandem Air Forklift Trailer (Model: HAIFL42CTA)

Length / Width: 45 feet x 102 inches	
Suspension Type: Fixed closed tandem air	
Frame Rating: 80,000 lbs distributed - GAWR and tire ratings determine legal payloads	
Flooring: 1 1/8 inch aluminum with 4 wood nailer strips	
Crossmembers: 12 inch centers - 4 inch jr. I-steel	
Single Coil Hauling Package: Included	
Side Rails: Exclusive Revolutionary RASR Rail Technology -- one piece routed aluminum designed for strength and impact	
Chain Cargo Tie Downs: None standard	
Stake Pockets: Routed aluminum on 24 inch centers (2 load securement openings between stake pockets)	
Rubrail: Integrated with siderail	
Main Beams: 130K load bearing flanges	
Kingpin: 30 inches	
Loaded Fifth Wheel Height: 49 inches	
Landing Gear: OEM Standard with Forward & Rear Bracing	
Knee Braces: Fabricated on approx. 60 inch C/C	
Bulkhead Pockets: 4 DOT type bulkhead pockets only - welded to front	
Bulkheads: Removable steel 4 post DOT type bulkhead – no turnback – 48 inches high with front pockets	
Number of Axles: 2	
Axle Spindle: Tapered	
Brakes: Spring brakes, auto slacks	
Air Line Filters: (2) Meritor In-line type installed	
ABS: 4S/2M - no cable or tool	
Axle Spread: 49 inches - set ahead for fork clearance	
Hub and Drums: 10-hole hub-piloted with outboard cast drums	
Wheel Ends: Grease in hubs - *** 5-year wheel end warranty ***	
Wheels: 22.5 x 8.25 steel disc wheels - pre-painted white - STANDARD	
Tires: 11R 22.5 14PR OEM standard tires	
Tire Inflation System: None standard	
Suspension Detail: Hendrickson AANT23K Intraax air ride	
Auto Glad Hand Dump: Installed	
Front Corners: Tapered steel	
Electrical System: LED: 3 lights/side, 2 lights/side on rear - STANDARD	
Paint: Black urethane on steel parts with Infinity decals - STANDARD	
Conspicuity Tape: Per NHTSA specs - installed in recess on rubrails	
Bumper: Weld-on hinged type; Uprights notched inside for additional fork clearance	
Mudflaps: 1 set OEM standard behind rear axle only	
Spare Tire Carrier: None standard	
Winch Track: Full length integrated double L type aluminum on both sides -- STANDARD	
Sliding Winches: 12: 6 each side; sliding Rope Hook/ Winch Strap Hook Retainers -- STANDARD	
27' Winch Straps: None standard	
30' Winch Straps: None standard	
Dock Bumpers: Not available due to design	
Hubodometer: None standard	
Registration Holder: Install registration holder - OEM standard	
Tool Box: 1 aluminum double door box – 24 inches x 24 inches x 60 inches – installed Curb Side	
VIN Plate: Bilingual US/Canadian VIN plate	
Forklift Kit: Factory installed Fontaine design with adjustable curved upper wheel stops which accepts most Princeton, Moffett, & Navigator brand lifts	
Forklift Kit Note: *Dealer and/or Customer are responsible for final adjustment of stops & kit in order to fit actual lift being transported. **Actual brand & model to be advised to confirm compatibility	
Forklift Kit Lower Tire Supports for Moffett: Removable lower Moffett tire supports each side	
Front Counterweights: Steel recessed at front with approximate combined wt. of 1,112#; *Customer to confirm that counterweights are adequate with lift being transported	
Please Note: Price includes commodity surcharges	
Unit Numbers & Decals: Not available	

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.