

Hale Trailer Brake & Wheel A012131-A012145 VINS: 65255-65269



| PEERLESS TRANSPORT SEMI: Dual Axle, Live Floor, 48' Length, 16.2 Units | | |
|--|---|--|
| STANDARD SPECIFICATIONS: CTSSF-48 (South Specs) | | |
| Type: | Peerless dual axle, transport semi-trailer, 45 degree front | |
| Design: | Box design, flat floor, end dump, live floor | |
| Construction: | Skin stressed .063 natural aluminum with aluminum interior posts (14.5" centers) Skins to extend to bottom of lower rail | |
| Unloading Time: Approximately 8 minutes | | |
| Capacity: | 16.2 units (119.8 cu yd) | |
| Dimensions: | 48' long, 8' 6" wide, 13' 3" high, 37" king pin location, 36" rear axle from rear of trailer | |
| Tires: | Eight (8) 11:00 x 24.5 radial tires | |
| Wheels: | Eight (8) 24.5 x 8.25 - 10 hole, 11 1/4" B.C. hi-tensile steel, Unimount | |
| Axles: | 25,000# cap. inserted spindles, 77 1/2" track, 10 stud, 11 1/4" B.C. hubs, outboard drums, oil seals, quick change brake shoes, auto slacks | |
| Brakes: | 16 1/2" x 7" air, CM18 lining, type 3030 air chambers, DOT relay emergency system | |
| A.B.S.: | 2 sensor - 1 module | |
| Suspension: | Four spring three leaf tandem (Hutch H9700T with slider) | |
| Landing Gear: | Two speed, crank on driver's side (Holland Atlas 55), channel bracing | |
| King Pin: | Standard SAE, heat treated, 37" setting, 49" height, 3 I-beams with 5/16" plate | |
| Cross Sills & Decking: | Keith 7/32" two live floor, 4" Jr. I-Beams on 12" centers with aluminum sub-deck, | |
| Тор: | Flat design, open top, single center tie | |
| Top Cover: | Shur-lok roll over tarp, vinyl materal black in color, rear crank, <u>flat tarp bows</u> | |
| Rear Door: | Full opening, side hinged, solid freight door with four (4) latches, low mount | |



| Dump Stands: | Two (2) blades at rear for standard Peerless backstop |
|--------------|--|
| Screens: | Safety screens on front and under drive |
| Ladders: | One located at front and one located at rear |
| Rope Hooks: | None |
| Mud Flaps: | Legal, rubber |
| Wiring: | Unitized wiring system, 12 volt, air and light plugs on front center |
| Lights: | Four (4) legal DOT combination stop, tail and directional lights. Legal DOT clearance lights |
| Reflectors: | Legal DOT |
| Paint: | Aluminum natural, steel components primed and painted BLACK |
| Weight: | Approximately 14,300# |
| REF#: | 64276 |