



Hale Trailer Brake & Wheel

A012378-A012379

VINS: 42402-42403

Talbert Manufacturing, Inc.

Model: AC-20-AR

Capacity in tons: 20

1. TONGUE

Pintle eye

Tongue

Adjustable pintle eye (3" ID) with 48" chain and grab hooks
5'-6" with lockable tool box with aluminum diamond plate lid - move hinge 4" forward

Drop leg

2-speed, 50,000# crank down dual landing leg, mounted to main beams and headboard

Electrical receptacle

Seven pin connector

Headboard

8" high full width

2. DECK

Deck section design

One piece tongue, main beam and beavertail (cold formed)

Deck section length

27'-0" (21'-0" flat with 6'-0" beavertail)

Deck section width

8'-6"

Loaded deck height

32-1/4"

Flooring

1-1/2" apitong with individual wheel wells

Lash rings

10 total -

4 each side on flat deck (straight style), 8 total

1 each side on beavertail (straight style), 2 total

Mainbeams

12" deep hi-tensile

Crossmembers

6" deep hi-tensile

Sidemembers

8" deep hi-tensile

Beavertail

6'-0" with wood flooring full width

Ramps

38" wide x 6'-0" long air ramps with wood flooring, stored vertically with lock bar

3. RUNNING GEAR

Number of axles

2

Axle capacity

25,000#, full width track

Brakes

12-1/4" x 7-1/2" air with 2S/1M ABS. Spring brakes on both axles.

Wheels

Steel disc with oil seals (6.75 x 17.5)

Tires

Eight (8) 215/75R17.5 (H) 16PR radials

Use valve stem extensions on inside wheels

Suspension

44,800# Hutch spring

4. GENERAL

Lights and wiring

12 volt LED system (license plate regular), supplied with female 7-way plug on tongue, SUPPLY JUMPER CORD FOR TRUCK

Paint

Valspar standard Talbert black

Estimated empty weight

9,140#

Additional general specifications

Formed step in front of 1st axle both sides of trailer

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.