



Hale Trailer Brake & Wheel

A012584-A012592

VINS: 62762-62770



Revolution 52 Alum Flat 53' Rear Axle Slide (Model: HAR522RSA)

Length / Width: 53 feet x 102 inches
Suspension Type: Rear axle slide; This Trailer Design Does NOT Meet Proposed GHG2 Compliance Requirements
Frame Rating: 80,000 lbs distributed - 52,000 lbs concentrated in 4 feet- GAWR and tire ratings determine legal payloads
Flooring: Knurled extruded 3-1/8 aluminum, StirLITE Friction Stir Welded Floor with 2 wood nailer strips; Heavy wall extrusions in single coil area; Heavy wall extrusion at rear
Side Rails: Exclusive Revolutionary RASR Rail Technology -- one piece routed aluminum designed for strength and impact
Stationary Chain Cargo Tie Downs: 17 pair - recessed in siderails
Stake Pockets: Routed Aluminum on 24 inch centers (2 load securement openings in between stake pockets)
Rubrail: Integrated with side rail
Main Beams: Extruded aluminum - 8.25 inch flange
Kingpin: 30 inches
Loaded Fifth Wheel Height: 49 inches
Landing Gear: Jost AX100G19 ALUMILIGHT Aluminum Landing Gear with forward & rear bracing
Bulkheads: None standard
Number of Axles: 2
Axle Spindle: Tapered
Brakes: Spring brakes, auto slacks, Aluminum air tank
Air Line Filters: (2) Meritor In-line type installed
ABS: 4S/2M - no cable or tool
Axle Spread: 122 inches open - 54 inches closed - Meets California, Canadian RTAC and BC dimensional specifications in closed
Hub and Drums: 10-hole hub-piloted with outboard cast drums - STANDARD
Wheel Ends: Grease in hubs - *** 5-year wheel end warranty ***
Wheels: 22.5 x 8.25 aluminum Lvl One buffed wheels
Tires: 295/75R 22.5 14PR OEM standard tires
Tire Inflation System: None standard
Suspension Detail: Hendrickson air ride
Air Assist Slide Box Pins: Standard mount of controls on slider frame
Auto Glad Hand Dump: Installed
Electric Dump Valve: Wired to 7-way auxiliary socket to dump rear axle
Front Corners: Tapered
Electrical System: LED: 5 Lights/Side; Rear with 3 4-inch Round Lights/Side, 3 Round Lights Center Cluster
Other Electrical Specifications: 4 way socket on rear with one hot/one ground pin for wide load and strobe light connections
Paint: Black urethane on steel parts with Revolution decals - STANDARD
Conspicuity Tape: Per NHTSA specs - installed in recess on rubrails
Bumper: Bolt-On; Meets underide requirements
Mudflaps: 1 set OEM standard behind rear axle only
Spare Tire Carrier: None standard
Winch Track: Dual full-length integrated aluminum -- double L design
Sliding Winches: 12 standard; 6 each side; sliding rope hook/ winch strap hook retainers - STANDARD
27' Winch Straps: None standard
30' Winch Straps: None standard
Sliding J-Hook for Ring vs. Flat Hook on 4" Strap: None standard
Dock Bumpers: 1 pair rubber on rear
Hubodometer: None standard
Registration Holder: Install registration holder - OEM standard
Tool Box: 1 aluminum double door box - 24 inches x 24 inches x 60 inches - installed Curb Side; includes 4 sliding
VIN Plate: Bilingual US/Canadian VIN plate
Please Note: Price includes commodity surcharges
Unit Numbers & Decals: Not available

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.