



## Hale Trailer Brake & Wheel

A012596-A012601

VINS: 62756-62761



### Velocity 53' Air Slider (Model: HAVSF22SAT)

<b>Length / Width:</b> 53 feet x 102 inches
<b>Suspension Type:</b> Sliding air tandem; This Trailer Design Does NOT Meet Proposed GHG2 Compliance Requirements
<b>Frame Rating:</b> 80,000 lbs distributed - GAWR and tire ratings determine legal payloads
<b>Flooring:</b> 1 1/8 inch wood
<b>Crossmembers:</b> 12 inch centers - 4 inch jr. I-steel
<b>Side Rails:</b> 6 inch structural channel @ 6.5 lbs/ft
<b>Stake Pockets:</b> 3/16 inch steel on 24 inch centers
<b>Pipe Spools:</b> Double between stake pockets
<b>Rubrail:</b> 3/8 inch x 2 1/2 inch steel
<b>Main Beams:</b> 130K load bearing flanges
<b>Kingpin:</b> 30 inches
<b>Loaded Fifth Wheel Height:</b> 49 inches
<b>Landing Gear:</b> OEM Standard with Forward & Rear Bracing
<b>Knee Braces:</b> Fabricated on approx. 60 inch C/C
<b>Bulkheads:</b> Removable steel 4 post DOT type bulkhead - no turnback - 48 inches high
<b>Bulkhead Pockets:</b> 4 - F-5 DOT-type steel
<b>Number of Axles:</b> 2
<b>Axle Spindle:</b> Tapered
<b>Brakes:</b> Spring brakes, auto slacks
<b>Air Line Filters:</b> (2) Meritor In-line type installed
<b>ABS:</b> 4S/2M - no cable or tool
<b>Axle Spread:</b> 49 inches (40 feet C/L kingpin to C/L rear axle in front position)
<b>Hub and Drums:</b> 10-hole hub-piloted with outboard cast drums
<b>Wheel Ends:</b> Grease in hubs - *** 5-year wheel end warranty ***
<b>Wheels:</b> 22.5 x 8.25 steel disc wheels - pre-painted white - STANDARD
<b>Tires:</b> 11R 22.5 14PR OEM standard tires
<b>Tire Inflation System:</b> None standard
<b>Suspension Detail:</b> Hendrickson AAZNT46K Intraax air ride slider - 60 inches adjustable
<b>Air Assist Slide Box Pins:</b> Standard mount of controls on slider frame
<b>Auto Glad Hand Dump:</b> Installed
<b>Front Corners:</b> Tapered
<b>Electrical System:</b> LED: 3 lights/side, 2 lights/side on rear- STANDARD
<b>Paint:</b> Black urethane with Velocity decals - STANDARD
<b>Conspicuity Tape:</b> Per NHTSA specs - installed on rubrails
<b>Bumper:</b> Weld-on type - meets underride requirements
<b>Mudflaps:</b> 1 set OEM standard
<b>Spare Tire Carrier:</b> None standard
<b>Winch Track:</b> Steel on road side
<b>Sliding Winches:</b> 12 standard
<b>27' Winch Straps:</b> None standard
<b>30' Winch Straps:</b> None standard
<b>Dock Bumpers:</b> 1 pair rubber on rear
<b>Hubodometer:</b> None standard
<b>Registration Holder:</b> Install registration holder - OEM standard
<b>Tool Box:</b> None standard
<b>VIN Plate:</b> Bilingual US/Canadian VIN plate
<b>Please Note:</b> Price includes commodity surcharges
<b>Unit Numbers &amp; Decals:</b> Not available

#### DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.