



# Hale Trailer Brake & Wheel

A012602-A012613

VINS: 62744-62755



## Infinity Flat 45' Closed Tandem Air Forklift Trailer (Model: HAIFL42CTA)

<b>Length / Width:</b> 45 feet x 102 inches
<b>Suspension Type:</b> Fixed closed tandem air
<b>Frame Rating:</b> 80,000 lbs distributed - GAWR and tire ratings determine legal payloads
<b>Flooring:</b> 1 1/8 inch aluminum with 4 wood nailer strips
<b>Crossmembers:</b> 12 inch centers - 4 inch jr. I-steel
<b>Single Coil Hauling Package:</b> Included
<b>Side Rails:</b> Exclusive <b>Revolutionary RASR Rail Technology</b> -- one piece routed aluminum designed for strength and impact
<b>Chain Cargo Tie Downs:</b> None standard
<b>Stake Pockets:</b> Routed aluminum on 24 inch centers (2 load securement openings between stake pockets)
<b>Rubrail:</b> Integrated with siderail
<b>Main Beams:</b> 130K load bearing flanges
<b>Kingpin:</b> 30 inches
<b>Loaded Fifth Wheel Height:</b> 49 inches
<b>Landing Gear:</b> OEM Standard with Forward & Rear Bracing
<b>Knee Braces:</b> Fabricated on approx. 60 inch C/C
<b>Bulkhead Pockets:</b> 4 DOT type bulkhead pockets only - welded to front
<b>Bulkheads:</b> Removable steel 4 post DOT type bulkhead - no turnback - 48 inches high with front pockets
<b>Number of Axles:</b> 2
<b>Axle Spindle:</b> Tapered
<b>Brakes:</b> Spring brakes, auto slacks
<b>Air Line Filters:</b> (2) Meritor In-line type installed
<b>ABS:</b> 4S/2M - no cable or tool
<b>Axle Spread:</b> 49 inches - set ahead for fork clearance
<b>Hub and Drums:</b> 10-hole hub-piloted with outboard cast drums
<b>Wheel Ends:</b> Grease in hubs - *** 5-year wheel end warranty ***
<b>Wheels:</b> 22.5 x 8.25 steel disc wheels - pre-painted white - STANDARD
<b>Tires:</b> 11R 22.5 14PR OEM standard tires
<b>Tire Inflation System:</b> None standard
<b>Suspension Detail:</b> Hendrickson AANT23K Intraax air ride
<b>Auto Glad Hand Dump:</b> Installed
<b>Front Corners:</b> Tapered steel
<b>Electrical System:</b> LED: 3 lights/side, 2 lights/side on rear - STANDARD
<b>Paint:</b> Black urethane on steel parts with Infinity decals - STANDARD
<b>Conspicuity Tape:</b> Per NHTSA specs - installed in recess on rubrails
<b>Bumper:</b> Weld-on hinged type; Uprights notched inside for additional fork clearance
<b>Mudflaps:</b> 1 set OEM standard behind rear axle only
<b>Spare Tire Carrier:</b> None standard
<b>Winch Track:</b> Full length integrated double L type aluminum on both sides -- STANDARD
<b>Sliding Winches:</b> 12: 6 each side; sliding Rope Hook/ Winch Strap Hook Retainers -- STANDARD
<b>27' Winch Straps:</b> None standard
<b>30' Winch Straps:</b> None standard
<b>Dock Bumpers:</b> Not available due to design
<b>Hubodometer:</b> None standard
<b>Registration Holder:</b> Install registration holder - OEM standard
<b>Tool Box:</b> 1 aluminum double door box - 24 inches x 24 inches x 60 inches - installed Curb Side
<b>VIN Plate:</b> Bilingual US/Canadian VIN plate
<b>Forklift Kit:</b> Factory installed Fontaine design with adjustable curved upper wheel stops which accepts most Princeton, Moffett, & Navigator brand lifts
<b>Forklift Kit Note:</b> *Dealer and/or Customer are responsible for final adjustment of stops & kit in order to fit actual lift being transported. **Actual brand & model to be advised to confirm compatibility
<b>Forklift Kit Lower Tire Supports for Moffett:</b> Removable lower Moffett tire supports each side
<b>Front Counterweights:</b> Steel recessed at front with approximate combined wt. of 1,112#; *Customer to confirm that counterweights are adequate with lift being transported

### DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.