

Hale Trailer Brake & Wheel

A012619-A012623

VINS: 82628-82632



EAST GENESIS UNLOADER TRAILER

OPEN TOP

CLOSED TOP



BODY: "GENESIS"		TAILGATE:		CHASSIS:	
WIDTH (INCHES)	102	HEIGHT	FULL	MODEL	QUAD (10)(14)
LENGTH (FEET)	50	TYPE	SINGLE	TYPE	ALUM SUB FRAME
HEIGHT (INCHES)	104	STYLE	GENESIS	AXLE TO AXLE	49" - 49" - 49"
SIDE MAT'L (OUTBOARD)	"GENESIS"	MAT'L THICKNESS	0.150	REAR AXLE SETTING	55"
FRONT	0.150	S / S HINGE ON	P/S 4-3-4	5TH WHEEL HT	51"
MIDDLE	0.150	GATESEAL	NONE	PIN SETTING	36" w / 3/8" PLATE
REAR	0.150	GATE LADDER	Commercial- Ctr	SUSPENSION	REYCO 21-B (11)(12)
POLISHED SIDES	NO	TARP HOOKS	NONE	SPRINGS	SINGLE LEAF
ROOF	NONE	WINDERS	ONE - D/S	AXLES	TP - 23,000 GAWR
ROOF MAT'L	NONE	GATE GUIDE	YES	BRAKES	16-1/2" x 7"
BULKHEAD	3/16" (1)(7)	GATE CONTROL	MECH	DUSTSHIELDS	YES
TARP HOOKS	NONE	POCKETS	EXTRUDED	BRAKE CHAMBERS	ON TOP OF AXLES
TARP BASKET	NONE	CROSSPIPE (S)	TWO - MIDDLE -	ABS	2S / 1M
TARP	NONE		SPRING TYPE -	HUBS	10 STUD STEEL
CATWALK	YES - FULL WIDTH		REAR TUBE TYPE		EAST ELITE
B.H. LADDER	Commercial D/S	COMPACTOR:		WHEELS	8.25 x 24.5
CROSSMEMBER	"I"BEAM- 12" C/L	SIDE LATCH	N/A		16 STEEL DISC
FLOOR MAKE	KEITH 3.5" Drives	CENTER LATCH		TIRES	11R 24.5 R250ED
FLOOR MAT'L	2299 1/2" IMPACT	PIN DIA.			16 PLY BRIDGEST.
WEARPADS	CWS	HYDRAULICS:		DOLLIES	JOST 2 SPD A451
TAPE COLOR	NONE	HOSES	TWO-4000 PSI	LOCATION	D/S CRANK
LIGHT PANEL	IN GATE LED (8)	LENGTH	144"	BUMPER	UNDERRIDE GUARD
MARKER LIGHTS	3 PR BOTTOM ONLY	FITTINGS	PUSH-PULL	TOW HOOK(S)	TWO
MIDMOUNT SIGNALS	MODEL 60	HP	1" MALE	PUSH BLOCKS	YES
MUDFLAPS	YES	LP	1" FEMALE	PAINT	SILVER
HOSE HANGER	YES	HOSE LOCATION	CENTER		
TIRE CARRIER	NONE	AIR & ELECTRICAL	CENTER (9)		

REMARKS: PRICING SUBJECT TO CHANGE 12 WEEKS PRIOR TO ESTIMATED BUILD TIME

1. NO INSIDE BULKHEAD STEPS
2. WELD ENDS OF ALL CROSSMEMBERS TO BOTTOM RAIL.
3. KEITH ALUMINUM FRAME. STAINLESS STEEL HYDRAULIC TUBING. ADD DRIVE BRACES AND NYLON T BLOCKS
4. 3 PAIR PER SIDE BOTTOM ONLY W/ PROTECTORS.
5. FILTERED GLADHANDS
6. ALUMINUM AIR TANKS TO HAVE CABLE OPERATED DRAINS EXTENDED TO D/S BOTTOM RAIL.
7. MANDOR IN THE CENTER OF THE BULKHEAD
8. ADD 1 PR NON LED BACK UP LIGHTS WIRED TO AUXILIARY IN THE TAILGATE OOX ooo XOO
9. AUXILIARY 6-WAY PLUG (LOCATED NEAR STD 7 WAY) WIRED INTO JUNCTION BOX AT REAR JUST AHEAD OF MOST FORWARD AXLE
10. RUN ALUMINUM SUBFRAME TO THE BACK OF THE LANDING GEAR.
11. MOVE DRIVE UNIT FORWARD TO MISS QUAD SUSPENSION - REYCO 21B -4 FIXED AXLES.
12. SPRING SUSPENSION REYCO 21 B - 4 FIXED AXLES
13. SPLASH GUARD HOLD DOWN BEARINGS
14. REYCO GALVANIZED SUSPENSION

OVERALL HEIGHT (FT) 13-3 **EMPTY WEIGHT (#)** 20,907 **CUBIC YARDS** 130
BODY/FAB/INSPECTION/FRAME/INVENTORY/SALES/TIRES/PAINT/ACID

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical.
 Equipment availability, prices and specifications are subject to change without notice.

