

HALE

TRAILER

BRAKE & WHEEL

EAST GENESIS UNLOADER

OPEN TOP ☒



A012624-A012628

VIN: 82305-82309

SALES | RENTALS | PARTS | SERVICE

| | | | |
|-----------------|--------------|-------------------|--------------|
| Allentown, PA: | 800-383-8894 | Jacksonville, FL: | 800-828-3055 |
| Baltimore, MD: | 888-601-7500 | Little Rock, AR: | 833-424-8944 |
| Boston, MA: | 800-854-5310 | Portland, ME: | 800-325-4253 |
| Concord, NC: | 800-438-2250 | Richmond, VA: | 866-839-3495 |
| Delmar, DE: | 866-486-1400 | Scranton, PA: | 800-569-1400 |
| Des Moines, IA: | 888-673-5011 | Springfield, MA: | 800-854-5306 |
| Elkton, MD: | 800-544-7127 | Voorhees, NJ: | 866-315-0235 |

HaleTrailer.com | @haletrailer



800-232-6535 *FINANCING AVAILABLE

| BODY: "GENESIS" | | TAILGATE: | | CHASSIS: | |
|-----------------------|-------------------|------------------|-----------------|-------------------|---------------------|
| WIDTH (INCHES) | 102 | HEIGHT | FULL | MODEL | TRIDEM (10)(14) |
| LENGTH (FEET) | 50 | TYPE | SINGLE | TYPE | ALUM SUB FRAME |
| HEIGHT (INCHES) | 104 | STYLE | GENESIS | AXLE TO AXLE | 49" - 49" - 49" |
| SIDE MAT'L (OUTBOARD) | "GENESIS" | MAT'L THICKNESS | 0.150 | REAR AXLE SETTING | 55" |
| FRONT 0.150 | | S / S HINGE ON | P/S 4-3-4 | 5TH WHEEL HT | 51" |
| MIDDLE 0.150 | | GATESEAL | NONE | PIN SETTING | 36" w / 3/8" PLATE |
| REAR 0.150 | | GATE LADDER | Commercial- Ctr | SUSPENSION | REYCO 21-B (11)(12) |
| POLISHED SIDES | NO | TARP HOOKS | NONE | SPRINGS | SINGLE LEAF |
| ROOF | NONE | WINDERS | ONE - D/S | AXLES | TP - 23,000 GAWR |
| ROOF MAT'L | NONE | GATE GUIDE | YES | BRAKES | MAXX 22T ADB |
| BULKHEAD | 3/16" (1)(7) | GATE CONTROL | MECH | DUSTSHIELDS | N/A |
| TARP HOOKS | NONE | POCKETS | EXTRUDED | BRAKE CHAMBERS | N/A |
| TARP BASKET | NONE | CROSSPIPE (S) | TWO - MIDDLE - | ABS | 2S / 1M |
| TARP | NONE | | SPRING TYPE - | HUBS | 10 STUD LW STEEL |
| CATWALK | YES - FULL WIDTH | | REAR TUBE TYPE | | HXL-5 |
| B.H. LADDER | Commercial D/S | COMPACTOR: | | WHEELS | 8.25 x 24.5 |
| CROSSMEMBER | "I"BEAM- 12" C/L | SIDE LATCH | N/A | | 12 STEEL DISC |
| FLOOR MAKE | KEITH 3.5" Drives | CENTER LATCH | | TIRES | 11R 24.5 R250ED |
| FLOOR MAT'L | 2299 1/2" IMPACT | PIN DIA. | | | 16 PLY BRIDGEST. |
| WEARPADS | CWS | | | DOLLIES | JOST 2 SPD A451 |
| TAPE COLOR | NONE | HYDRAULICS: | | LOCATION | D/S CRANK |
| LIGHT PANEL | IN GATE LED (8) | HOSES | TWO-4000 PSI | BUMPER | UNDERRIDE GUARD |
| MARKER LIGHTS | 3 PR BOTTOM ONLY | LENGTH | 144" | TOW HOOK(S) | TWO |
| MIDMOUNT SIGNALS | MODEL 60 | FITTINGS | PUSH-PULL | PUSH BLOCKS | YES |
| MUDFLAPS | YES | HP | 1" MALE | PAINT | SILVER |
| HOSE HANGER | YES | LP | 1" FEMALE | | |
| TIRE CARRIER | NONE | HOSE LOCATION | CENTER | | |
| | | AIR & ELECTRICAL | CENTER (9) | | |

REMARKS: PRICING SUBJECT TO CHANGE 12 WEEKS PRIOR TO ESTIMATED BUILD TIME

- 1. NO INSIDE BULKHEAD STEPS
- 2. WELD ENDS OF ALL CROSSMEMBERS TO BOTTOM RAIL.
- 3. KEITH ALUMINUM FRAME. STAINLESS STEEL HYDRAULIC TUBING. ADD DRIVE BRACES AND NYLON T BLOCKS
- 4. 3 PAIR PER SIDE BOTTOM ONLY W/ PROTECTORS.
- 5. FILTERED GLADHANDS
- 6. ALUMINUM AIR TANKS TO HAVE CABLE OPERATED DRAINS EXTENDED TO D/S BOTTOM RAIL.
- 7. MANDOOR IN THE CENTER OF THE BULKHEAD 073-20176-01 STEP FOR MANDOOR
- 8. ADD 1 PR NON LED BACK UP LIGHTS WIRED TO AUXILIARY IN THE TAILGATE OOX ooo XOO
- 9. AUXILIARY 6-WAY PLUG (LOCATED NEAR STD 7 WAY) WIRED INTO JUNCTION BOX AT REAR JUST AHEAD OF MOST FORWARD AXLE
- 10. RUN ALUMINUM SUBFRAME TO THE BACK OF THE LANDING GEAR.
- 11. MOVE DRIVE UNIT FORWARD TO MISS TIRES OF FRONT AXLE OF FUTURE 4TH STEERABLE LIFT AXLE SPACED 52" AHEAD OF FRONT TRIDEM
- 12. CROSSMEMBERS ONLY FOR FUTURE 4TH IMT/ISS SUSPENSION IMT STEERABLE LIFT AXLE 52" AHEAD OF MOST FORWARD AXLE.
- 13. SPLASH GUARD HOLD DOWN BEARINGS
- 14. REYCO GALVANIZED SUSPENSION

CHANGE 1, 2, 3

| | | | | | | | |
|---------------------|------|------------------|------------------|--------|--|-------------|-----|
| OVERALL HEIGHT (FT) | 13-3 | BODY/FAB/INSPECT | EMPTY WEIGHT (#) | 20,907 | | CUBIC YARDS | 130 |
|---------------------|------|------------------|------------------|--------|--|-------------|-----|



DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical.
Equipment availability, prices and specifications are subject to change without notice.