



Hale Trailer Brake & Wheel
A012937-A012939
VINS: PA001915-PA001917



30ART		
30 Ton Tridem Air Tilt/Air Ramp		
Tags		
		Base Weight: 12,760
TRAILER	Overall Length	38 ft. 6 in.
	Overall Width	102 in.
	Weight lbs +/- 2%	13340, including options
	A-Frame	6 ft. 11 in. Hi-Tensile Cold Formed Wide Flange Beam
	Hitch	3 in. pintle eye, adjustable 5 position 17 in. to 31 in.
DECK	Deck Length	25 ft.
	Loaded Deck Height	34 in.
	Main Frame	Hi-Tensile Wide Flange 14 in. @ 30
	Cross Members	Hi-Tensile 6 in. Channel @ 8.2
	Side Rail	Hi-Tensile 8 in. Channel @ 11.5 open on inside
	Air Tilt Deck	* 4 Air Bags
	Floor	1 3/8 in. x 7 in. Keruing Shiplapped
	Landing Gear	Dual Holland Mark V 2 Speed
SUSPENSION/AXLES	Axles	25,000 lbs Capacity 77.5 in. Track ,1 Lift Axle with Control Box
	Spread	49 in.
	Suspension	Hutch 9700 spring ride., 1 Ridewell RAR 260 Underslung Air ride 25,000lbs. (includes air gauge)
	Alum Air Tank	*NPO*: Drain plug with cable
	Brakes	Quick Change 12 1/4 in. x 7 in.
	Brake Chamber	#3030, All Axles
	Air Brake System	2S/1M
	Bearings	Oil Bath
	Slack Adjusters	Automatic
	Hubs & Drums	8 Stud Unimount C / W Cast Drums
	Tires	235/75R17.5 16 ply
	Wheels	Alum. Wheel Pkg. 17.5 (6 steel, 6 polished)
BEAVERTAIL		
	Length	6 ft. @ 6 degree slope, Planked in
RAMPS		
	Length	45 in. x 96 in. Air Operated, Planked
	Width Extension	*NPO*: No more than 2 in. Between ramps
	Brackets	*NPO*: To hold ramp brace when not in use, 1 per side
GENERAL SPECIFICATIONS		
	Electrical System	Modular, Vapor Proof GROTE Ultra Blue
	Front Connector	SAE J560 7 Pin
	Lights	LED CMVSS 108 / FMVSS 108
	Finishing	Preparation by Steel Shot Blast, Commercial / Industrial Topcoat, Oven Baked
	Color	Black
	Mudflaps	1 set of BWS at rear
	Toolbox	Full A Frame mounted with solid bottom and cover
	Load Securement	9 pair of D-rings: 6 pr main deck, evenly spaced; 2 pr on B/T; 1 pr on main beam at headboard
	Fenders	3/16 in. deck plate
	Ladder	*NPO*: Ladders; 1 step at front on driver's side
GVWR Rating is based on standard configuration and a 15% Tongue weight distribution		

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical.
Equipment availability, prices and specifications are subject to change without notice.