



Hale Trailer Brake & Wheel

A013103-A013108

VINS: 82349-82354



FRAMELESS DUMP

Length	24'	Tarp Bar	NONE	Body	
Width	84" GENESIS INBOARD	Tarp	NONE	Accessories	96" TANDEM SPRAY SKIRTS AT REAR
Side Height	56" (54" + 2" ANGLE)	Bow Holders	NONE		
Top Rail	4-1/2" DUMP	Tarp Bows	NONE		
Side Matl-front	20' --- .100" WALL	Tarp Basket	NONE		
-middle	xxxxx	Tarp Hooks	NONE		
-rear	4' --- .140" WALL	Bulkhead Mat'l	3/16"		
Side Options	ANGLE ON SIDES	Bulkhead	NONE		
Floor Mat'l	1/4" FULL LENGTH	Options			
Crsmbr Spacing	12"	Body Fenders	NONE		
		Ladders (Out)	D/S-FRONT		
Floor Options	NO EAST LINER	Inside	D/S-FRONT-ANGLES		
		Shovel Hgr	NONE		
Tailgate Control	FRAME + ELEC CC (1)	Light Panel	LED 9-LIGHTS 000 000 000		
Body Pkg	NONE	Marker Lights	LED 3 PER SIDE		
Options		MMTS	IN PIVOT BRACKET		
Vibrator	NONE	Apron	NONE		
Mudflaps	STD + ACROSS REAR				

CHASSIS SPECIFICATIONS

Model	TANDEM	ABS	4S/2M	Tire Carrier	NONE
Length	PER ENGINEERING			Landing Gear	JOST AX150 D/S CRANK
Width	96"				
Draft Arms	ALUMINUM	Independ. Susp(s)	NONE		
Hoist	8-4-161				
King Pin Setting	16"	Distance:	N/A		
		From:	N/A		
5th Whl Ht	49"				
Rear Axle Setting	21.5"	Controls	N/A		
K/P To Rear Axle	250.5"				
Suspension	AAT30K/E2 / L-LIFT-E1	Location	N/A		
Susp Control	FRAME + ELEC CC (1)	Axle(s)	N/A		
Susp Spacing	52"	Accessories	N/A		
Susp Options	NONE				
Springs	AIR				
Axles	TP SPINDLES - 71-1/2" track	Brakes	N/A		
Accessories	NONE	Drums	N/A		
Brakes	16-1/2" x 7" EXTENDED LIFE	Hubs	N/A		
Drums	LIGHTWEIGHT				
Hubs	10-STUD LIGHTWEIGHT	Wheels	N/A		
	HXL-5 WHEEL PKG;GREASED				
Wheels	8.25" x 22.5" 8 HP	Tires	N/A		
Tires	11R 22.5 R196A BS				

REMARKS:

1. WIRED TO AUXILIARY PLUG
2. RAISE BULKHEAD AND GATE TO BE FLUSH WITH ANGLE
3. FRONT LIFT AXLE TO BE ACTUATED THROUGH FRAME SWITCH AND ELEC CC WIRED TO AUXILIARY
4. HENDRICKSON TIRE MAXX PRO INFLATION SYSTEM BOTH AXLES.

CHANGE 1

WEIGHT: 8.389

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.