

## Hale Trailer Brake & Wheel A013109-A013123 VINS: 39477-39491



BASE MODEL: FCLH	Combo Flat Lift Hauler	
components	description	
CAPACITY	Standard Beam Pkg - 80,000 GVWR (60,000 in 10' Span)	
OVERALL LENGTH	45'	
OVERALL WIDTH	8' 6"	
KING PIN SETTING	30" - Tapered Front	
UPPER COUPLER PLATE	1/4"	
UPPER COUPLER HEIGHT	48"	
FRONT SKIRT	Steel	
REAR SKIRT	Steel	
BULKHEAD	Removable Steel - 48" - No Side Return - 4 Posts DOT - (+387#) AC521	
MAIN FRAME	26" FabPreCamb.I-Beams-(80K Pkg)	
SIDE RAILS	6" - Alum- Extruded W/Double L Track	
FLOOR SILLS	4" Steel I-Beam 12" O.C. HD Pkg.	
COIL HAUL PACKAGE	None	
FLOOR DECKING	1-1/8" HD Aluminum W/4 Nailer Boards	
WINCH TRACK	Double L Aluminum- Extruded Siderail R/S Only	
TIE BAR	Curb Side - Full Length - 3/8" x 2"	
WINCHES	12 DOUBLE L (+)#75	
STRAPS	None None	
SUSPENSIONS	Spring Ride Hutch H9700 2 Axle 23K Fixed	
SUSPENSION LOCATION	Set 66" to CL of Rear Axle to Rear of Trailer	
AXLES	(2) 22.5K Capacity- Type 30 Chambers- Auto Slacks	
AXLE SPACING	49" (+35#)	
LANDING GEAR	Two Speed - Jost A500	
LIFT AXLE	None	
DUMP VALVE	None	
SCALES	None	
ABS SYSTEM	Wabco ABS System 2S/1M	
PARKING BRAKES	All Axles	
DUST SHEILDS	None	
TIRE INFLATION SYSTEM	None	
TIRES	11R 22.5- DOUBLE COIN	
WHEELS	Disc - Hub Piloted - 22.5 Steel	
ANTI-SAIL MUD FLAPS	Behind Rear Axle	
STAKE POCKETS	24" O.C. Sides & 4 Across Front	
SPOOL	Triangular Shaped	
RUB BAND ALUM	3/8" x 3" - Aluminum - Recessed for DOT Tape	
CARGO TIE DOWN	None	
TOOLBOX MATERIAL	None	
TOOLBOX TYPE	None	
TOOLBOX LOCATION	None	
TIRE CARRIERS	None	
LIGHTS	Grote Ultra Blue Sealed Wiring Harness- 2 Micros Per Side & Mid Turn-2/3/2 Rear	
CUSTOM LIGHTS	None	
FORK LIFT KIT MODELS	Universal MT Lift Hauler- Moffet M55 & Princeton PB50 W/Folding Bumper(AK643)	
FORK GUIDES	4ft Forks Non-Tubular Guides	
COUNTER BALANCE	45' = 1000#	
	EMFG. Only Responsible For Issuses With Listed Forklift Models	
PAINT BALANCE CLAUS	Black - PPG Epoxy Primer and Acrylic Polyurethane - Shot Blasted	
CUSTOM 1	None	
CUSTOM 2	None	
CUSTOM 3	None	
CUSTOM 4		
COSTOIN 4	None	