



## Hale Trailer Brake & Wheel

A013188-A013194

VINS: 39646-39652



Base Model: CVCT45x102 Spring Fixed

Serial #: 39646 - 39652

components description

CAPACITY 45FT 2Axle GVWR 66,290LBS

OVERALL LENGTH 45'

OVERALL HEIGHT FRONT 13'-1"

OVERALL WIDTH 8' 6" - 45ft

UPPER COUPLER HEIGHT 48"

UPPER COUPLER PLATE 5/16" Plate With Pick Up Eye

KING PIN SETTING 36"

SWING CLEARANCE 90"=36KP

LANDING GEAR Two Speed-Holland Mark "V" W/ 12" Channel Foot

\*\*Mark V Landing Gear.\*\*

SUSPENSIONS Spring Ride - Hutchens-2 Axle

SUSPENSION LOCATION Set at Rear Most Position

AXLES (2) 22,500K Capacity - Type 30 Chambers - Auto Slacks - ABS

AXLE SPACING 49"

LIFT AXLE None

WHEELS Disc - Steel - Hub Piloted- 22.5-(-56#)

TIRES 11R22.5-Manufacturer Choice

FRONT TYPE 10" Diagonal

FRONT MATERIAL Aluminum .063 - Pre Painted White Aluminum

LADDERS None

REAR DOOR TYPE Heavy Duty Aluminum Top Hinged Chip Gate - Top Half Open for Blow In W/Wear

Pads

REAR DOOR MATERIAL Heavy Duty Galvanized Mesh

SIDE SHEET MATERIAL .063 Aluminum Smooth(+140#)

SIDE POST Extruded Aluminum on 16" Centers

SIDE SHEET COLOR Pre Painted White

LOWER RAIL Heavy Duty - Aluminum Lower Rail

SIDE VENTS 7 Per Side - 22" in Height and Framed - Expanded Metal Vent Screen for 16" Post

Spacing

FRONT VENT None

INSIDE LINING Front - H.D. Aluminum Chip Sheild & 60"x30'.026 Galvanized Sht Top/Center

ROOF ASSY .063 Alum Smooth Sheet W/ Exp. Bows 16/16/16 CTRS

FLOOR Corr Fabricated Aluminum

FLOOR SILLS 4" Steel - Wax-Dipped I-Beam w/ Undercoating

LOAD BREAKERS 4 - 36" Apitong-Staggered on Floor(Tippers Only)

SILL SPACING 12"/16"/12" STD

DUST SHIELDS None

ANTI-SAIL MUD FLAPS Behind Rear Axle

BUMPER H.D. 3" x 4" Push Bumper

LIGHTS Sealed Wiring Harness W/ LED PKG

CUSTOM LIGHTS None

PAINT Silver - Rear Frame

UNDERCOAT Valspar - Black Corrosion Resistant

### DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical.

Equipment availability, prices and specifications are subject to change without notice.