



Hale Trailer Brake & Wheel

A013231-A013236

VINS: 63038-63043



Infinity Flat 48' Air Slider (Model: HAICF12SAT)

Length / Width: 48 feet x 102 inches

Suspension Type: Sliding air tandem; This Trailer Design Does NOT Meet Proposed GHG2 Compliance Requirements

Frame Rating: 80,000 lbs distributed - GAWR and tire ratings determine legal payloads

Flooring: 1 1/8 inch aluminum with 4 wood nailer strips

Crossmembers: 12 inch centers - 4 inch jr. I-steel

Single Coil Hauling Package: Included

Side Rails: Exclusive Revolutionary RASR Rail Technology -- one piece routed aluminum designed for strength and impact

Chain Cargo Tie Downs: 15 pair recessed in siderails

Stake Pockets: Routed aluminum on 24 inch centers (2 load securement openings between stake pockets)

Rubrail: Integrated with siderail

Main Beams: 130K load bearing flanges

Kingpin: 30 inches

Loaded Fifth Wheel Height: 49 inches

Landing Gear: OEM Standard with Forward & Rear Bracing

Knee Braces: Fabricated on approx. 60 inch C/C

Bulkhead Pockets: 4 DOT type bulkhead pockets only - welded to front

Bulkheads: Removable steel 4 post DOT type bulkhead - no turnback - 48 inches high with front pockets

Number of Axles: 2

Axle Spindle: Tapered

Brakes: Spring brakes, auto slacks

Air Line Filters: (2) Meritor In-line type installed

ABS: 4S/2M - no cable or tool

Axle Spread: 49 inches

Hub and Drums: 10-hole hub-piloted with outboard cast drums

Wheel Ends: Grease in hubs - *** 5-year wheel end warranty ***

Wheels: 22.5 x 8.25 steel disc wheels - pre-painted white - STANDARD

Tires: 11R 22.5 14PR OEM standard tires

Tire Inflation System: None standard

Suspension Detail: Hendrickson AAZNT46K Intraax air ride slider - 60 inches adjustable

Air Assist Slide Box Pins: Standard mount of controls on slider frame

Auto Glad Hand Dump: Installed

Front Corners: Tapered steel

Electrical System: LED: 3 lights/side, 2 lights/side on rear - STANDARD

Paint: Black urethane on steel parts with Infinity decals - STANDARD

Conspicuity Tape: Per NHTSA specs - installed in recess on rubrails

Bumper: Weld-on type - meets override requirements - painted steel

Mudflaps: 1 set OEM standard

Spare Tire Carrier: None standard

Winch Track: Full length integrated double L type aluminum on both sides -- STANDARD

Sliding Winches: 12: 6 each side; sliding Rope Hook/ Winch Strap Hook Retainers -- STANDARD

27 foot Winch Straps: None standard

30 foot Winch Straps: None standard

Dock Bumpers: 1 pair rubber on rear

Hubodometer: None standard

Registration Holder: Install registration holder - OEM standard

Tool Box: None standard

VIN Plate: Bilingual US/Canadian VIN plate

Please Note: Price includes commodity surcharges

Unit Numbers & Decals: Not available

Stacking: Price includes Standard stacking of each trailer

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical.

Equipment availability, prices and specifications are subject to change without notice.