



Hale Trailer Brake & Wheel A013237-A013245 VINS: 63192-63200

Velocity 48' Wide Spread Air (Model: HAVSF12WSA)

Length / Width: 48 feet x 102 inches **Suspension Type:** Wide spread air

Frame Rating: 80,000 lbs distributed - GAWR and tire ratings determine legal payloads

Flooring: 1 1/8 inch wood

Crossmembers: 12 inch centers - 4 inch jr. I-steel

Single Coil Hauling Package: Included

Side Rails: 6 inch structural channel @ 6.5 lbs/ft Stake Pockets: 3/16 inch steel on 24 inch centers

Pipe Spools: Double between stake pockets **Rubrail:** 3/8 inch x 2 1/2 inch steel

Main Beams: 130K load bearing flanges

Kingpin: 30 inches

Loaded Fifth Wheel Height: 49 inches

Landing Gear: OEM Standard with Forward & Rear Bracing

Knee Braces: Fabricated on approx. 60 inch C/C

Bulkheads:Removable steel 4 post DOT type bulkhead - no turnback - 48 inches high

Bulkhead Pockets: 4 - F-5 DOT-type steel

Number of Axles: 2
Axle Spindle:Tapered

Brakes:Spring brakes, auto slacks

Air Line Filters:(2) Meritor In-line type installed

ABS: 4S/2M - no cable or tool

Axle Spread: 122 inches - set at rear

Hub and Drums: 10-hole hub-piloted with outboard cast drums **Wheel Ends:** Grease in hubs - *** 5-year wheel end warranty ***

Wheels:22.5 x 8.25 steel disc wheels - pre-painted white - STANDARD

Tires:11R 22.5 14PR OEM standard tires

Tire Inflation System:None standard

Suspension Detail: Hendrickson AANT23K Intraax air ride

Auto Glad Hand Dump:Installed

Electric Dump Valve:Wired to 7-way auxiliary socket to dump rear axle

Air Lift:None standard Front Corners: Tapered

Electrical System:LED: 3 lights/side, 2 lights/side on rear- STANDARD

Paint:Black urethane with Velocity decals - STANDARD Conspicuity Tape: Per NHTSA specs - installed on rubrails

Bumper: Weld-on type - meets underride requirements

Mudflaps:2 sets OEM standard; Spring loaded brackets behind front axle

Spare Tire Carrier:None standard
Winch Track: Steel on road side
Sliding Winches:12 standard
27 foot Winch Straps:None standard
30 foot Winch Straps:None standard

Dock Bumpers: 1 pair rubber on rear

Hubodometer:None standard
Registration Holder:Install registration holder - OEM standard

Tool Box:None standard

VIN Plate: Bilingual US/Canadian VIN plate
Please Note: Price includes commodity surcharges

Unit Numbers & Decals: Not available