



Hale Trailer Brake & Wheel A013315-A013317 VINS: 39896-39898

Base Model: CW45x102 Air Slider

Serial #: 39896 - 39898 components description OVERALL LENGTH 45' OVERALL WIDTH 8' 6" - 45ft

OVERALL HEIGHT FRONT 12'-10"= 6" Bow Rise in tarp system included in height

UPPER COUPLER HEIGHT 48"
UPPER COUPLER PLATE 5/16" Plate

KING PIN SETTING 36"

SWING CLEARENCE 90"= 36KP

LANDING GEAR Two Speed

SUSPENSIONS AirRide - Holland CBX50 Slider - Front Lift - Axle Tapped For Future PSI

\*\*Air Gauge At Nose Roadside.\*\*

SUSPENSION LOCATION Slider/Variable

AXLES (2) 25K Capacity - Type 30 Chambers - Auto Slacks - ABS - Air Ride

\*\*Axles Tapped For Future PSI.\*\*

**AXLE SPACING 49"** 

LIFT AXLE Air Lift Front Axle - Air Ride

WHEELS Disc - Hub Piloted- 22.5- (-56#)

TIRES 11R22.5 General RA 16 PLY

FRONT TYPE 10" Diagonal

FRONT MATERIAL Aluminum .063 - Pre Painted White Aluminum

**LADDERS Aluminum Nose** 

REAR DOOR TYPE Heavy Duty Dry Van Style Door

\*\*Quad Door Locks.\*\*

REAR DOOR MATERIAL Galv./Quilted Stainless Steel Plywood

SIDE SHEET MATERIAL .063 Aluminum Smooth

\*\*Install .100 Rear Sheets (1) Per Side.\*\*

INTERIOR LINING None

SIDE SHEET COLOR Pre-Painted White

SIDE POST Extruded Aluminum on 12" Centers

\*\*Half Round Post.\*\*

LOWER RAIL Heavy Duty Aluminum Lower Rail

FLOOR HallcoWalkFloorSyst,6000Series,7/32"STDDeck,Alum.Sub,45'-102WD

\*\*3.5" Drive Unit With 24" Wear Pads. \*\*

FLOOR SILLS 4" Alum. I-Beams between L.G.& Susp. & L.G.& 5th Wheel

SILL SPACING 8"/10"/8" Heavy Duty

\*\*Alum Sills On 8" Centers Between Fifth Wheel and Landing Gear. \*\*

\*\*Alum Sills On 10" Centers in Bay Area.\*\*

PARKING BRAKES All Axles

**DUST SHEILDS None** 

ANTI-SAIL MUD FLAPS Behind Rear Axle

BUMPER H. D. 3" x 4" Push Bumper

\*\*Stainless Steel Rear Frame.\*\*

\*\*Cathedral Rear Frame.\*\*

TARP SYSTEM Shur-Co Brand Solid Lock and Roll-Frt&RrCap-0Bows-22oz-2Straps-45'-102WD

\*\*(3) 6" Arch Sidewall Stiffeners.\*\*

TARP COLOR BLACK

LIGHTS Sealed Wiring Harness W/ LED PKG

\*\*LED Back Up Lights Mounted in Bumper - Work Lights Inside Front - Wired to Front in Waterproof Switch.\*\*

\*\*5 Marker Lights Per Side Along Lower Rail.\*\*

PAINT Stainless Fifth Wheel and Rear Frame, Undercoat Black

**GAWR 24.5K** 

Reference #19560