

Hale Trailer Brake & Wheel

A013333-A013337

VINS: 82643-82647



EAST GENESIS UNLOADER TRAILER

OPEN TOP



CLOSED TOP



BODY:		TAILGATE:		CHASSIS:	
WIDTH (INCHES)	102	HEIGHT	FULL	MODEL	TANDEM
LENGTH (FEET)	45	TYPE	SINGLE	TYPE	ALUM SUB FRAME
HEIGHT (INCHES)	100	STYLE	GENESIS	AXLE TO AXLE	52"
SIDE MAT'L (OUTBOARD)	"GENESIS"	MAT'L THICKNESS	0.150	REAR AXLE SETTING	26-1/2"
FRONT	0.150	S / S HINGE ON	PASS. SIDE 4-3-4	5TH WHEEL HT	49"
MIDDLE	0.150	GATESEAL	NONE	PIN SETTING	36" + 3/8" KP PLATE
REAR	0.150	GATE LADDER	CAST -CENTER	SUSPENSION	AAT30K/E2-1 (8)
POLISHED SIDES	NONE	TARP HOOKS	NONE	SPRINGS	AIR
ROOF	NONE	WINDERS	ONE	AXLES	TP SPINDLES
ROOF MAT'L	NONE	GATE GUIDE	YES	BRAKES	16-1/2" x 7"
BULKHEAD	3/16" (1)(6)	GATE CONTROL	MECH - BOLT CLAW	DUSTSHIELDS	YES
TARP HOOKS	NONE	POCKETS	EXTRUDED	BRAKE CHAMBERS	STD
TARP BASKET	NONE	CROSSPIPE (S)	TWO	ABS	2S/1M
TARP	NONE		MIDDLE - TUBE TYPE -	HUBS	10 S STEEL
CATWALK	YES		REAR - TUBE TYPE	DRUMS"	CAST
B.H. LADDER	D/S-COMMERCIAL	COMPACTOR:		WHEELS	8.25 X 24.5 (9)
CROSSMEMBER	"1"BEAM- 12" C/L	SIDE LATCH	N/A		
FLOOR MAKE	KEITH - 3.5" DRIVES	CENTER LATCH		TIRES	11R 24.5 R196A
FLOOR MAT'L	#2299-1/2" IMPACT	PIN DIA.			BRIDGSETONE
WEARPADS	CWS	HYDRAULICS:		DOLLIES	2 SPEED JOST A451
TAPE COLOR	BLUE	HOSES	TWO-4000 PSI	LOCATION	D/S CRANK
LIGHT PANEL	LED IN TAILGATE	LENGTH	144"	BUMPER	STEEL
MARKER LIGHTS	LED (3)	FITTINGS	PUSH-PULL	TOW HOOK(S)	TWO
MIDMOUNT SIGNALS	LED - MODEL 60	HP	1" MALE	PUSH BLOCKS	YES (7)
MUDFLAPS	STD + (7)	LP	1" FEMALE	PAINT	SILVER
HOSE HANGER	ON BULKHEAD	HOSE LOCATION	DRIVER SIDE		
TIRE CARRIER	NONE	AIR & ELECTRICAL	DRIVER SIDE		

REMARKS: PRICE SUBJECT TO CHANGE 12 WEEKS PRIOR TO ESTIMATED BUIL DATE

1. YES INSIDE BULKHEAD STEPS.
2. WELD ENDS OF ALL CROSSMEMBERS TO BOTTOM RAIL.
3. 3 PAIR PER SIDE LED TOP & BOTTOM. GROMMETS IN ALL LOCATIONS WHERE WIRE PASSES THROUGH METAL.
4. FILTERED GLAD HANDS.
5. ALUMINUM AIR TANKS TO HAVE CABLE OPERATED DRAINS EXTENDED TO D/S BOTTOM RAIL.
6. ADD ACCESS HOLE IN FRONT DRIVERS SIDE OF BULKHEAD THROUGH 5th WHEEL PLATE BAND FOR FUTURE ACCESS TO STEEL HYDRAULIC TUBES. FINISH OFF WITH SMALL COVER PLATE SECURED WITH TEC-SCREWS.
7. ADD REAR CENTER CHASSIS MUDFLAP
8. MANUAL EXHAUST SWITCH ON D/S SUBFRAME
9. 4 STEEL DISC INSIDE, 4 HP ALUMINUM DISC OUTSIDE. ADD PLASTIC INSULATOR BETWEEN STEEL AND ALUMINUM WHEELS.
10. ADD REGISTRATION HOLDER TO D/S LANDING GEAR BRACKET TRUCKLITE 536-05015-20.
11. STANDARD NYLON T BLOCKS

OVERALL HEIGHT (FT)

12.92

EMPTY WEIGHT (#)

17,287

CUBIC YARDS

112

(EMPTY WEIGHT VARIANCE +/- 3%)

BODY/FAB/INSPECTION/FRAME/INVENTORY/SALES/TIRES/PAINT/ACID

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical.

Equipment availability, prices and specifications are subject to change without notice.

