



Hale Trailer Brake & Wheel

A013449-A013454

VINS: 7243-7248

Model: **ALUMINUM-ARA**



Item	Description
TANK CONSTRUCTION	ARA
CAPACITY	7250 GALLONS (7500 GALLONS SHELL FULL)
OUTAGE	1 PERCENT (MINIMUM)
CODE	49 CFR 173.247
DESIGN PRESSURE	ATMOSPHERIC
VENTING	ASPHALT TYPE, LIGHT WEIGHT STYLE
TEMPERATURE RATING	375 DEGREE
MATERIAL-BARREL	5454-H32 ALUMINUM
SURGE PLATES	(2) ALUMINUM
COMPARTMENTS	ONE
CAPACITY MARKERS	3-DISC
INSULATION	4" FIBERGLASS, 1# DENSITY, NOT COMPRESSED
ALUMINUM JACKETING	0.040" SIDE SHEETS/0.060" HEADS
REAR DISCHARGE VALVE	6" VALVE W/ 3" LINE & CAMLOCK CAP. INCLUDES 3/4" PORT FOR WASHOUT CONNECTION.
FRONT PUMP-OFF VALVE	3" VALVE W/ SWIVEL & INTERNAL LINE, OUTLET TERMINATING WITH A 3" CAMLOCK ADAPTER & CAP. INCLUDES 3/4" PORT FOR WASHOUT CONNECTION AND 8' HOSE TROUGH ON RH FRONT FENDER.
GATE VALVE	4" AT REAR UNLOADING LINE
THERMOMETER	3" DIAL IN WELL W/ PLEXIGLASS COVER
MANHOLE	20" ASPHALT TYPE
MANHOLE PLATFORM	4 SIDED, ALUMINUM
DEFLECTOR PAN	BENEATH MANHOLE
MANHOLE OVERFLOW	2" EXTERNAL
HEATING SYSTEM	NONE
LADDER	ALUMINUM-CURBSIDE
WALKWAY	NONE
HOSE TROUGH	12" WIDE, ALUMINUM
TIRE CARRIER	NONE
FENDERS	ALUMINUM, FRONT & REAR WITH MUDFLAPS ON REAR FENDERS. MANUAL HOLDER ON FRONT ROADSIDE FENDER
LIGHTS	L.E.D. TYPE WITH ALUMINUM LIGHT BOXES @ REAR
GLAD HANDS	LOW MOUNT
BUMPER-SPLIT TYPE	WITH SLOPING OUTLET
CONSPICUITY MARKING	PER DOT REQUIREMENTS
UPPER COUPLER	ADJUSTABLE
LANDING LEGS	2-SPEED, CURBSIDE CRANK WITH HORIZONTAL BRACE BETWEEN LANDING LEGS
LANDING LEGS	ADDITIONAL FORWARD BRACING
BOGIE	ALUMINUM



SUSPENSION	INTRAAX AANT23K AIR RIDE TANDEM W/MANUAL EXHAUST MOUNTED ON REAR CROSSMEMBER
OIL SEALS	HXL5 (5 YEAR WARRANTY)
AIR BRAKES	16.5" X 7" W/AUTO SLACKS AND CENTRIFUSE DRUMS
ANTI-LOCK BRAKES	2S/2M SYSTEM (2 SENSORS/2 MODULATORS)
AXLES	22,500# BEAM RATING WITH HP BEARINGS
HUBS	DURALIGHT
ALUMINUM DISC WHEELS	ACCURIDE 10-HOLE, HUB PILOTED, STANDARD POLISH
TIRES	11R22.5-G
AUTOMATIC TIRE INFLATION SYSTEM	AXLES PREPARED FOR TIREMAAX PRO, SYSTEM NOT INSTALLED
PAINT	STEEL PARTS ONLY-BLACK
CENTER PAINT BAND	14' WIDE BAND-BLACK
PLACARD KIT	SLIDE-IN TYPE W/ " HOT" PLACARD, 4 SIDES
SAMPLE VALVE	3/4"
HUBODOMETER	ON DRIVER SIDE REAR AXLE

Etnyre reserves the right to modify pricing on all quotes and orders with material and labor surcharges as needed

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical.
Equipment availability, prices and specifications are subject to change without notice.