

# HALE

## TRAILER

### BRAKE & WHEEL

## Hale Trailer Brake & Wheel

013595-013603

### 68791 TK85EFX, 5 section, 52'-7 1/2" closed, 177'-9" open, (195'-13223-TK85EFX

#### STANDARD EQUIPMENT

85,000-lb. capacity

8'-6" wide

9'-2" gooseneck (detachable, low profile)

19" kingpin setting

49" 5th wheel height

58" front platform height (102" wide, 28" long)

Slide-able rear platform (102' wide, 36" long)

45 deg. tapered front corners

Heavy duty front pullout/rotate down stabilizing legs

Narrow Mono-beam design with 4 stages

Kingpin steering

15 ft. non-loadbearing pull-out rear extension

Tritronic remote control with auto align function

Remote can be used wireless or cord type

42 deg max steer angle (3rd axle)

Self-contained hydraulics

Hydraulic support leg to aid in closing and opening

Individual aluminum fenders

3 axle-72" axle spacing

4S2M Anti-lock brakes

Steel hub-piloted - cast drums

6.75 x 17.5 8-hole disc wheels

235/75R X 17.5 tires

Red & white conspicuity markings

Blasted prior to paint

Color: Trail King 2-part polyurethane

Item #	Category	Description	Weight (lbs)	Qty
68983	Open Deck	68791 TK85EFX, 5 section, 52'-7 1/2" closed, 177'-9" open, (195'-9" including pull-out) 102" wide, 11'-8 1/2" gooseneck with 104" swing clearance, 13HP Honda SCU, (1) 36" X 102" sliding platform at rear, rear pullout (18'), 3 axle		
13230	Landing Gear	2-speed landing gear		
13232	Suspensions	Air ride suspension HT250		
13234	Axles	25,000 lb. cap. Axle (5/8" wall)		
13257	Wheel Finish	6.75 x 17.5 8-hole machined aluminum wheel (inside)		6
13261	Wheel Finish	6.75 x 17.5 8-hole polished aluminum wheel (per wheel) ILO Std 6.75 x 17.5 8-hole machined aluminum wheel		6

07907	Tire Size	235/75R17.5 - 18 ply HTL2 (tire only) (per tire)
10059	Spare Tires	No spare tire
13241	Hydraulics & Controls	Hydraulic turntable style steering
13245	Hydraulics & Controls	13 hp Honda (ILO diesel)
08024	Paint	Black S7203 with white decals (735-432-039)

**13223-Additional Options**

Item #	Category	Description	Weight (lbs)	Qty
68791	Custom Options	68791 TK85EFX, 5 section, 52'-7 1/2" closed, 177'-9" open, 102" wide, 11'-8 1/2" gooseneck with 104" swing clearance, 13HP Honda SCU, (1) 36" X 102" sliding platform at rear, rear pullout (18'), 3 axle		
68983	Custom Options	68983 TK85EFX-5 Move SCU to rear of trailer behind axles. Move axles ahead 56" to allow room for the SCU  <i>SCU Box Frame to have weep holes drilled into the tubes.</i>		
76632	Custom Options	76632 EFX - Isolate the accelerator for use when manual steering		
09999-01	Custom Options	4" strobes in addition to 3rd tail light package.		
08569	Miscellaneous	DOT Inspection		

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.