



# Hale Trailer Brake & Wheel

## A013668-A013719

### VINS: A2960-A3009

<b>Xcalibur Extendable 48ft - 80ft Spring Slider Tandem (Check with your Fontaine Sales Rep for Pricing)</b> <b>(Model: XCALIBUR XTP4880SS2)</b>	
	Est. Wt.: 16,230# +/- 3%
<b>Capacity:</b> 80,000 lbs distributed - self-supporting, properly blocked	
<b>Length:</b> 48 feet (closed) to 80 feet (open)	
<b>Width:</b> 8 feet 6 inches	
<b>Kingpin:</b> 24 inches	
<b>Loaded Fifth Wheel Height:</b> 49 inches	
<b>Landing Gear:</b> OEM Standard	
<b>Bulkheads:</b> None	
<b>Bulkhead Pockets:</b> 4 - F-5 DOT-type steel	
<b>Front Corners:</b> Tapered	
<b>Suspension:</b> Sliding spring tandem	
<b>Frame Rating:</b> 80,000 lbs distributed - self-supporting, properly blocked	
<b>Load Scale:</b> None Standard	
<b>Main Beams:</b> Minimum grade 80 flanges	
<b>Crossmembers:</b> 12 inch centers - 4 inch jr. I-steel	
<b>Side Rails:</b> 6 inch structural channel @ 6.5 lbs/ft	
<b>Stake Pockets:</b> 3/16 inch steel on 24 inches centers	
<b>Rubrail:</b> 2 1/2 inch x 3/8 inch thick HD mill formed steel	
<b>Conspicuity Tape:</b> Per NHTSA specs - installed on rub rail	
<b>Flooring:</b> 1 1/8 inch wood	
<b>Winch Track:</b> Full-length steel on road side	
<b>Sliding Winches:</b> 12 - without straps	
<b>Winch Straps:</b> None	
<b>Air and Electrical @ Extension Locks:</b> Inside track system	
<b>Tool Box:</b> None	
<b>Bumper:</b> Meets underride requirements	
<b>Mudflaps:</b> 1 set Fontaine	
<b>Number of Axles:</b> 2	
<b>Axle Spindle:</b> Tapered	
<b>Axle Spread:</b> 49 inches	
<b>Brakes:</b> Spring brakes, auto slacks	
<b>Dust Shields:</b> None	
<b>Suspension:</b> Sliding spring tandem	
<b>Suspension:</b> Hutch H-9700 3 leaf spring slider - 60 inch adjustable	
<b>Frame Rating:</b> 80,000 lbs distributed - self-supporting, properly blocked	
<b>ABS:</b> 2S/1M - no cable or tool	
<b>Load Scale:</b> None Standard	
<b>Hub and Drums:</b> 10-hole hub-piloted with outboard cast drums	
<b>Wheel Ends:</b> Grease in hubs	
<b>Wheels:</b> 22.5 x 8.25 steel disc wheels - pre-painted white -	
<b>Tires:</b> 11R 22.5 14PR OEM Standard tires	
<b>Hubodometer:</b> None Standard	
<b>Tire Inflation:</b> None Standard	
<b>Electrical System:</b> Sealed harness and LED Lights: 3 lights per side on rear with 4 inch flush mounted amber strobes (no battery back-up)	
<b>Additional Marker Lights:</b> None Standard	
<b>Paint:</b> Fontaine black polyurethane enamel	
<b>VIN Plate:</b> Bilingual VIN plate	
<b>Registration/Document Holder:</b> Registration/document holder installed	

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.