



**Hale Trailer Brake & Wheel**  
**A013727-A013728**  
**VINS: 64608-64609**



PEERLESS TRANSPORT SEMI: Dual Axle, Live Floor, 53' Length, 18.4 Units

STANDARD SPECIFICATIONS: **CTSSF-53**

Type: Peerless dual axle, transport semi-trailer

Design: Box design, flat floor, end dump, live floor, **9" front mitered corners**

Construction: **.063 prepainted white skin stressed aluminum with aluminum exterior posts (21.5" centers)**  
North skin design

Unloading Time: Approximately 8 minutes

Lower Rail: **¼" extruded aluminum**

Capacity: 18.4 units (136.3 cu yd)

Dimensions: **53' long, 8'6" wide, 13' 6" high, 37" king pin location, 36" rear axle from rear of trailer**

Tires: Eight (8) **295/75R 22.5 radial tires**

Wheels: Eight (8) 22.5 x 8.25 - 10 hole, 11 1/4" B.C. **aluminum unimount wheels, polished outside steel inside**

Axles: **25,000# cap., 77 1/2" track, 10 stud, 11 1/4" B.C. hubs, outboard drums, oil seals, quick change brake shoes, auto slacks**

Brakes: 16 1/2" x 7" air, CM18 lining, type 3030 air chambers, DOT relay emergency system

A.B.S.: 2 sensor - 1 module

Suspension: **Hendrickson AAT25K air ride with quick draw slider- Front axle lift, manual dump valve**

Scales: **Air gauge scale mounted on front driver's side corner**

Landing Gear: Two speed, crank on driver's side (**Holland Atlas 55**)

King Pin: Standard SAE, heat treated, **37" setting, 49" height / 40'0" king pin to center of rear axle**

Cross Sills & Decking: **Keith 3/16" two way standard live floor, 4" aluminum I-Sills on 12" centers with 4" steel Jr. I-Beams over suspension with aluminum sub-deck, Fold-up slope sheet in front**

Top: Flat design, open top, **three flat center ties**



Top Cover: **Roll Rite electric roll over tarp, rear flex arm, key fob control.**

Rear Door: **Full opening, side hinged, solid freight doors skinned with white aluminum, (4) lock rods, solid door hold back, "offset" hinges and door header turned sideways**

Ladders: **One located at front**

Rope Hooks: **None**

Hydraulic Hoses: **Not Furnished**

Mud Flaps: **Legal, rubber**

Wiring: **Unitized wiring system, 12 volt**

Lights: **Four (4) legal DOT combination stop, tail and directional lights. Legal DOT clearance lights, five (5) clearance lights top and bottom each side, all lights to be LED**

Reflectors: **Legal DOT**

Paint: **Aluminum white, steel components primed and painted black**

Weight: **Approximately 15,381#**

**DISCLAIMER**

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.