



Hale Trailer Brake & Wheel

A013889-A013891

VINS: 42579-42581

Talbert Manufacturing, Inc.

Model: AC-20-AR

Capacity in tons: 20

1. TONGUE

Pintle eye
Tongue

Adjustable pintle eye (3" ID) with 48" chain and grab hooks
5'-6" with lockable tool box with aluminum diamond plate lid - move hinge 4" forward

Drop leg

2-speed, 50,000# crank down dual landing leg, mounted to main beams and headboard

Electrical receptacle
Headboard

Seven pin connector
8" high full width

2. DECK

Deck section design
Deck section length
Deck section width
Loaded deck height
Flooring
Lash rings

One piece tongue, main beam and beavertail (cold formed)
27'-0" (21'-0" flat with 6'-0" beavertail)
8'-6"

32-1/4"

1-1/2" apitong with individual wheel wells

10 total -

4 each side on flat deck (straight style), 8 total

1 each side on beavertail (straight style), 2 total

Mainbeams
Crossmembers
Sidemembers
Beavertail
Ramps

12" deep hi-tensile

6" deep hi-tensile

8" deep hi-tensile

6'-0" with wood flooring full width

38" wide x 6'-0" long air ramps with wood flooring, stored vertically with lock bar

3. RUNNING GEAR

Number of axles
Axle capacity
Brakes
Wheels
Tires

2

25,000#, full width track

12-1/4" x 7-1/2" air with 2S/1M ABS. Spring brakes on both axles.

Steel disc with oil seals (6.75 x 17.5)

Eight (8) 215/75R17.5 (H) 16PR radials

Use valve stem extensions on inside wheels

44,800# Hutch spring

Suspension

4. GENERAL

Lights and wiring

12 volt LED system (license plate regular), supplied with female 7-way plug on tongue, SUPPLY JUMPER CORD FOR TRUCK

Paint

Valspar standard Talbert black

Estimated empty weight

9,140#

Additional general specifications

Formed step in front of 1st axle both sides of trailer

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.