



Hale Trailer Brake & Wheel
 A013984-A013985
 VIN: 00460--00462



53ET3XP	
53 ft. Tridem	
Paving & Recovery	
Base Weight:	18,540

TRAILER

Overall Length	53 ft.
Overall Width	102 in. (Over width permits may be required)
Weight lbs +/- 2%	19759, including options
Spacing	*NPO*: King pin to center of rear axle not to exceed 42 ft 11 in.

GOOSENECK

Coupler	Weld in King Pin
Coupler Plate	5/16 in. Hi-Tensile, 48 in. Height
Coupler Location	18 in.
Length	10 ft. 6 in.
Cross Members	Hi-Tensile 4 in. Jr. I-beam @ 16 in. O/C
Swing Clearance	83 in.
Floor	1 1/8 in. Shiplapped Apitong/Keruing
Web	1/4 in. Hi-Tensile

DECK

Deck Length	35 ft. 1 in.
Loaded Deck Height	35 in.
Main Frame	3/8 in. x 5 in. Top Flange and 1/2 in. x 5 in. Bottom 100 KSI
Cross Members	Hi-Tensile Standard 4 in. I-beam @ 12 in. O/C on Lower Deck w/ Knee Braces
Side Rail	6 in. @ 8.2 Channel
Web	3/16 in. Hi-Tensile
Landing Gear	Dual 2 Speed
Floor	1 3/8 in. Shiplapped Apitong/Keruing with 3/16 in. Deckplate over the wheels
In Floor Chain Box	1 - located at rear of Gooseneck, 1 - located at rear of main deck, with deckplate covers included

SUSPENSION/AXLES

Axles	25,000 lbs Capacity
Air Lift	Air Lift c/w Control Box: lead axle
Spread	*NPO*: 60 in.
Suspension	Ridewell RAR 260 U/S 6 1/2 in. Air Ride 25,000 lbs - includes air gauge and dump valve in enclosure
Brakes	Quick Change 12 1/4 in. x 7 in.
Brake Chamber	#3030, All Axles
Air Brake System	2S/1M
Air Tank(s)	Aluminum
Slack Adjusters	Automatic
Camshafts	28 Spline Non Enclosed
Hubs & Drums	8 Stud Unimount C / W Cast Drums
Tires	Tire Upgrade to 245/70R17.5 Continental HTL2 ECO
Wheels	Alum. Wheel Pkg. 17.5 (6 steel, 6 polished)

BEAVERTAIL



53ET3XP
53 ft. Tridem
Paving & Recovery

BEAVERTAIL

Length 6 ft. @ 8 degree slope, Planked

RAMPS

Rear 45 in X 11 ft. Air Operated Bi Fold - Planked

Main Deck to G/N 12 ft. Inset Full width Air Operated - Planked

Main Deck to G/N *NPO*: Ramp Prop Access Covers

GENERAL SPECIFICATIONS

Electrical System Modular, Vapor Proof GROTE Ultra Blue

Lights LED CMVSS 108 / FMVSS 108

Front Connector SAE J560 7 Pin

Rear Connector 4 Pin Plug

Finishing Preparation by Steel Shot Blast, Commercial / Industrial Topcoat, Oven Baked

Color Black

Mudflaps 1 set of BWS at rear

Load Securement * Moulded Rub Rail, Stake Pockets and Spools 24 in. OC (Over all Width affected by option as shown)

Load Securement 15, Pair of in Floor Flush Mounted D-Rings: 3 pr GNK; 2 pr B/T; start directly aftr front ramp - 10 pr main deck, evenly spaced

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.