



Hale Trailer Brake & Wheel

A014061-A014066

VIN: S013563-S013568



**Revolution 52 Alum Flat 48' Wide Spread Air  
(Model: HAR5212WSA)**

<b>Length / Width:</b> 48 feet x 102 inches
<b>Suspension Type:</b> Wide spread air
<b>Frame Rating:</b> 80,000 lbs distributed - 52,000 lbs concentrated in 4 feet- GAWR and tire ratings determine legal payloads
<b>Flooring:</b> Knurled extruded 3-1/8 aluminum, <b>StirLITE Friction Stir Welded Floor</b> with 2 wood nailer strips; Heavy wall extrusions in single coil area; Heavy wall extrusion at rear
<b>Side Rails:</b> Exclusive <b>Revolutionary RASR Rail Technology</b> -- one piece routed aluminum designed for strength and impact
<b>Stationary Chain Cargo Tie Downs:</b> 15 pair - recessed in siderails
<b>Stake Pockets:</b> Routed Aluminum on 24 inch centers (2 load securement openings in between stake pockets)
<b>Rubrail:</b> Integrated with side rail
<b>Main Beams:</b> Extruded aluminum - 8.25 inch flange
<b>Kingpin:</b> 30 inches
<b>Loaded Fifth Wheel Height:</b> 49 inches
<b>Landing Gear:</b> Jost AX100G19 <b>ALUMILIGHT Aluminum Landing Gear</b> with forward & rear bracing
<b>Bulkheads:</b> None standard
<b>Number of Axles:</b> 2
<b>Axle Spindle:</b> Tapered
<b>Brakes:</b> Spring brakes, auto slacks, Aluminum air tank
<b>Air Line Filters:(2) Meritor In-line type installed</b>
<b>ABS:</b> 4S/2M - no cable or tool
<b>Axle Spread:122 inches - set at rear</b>
<b>Hub and Drums:10-hole hub-piloted with outboard cast drums - STANDARD</b>
<b>Wheel Ends:</b> Grease in hubs - *** 5-year wheel end warranty ***
<b>Wheels:22.5 x 8.25 Steel disc wheels - pre-painted white - STANDARD</b>
<b>Tires:11R 22.5 14PR premium OEM standard tires</b>
<b>Tire Inflation System:</b> None standard
<b>Suspension Detail:</b> Hendrickson AANT23K Intraax air ride
<b>Auto Glad Hand Dump:</b> Installed
<b>Electric Dump Valve:</b> Wired to 7-way auxiliary socket to dump rear axle
<b>Air Lift:</b> None standard
<b>Front Corners:</b> Tapered
<b>Electrical System:</b> LED: 5 Lights/Side; Rear with 3 4-inch Round Lights/Side, 3 Round Lights Center Cluster
<b>Other Electrical Specifications:</b> 4 way socket on rear with one hot/one ground pin for wide load and strobe light connections
<b>Paint:</b> Black urethane on steel parts with <b>Revolution decals - STANDARD</b>
<b>Conspicuity Tape:</b> Per NHTSA specs - installed in recess on rubrails
<b>Bumper:</b> Bolt-On; Meets underride requirements
<b>Mudflaps:</b> 2 sets <b>OEM standard; Spring loaded brackets behind front axle</b>
<b>Spare Tire Carrier:</b> None standard
<b>Winch Track:</b> Dual full-length integrated aluminum -- double L design
<b>Sliding Winches:</b> 12 standard; 6 each side; sliding rope hook/ winch strap hook retainers - <b>STANDARD</b>
<b>27 foot Winch Straps:</b> None standard
<b>30 foot Winch Straps:</b> None standard
<b>Sliding J-Hook for Ring vs. Flat Hook on 4" Strap:</b> None standard
<b>Dock Bumpers:</b> 1 pair rubber on rear
<b>Hubodometer:</b> None standard
<b>Registration Holder:</b> Install registration holder - <b>OEM standard</b>
<b>Tool Box:</b> None standard
<b>VIN Plate:</b> Bilingual US/Canadian VIN plate

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.