



Hale Trailer Brake & Wheel
A014067-A014071
VIN: 416801-416805



Product : , , , ,

GVWR

GVWR: Trailer to meet 68,000 Pound GVWR
 VIN PLATE: US - VIN Plate to Read in English (Standard)
 Product Type: HT Thermotech-Truck Load w/Swing Door
 Product Class: HT Thermotech TL

GEOMETRY

Length - Exterior: 53'-0"
 ** Length - Interior: 52'-2"
 Width - Exterior: 102.36"
 ** Width - Interior: 97.4"
 Height - Exterior: 13'-6"
 ** Height - Interior: 103.5"
 Deck Height: Standard application
 Fifth Wheel Height: 47"
 King Pin Location: 36"
 Landing Gear Location: 105" from King Pin (+ 1"/-1/4")

TIRES & WHEELS

Tire Furnished: Factory Furnished
 * Tire Manufacturer: Continental HTL1, Low Rolling Resistance Tire
 * Tire Size: 445/50R22.5
 Wheel Furnish: Factory Furnished
 * Wheel Material: All Aluminum Wheel
 * Wheel Manufacturer: Alcoa
 * Wheel Size: 14 x 22.5 (Aluminum, For Super Single) w/2" offset
 * Wheel Finish for Steel: None (Due to All Aluminum Wheel Application)
 * Tire Stem Valve Position: Super Single Aluminum Wheel
 * Wheel Finish for Aluminum: Aluminum Disc DuraBrite Polished w/2" Offset (For Super Single Tire - Alcoa Only)
 * Wheel Accessories: Install Wheel Separator (Spacer) Wheel vs Drum
 Valve Stem & Cap: Valve Stem & Metal Dome Cap

UPPER COUPLER

Upper Coupler-Reefer: 4.00" deep, Floor Over Coupler and Running to Front, Bolting Type
 Approach Plate: 3/16" thick 80,000 Lb Yield - 6 Support Channels
 King Pin (BTM Main) Plate: 1/4" thick 80,000 Lb Yield
 King Pin & Manufacturer: Standard (Jost) AAR Cruciform King Pin
 Front Bottom Rail: Stainless Steel & Stainless Steel Wrap-Around Impact Guard Striker Angle

BODY/BASE

Forward Crossmember: 4" Extruded Aluminum I-Beams: 12" C/L
 Landing Gear Crossmember: 4" Steel I-Beams (80,000 PSI) : 12" C/L (5ea)
 Bay Area Crossmember: 5.5" Extruded Aluminum I-Beams : 12" C/L
 Running Gear Crossmember: 4" Steel I-Beams (80,000 PSI) : 12" C/L with 8" C/L Last 4' (For Reefer Van only)
 Slider Body Rail (RV): 204" Rail Length
 Slider Rail Supplier: Hutchens Slider Rails
 Slider Rail Duty: Standard Duty
 Slider Rail Hole Space & Dia.: 4" increments holes with large diameter holes (Hutch & Binkley)
 * Fuel Tank Location: None, Prepare with fuel line conduit thru landing gear, forward & UC

FLOOR

Floor- Assembly Method:	Aluminum Floor Assembly with Weld (MIG). Seams to be Continuously / Uniformly Weld
* Floor-Detail Spec. - RV:	1.34" Extruded Aluminum (6061-T6) NW Flat Floor
Floor-Surface Spec. - RV:	Ridged Floor Surface with Safety Grip (Knurled)
* Rear Gutter & Trough:	Flush w/ Top of Floor (Mig) & w/o Trough -> Floor Plank will be extended to rear gutter (FLAT & DIARY TYPE STD)
Floor Ratings - RV:	18,000lb Rated Floor
Floor Drain - RV:	(4) Drains w/ Kazoo
Floor Filler Mat'l:	I-Filler (Ridge PVC)
* Floor Inserts -RV:	Extruded Aluminum 72" Long and Full Width

FRONT

Front Corner Radius:	6" Extruded Aluminum STD Duty Post (RV)
Front Panel & Color - RV:	0.04" Aluminum Prepainted White w/ Aluminum Insert
* Corner Radius Insert - RV:	0.035" Stainless Steel
Front Posts:	(4) Posts - (2) 3.15" Deep Steel Hats / (2) AL "Z" Post
Gladhands:	Phillips Qwik-E with Filters Control Line Only. Overlaid(Back open)+ aluminum plate
Front Receptacle(7-Way):	Phillips 7-Way w/ 3" Deep, No Circuit Breaker (HT Reefer STD)
Gladhand/7-Way Location:	Overlaid on Lower Roadside Front
Reefer Unit Front Frame:	Brace for type "A" (Large Opening)

RV-VAN ITEM

Reefer Unit Manufacturer:	Carrier
Reefer Unit Type:	Single-Temperature Type
Reefer Unit Spec.:	Carrier Single-Temp
* Reefer Unit Furnish:	Prep only for future installation after delivery
* Reefer Unit Install:	Customer or Other Install. Cut & Seal Hatch w/ Plywood for Shipment

SIDE

Side Material:	0.04" Aluminum Prepainted White w/ natural color rivets
Side Posts:	1.0" Deep Extruded Aluminum "Z" Post (STD)
Side Post Centers:	24" C/L with 12" C/L @ Upper Coupler and Support Gear
Side Top Rail:	Standard Side Top Rail for Thermotech
Side Bottom Rail:	Side Bottom Rail for Reefer 5.5" High Bay Crossmember - TL Thermotech
* Side Rub Rail:	(2) Alum Exterior Rub Rail (E15-032 One 1-1/8" Tear Drip) on Each Side-Total 4. No Higher than 6" above Bottom Rail & just below Side Top Rail
Fasteners to Bottom Rail:	Standard Rivets to attach C/Members to the Side Bottom Rail

REAR

* Rear Frame:	Swing Door Reefer Rear Frame (w/1 SUS Lock Rod per LH & RH Door)
Rear Door Opening Spec.:	Swing Door - HT Standard Reefer Door Opening Application (97.2" Width).
Corner Post Feature:	Standard
Door Sill Level (RV):	Door to Flush with Floor (HT STD)
Door Sill Feature:	Standard
Door Header Feature:	Standard
Door Type (RV):	Swing Door w/ Aluminum Frame & (1) Rubber Door Bumper on Each Door (HT Standard)
* Door-Outer Cover (RV):	Swing Door-Stainless Steel Mirror Finished Outer Cover Sheet
Door-Inner Lining (RV):	Swing Door-PP050 (0.043") Polar X
* Door Scuff:	Install 0.19" Extruded Aluminum x 16" high rear door scuff
* Door Grab Handle:	INSTALL 36" HANDLE ON ROADSIDE(L/H) ON SWING DOOR
Option - Door Install Instruct (RV):	Standard Door Installation Per Manufacturer's Recommendation
Option - Door Hold Back (RV):	Standard for Swing Door
Hinges:	Four (4) Aluminum Hinges per Door
Rear Underride Guard:	4" Tube Bolt on Assembly w/ Welded Perforated(Pooched) Horizontal. Rear Impact Guard (RIG30-NEW)
Option - Horiz Member/Other:	One piece roll formed w/continuous welding
Underide Bolt Spec.:	Stainless steel bolts & nuts - Optional
Dock Bumper:	Pair 3 X 5.88 HT High Performance Polyurethane Radius Bumper ATRO Black Color

Rubber Bumper Location: Inboard of Light Protector Bars (Standard)

LIFT GATE

ROOF

Roof Panel: 0.025" One Piece Corrugated Aluminum
Roof Bow: 1" Extruded Aluminum
Roof Bow Centers: 32" Centers Full Length

LINING/SCUFF

Side Lining - Reefer: Polar X Pp050 0.043"
Front Lining - Reefer: Polar X PP050 0.043"
Roof Lining - Reefer: Polar X PP050 0.043"
Sub-Floor: Polar X Pp030 0.023"
Side Scuff Mt'g Method: Recessed (STD)
* Side Scuff for Reefer: 16" High Extruded Aluminum
* Logistic Track for Reefer: (2) Row of "E" Track, Galvanized, Both Side
* Logistic Track Mt'g Method: Recessed (Horizontal)
* Logistic Track Locate: Located at 36" & 72" Floor to Centerline of Track

URETHANE INSULATION

Front Insulation: Front Insulation - 4" Polyurethane
Side Insulation: Side Insulation - 2" Polyurethane
* Roof Insulation: Roof Insulation - 3" Polyurethane
* Floor Insulation: Floor Insulation - 3" Polyurethane
Door Insulation: Swing Door-Insulation - 3" Polyurethane

LANDING GEAR

* L/Gear Spec.: Jost HT451.G3.17.157 Magnum 10 Year Warranty Full HDG
L/Gear Mt'g Method: Inboard Mounting (Standard)
L/Gear Shoes: 10" X 10" RCF (Removable Cushion Foot) Low Profile
L/Gear Ground Clearance: Nom. 12" Ground Clearance
L/Gear Mt'g Bracket: Hot Dip Galvanized Large Wing Plate
L/Gear Crank Handle: Roadside
L/Gear Options: None (HT STD)
L/Gear Cross Brace Design: HT Standard Cross Brace attachment Design

RUNNING GEAR

Bogie Type: Sliding Tandem(2) Axle Bogie
Axle Spacing: 49" Axle Spacing
* Axle ABS System: Tandem Axle w/4S2M ABS System
Bogie & Axle Location: Location to be Sliding Tandem Axle for specified slider Length w/Stop Bars @ Front & Rear
Option-Related Bogie Stopper Feature: STD plug stopper
Susp. Manufacturer: Hendrickson
Suspension Capacity: Standard Duty
* Hendrickson Susp. Specification: Hendrickson Ultraa-K Air Ride
Surelok (Anti-Dock): Surelok (Anti-Dock) Installed
Locking Pin Mechanism: Air-Assist Pin Puller or Quik Draw
Susp. Sub-Frame: Hendrickson K-2 STD Duty
Type of Susp Spring: Air Bag
Spring Specification: Air Bag
* Axle Diameter: 5.75"
Axle Supplier: Hendrickson
* Axle-General Spec.: Axle - Tandem (2) Axle included in Suspension (For 4S2M System)
Axle-Track Length: 77-1/2"
* Axle-Spindle Type: Parallel Spindle
Brake Lining Size: 16.5" X 7"
Brake Lining Spec.: Hendrickson Extended Service (Abex-3030-197)

* Brake Control System:	4S/2M Bendix TABS6 ABS Advanced Roll Stability System
Spring Brake Control:	Sealco 110500 Springbrake Priority
Brake Cont-Hose & etc.:	Standard Air Line & Hose Application (US&Canada)
* Slack Adjuster Spec.:	Gunite Auto-5.5", 28 Spline
Brake Chamber Spec.:	TSE 3030 Tamper Resist (HT standard)
Stroke Length:	MFG's Standard Stroke Length
Hub Specification:	HT Standard (KIC) 10 Stud Hub Piloted Outboard Iron Hub
Drum Specification:	HT Standard (KIC) Cast Drum
Hub/Drum-Opt(Nut&Other):	Standard
Bearing Specification:	Stemco
Lubrication Spec.:	Chev Delo Gear EP5 80-90 oil
* Wheel Seals Spec.:	Stemco Discover Seals, Hub Cap included in tire inflation system, Pro-Torq Nut
* Tire Inflation Spec.:	Hendrickson Tire Maax Inflation System for Undressed Axle (This kit include Hendrickson Hub Cap for TireMaax)
Tire Inflation Pressure:	100 PSI
* Tire Inflation Lamp Location:	Indicator PSI Light at Roadside Mounted over corner radius. (STD location)
* Tire Inflation Lamp Spec.:	33 Series Lamp

ELECTRICAL

* Harness-General Spec.:	Molded Color Code Grote Harness Oval molds with front terminal rings
Harness-Special Feature:	Manufacturer's Standard Feature
* Front Light:	(4) Trucklite 33275Y LED PC Rated Mounted with Grommet (2-Front & 2-Side)
* Rear ID Header Light:	(5) Trucklite Dual Function 33204R LED (Cluster of 3 & 1 Each Outboard)
* Rear ID-Special Feature:	Dual Function Rear Header Lights - 3 Lamps at center with Marker & Stop functionality, 2 Lamps outboard with Marker & Turn functionality
Rear Side Marker Type(Shape):	Mini Button Style Lamp with Antitheft Bracket
Rear Side Marker Detail Spec:	(2) Trucklite 33275R LED PC Rated Flush w/ Grommet 33725 w/ anti-theft hardware
Rear Side Marker MT'G Location:	Mounted on Standard Location on Rear Corner Post - HT STD
* S/T/Tail Light-Quantity & Type:	(6) Trucklite 40 or 44 Series (Round Style) or Equivalent
* S/T/Tail Light-Detail Spec:	(6) Trucklite 44331R LED Mounted w/ Stainless Steel Rivets (3 per Side).
Main Mid-Turn Light:	Install the Mid turn lamp
* Mid-Turn Mounting Method:	Mounting on Aerodynamic Side Skirt
* Main Mid-Turn Light-Detail Spec:	(2) Trucklite 60420Y LED Flange Mounted w/ Stainless Steel Ring
ABS Light Detail Spec:	(1) Trucklite 33275Y LED PC Rated w/ Grommet 33725 w/ anti-theft hardware
ABS Light MT'G Location:	Mounted on Standard Location on Rear Corner Post - HT STD
License Light:	(1) Trucklite 33210C LED with 33815 Anti-Theft Flange
* Option Related Lamps/Harness:	Additional Trucklite 33 LED series Marker Lights. (5) Each Side Top & Bottom Rail (Total 16 Extra Light)
Electrical Related Regulation:	Standard Application

MARKING/DECALS

HT & Product Type Decal Package:	Hyundai Logo & Product Type Decals Application(For not having pre-painted white panels for side/door/front, Apply white HT Corporate decals)
Decal Package:	Factory Furnished Hyundai Information & Regulatory Decal Package with FMCSA Specified in Notes
Decal Opt 2-Decal Location:	Standard Application
Decal Opt 3-Decal Installation:	Standard Application
Decal Opt 5-Decal Location-reefer:	Standard Application
Decal Opt 6-Decal Installation-reefer:	Standard Application
Conspicuity Vendor:	3M
Conspicuity Markings:	Hyundai Standard Conspicuity with Logo Applied to Side Bottom Rail
License Plate:	Temporary For Delivery. Fasten on SUS Mounting Plate
License Plate Brk't Install:	Standard Install Location - Roadside Below Door Sill
Furnish Document Holder:	Factory Furnished
Document Holder Detail Spec:	(1) Phillips 16-802
Document Holder/Manifest Loc.:	Overlaid on Lower R/S Front

- * Vent Door Specification: (1) Side Hinged Swing type Vent Door-Stainless Steel
- * Vent Door Location: Lower C/S (RH) Rear Door

PAIN/FINISH

- Upper Coupler Finish: Stainless Steel-Forward Section w/ Black Undercoating inside of Upper Coupler
- Crossmembers Finish: HDG : ALL Steel Crossmembers including Hat C/M, L/G & Bogie Area (Except any Aluminum)
- * Axle & Components Finish: Black Undercoating
- * Susp. Sub-Frame Finish: Black Undercoating
- L/Gear(K-Bracing) Finish: Hot Dip Galvanized
- L/Gear(Upper Leg) Finish: Hot Dip Galvanized
- Rear Frame-Finish: Stainless Steel
- Rear Frame-Paint Color: None (For Galvanized or Stainless Steel)
- Rear Underride-Finish & Spec.: Hot Dip Galvanized
- Rear Underride-Paint Color: None (For Galvanized or Stainless Steel)

MISCELLANEOUS

- Mudflap Provider: Factory Furnished Mudflaps
- Mudflap Specification: 24"x30" White Plain Plastic with Hyundai Logo 3/8# thick with Anti-spray ribs
- Mudflap Mounting Loc.: Suspension frame (Tandem/Single axle frame without P.H.)
- Mudflap Mounting: STD Location w/ H.D Washer Retainer
- * Aero Dynamic Furnish: Factory Furnished
- * Aero Dynamic Skirt Spec.: Ridge Green Wing Side Skirt - Aero Dynamic Device with Black Color

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical.
Equipment availability, prices and specifications are subject to change without notice.