



# Hale Trailer Brake & Wheel

A014091-A014092

VIN: 033585-033586



Series: HYDRAULIC DETACHABLE GOOSENECK

Model: RTN35TD-PS TRAILER

Item	Description
MODEL	RTN35TD-PS TRAILER
TONS CAPACITY	35 TONS IN ANY 16'
CONSTRUCTION	(4) I-BEAM, CAMBERED, T-1 STEEL
CUSTOM/PAVER SPECIAL	TAPERED FRONT BEAMS (8-3/8" DEEP)
PLATFORM WIDTH	8'-6"
PLATFORM LENGTH	23'
PLATFORM HEIGHT/ROAD CLEARANCE	22"/6" LOADED (ADJUSTABLE)
CROSSMEMBER SPACING	ON 20" CENTERS
FRONT FOLDING RAMPS	41" LONG-WOOD FILLED-ADJUSTABLE
HYDRAULIC SYSTEM	FROM TRACTOR WETLINE
GOOSENECK	NON-GROUND ENGAGING REMOVABLE-HI LIFT
GOOSENECK SUPPORT CYLINDER	HYDRAULIC
GOOSENECK CONNECTION	PIN & STIRRUP TYPE W/ VERTICAL AIR LOCK PIN
SWING CLEARANCE	90"
FIFTH WHEEL HEIGHT	48"-50"-52"-54"-56" LOADED (ADJUSTABLE)
1/8" ALUMINUM TOP COVER	OVER GOOSENECK AREA
AIR BRAKES	16.5" X 7" W/ AUTO SLACKS & OUTBOARD DRUMS
SPRING BRAKES	ON ONE AXLE
AXLES	(2) 22,500# 5/8" WALL W/ LIMITED CHAINS
TIRES	(8) 255/70R22.5 (H)
WHEELS	ACCURIDE EXTRA POLISHED OUTERS, STEEL DISC INNERS
SUSPENSION	AIR RIDE W/ 55" AXLE SPACING
SUSPENSION	+3/-3 HEIGHT CONTROL, AUTO/MANUAL
MANUAL EXHAUST VALVE	ON ALL AXLES
LIGHTS	L.E.D. TRUCK-LITE RUBBER SEALED SYSTEM
BATTERY BACK-UP	AMBER STROBE LIGHTS ON BATTERY-BACK UP FLASH ALL LIGHTS
3RD TAILLIGHT PACKAGE	AMBER L.E.D. STROBE WARNING LAMPS
LASH RINGS	(12) TOTAL- 4 PER SIDE (BENT STYLE), 1-EACH SIDE FRONT OF DECK FLAT STYLE ON 45 DEGREE ANGLE, 1 EACH BOLSTER (FLAT STYLE)
EXTENSION BRACKETS (OUTIGGERS)	12" SWINGING/REMOVABLE OUTRIGGERS WITHOUT PLANKS; INCLUDES 12" DOUBLE HOOK-ON OUTRIGGERS AT FRONT OF DECK
DECKING	1-1/2" APITONG FULL WIDTH
PAINT	GLOSS BLACK (2-PART URETHANE) STEEL PARTS TO MATCH PAINT COLOR
FLAG HOLDER SLOTS	IN BOLSTERS
REAR DECK	FULL WIDTH-WOOD COVERED, 1 1/2" APITONG
REAR SLOPE (MAIN TO REAR DECK)	3 TO 1 (18 DEGREE) W/FULL WIDTH DECKING
ROLLER STOP@REAR	4" HIGH, WIDTH OF MAIN BEAMS
FLAG HOLDER W/ THUMB SCREWS	1-PAIR FRONT CORNER OF DECK, 1-PAIR ENDS OF LIGHT PANEL
ALUMINUM STORAGE BASKETS BOLT-IN	(1) 2ND SECTION FROM FRONT OF DECK

Etnyre reserves the right to modify pricing on all quotes and orders with material and labor surcharges as needed

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical.

Equipment availability, prices and specifications are subject to change without notice.