

HALE

TRAILER

BRAKE & WHEEL

A014200-A014203
 VINS: 476221-476223
 & 476228

SALES | RENTALS | PARTS | SERVICE

| | | | |
|------------------------|--------------|--------------------------|--------------|
| Allentown, PA: | 800-383-8894 | Jacksonville, FL: | 800-828-3055 |
| Baltimore, MD: | 888-601-7500 | Little Rock, AR: | 833-424-8944 |
| Boston, MA: | 800-854-5310 | Portland, ME: | 800-325-4253 |
| Concord, NC: | 800-438-2250 | Richmond, VA: | 866-839-3495 |
| Delmar, DE: | 866-486-1400 | Scranton, PA: | 800-569-1400 |
| Des Moines, IA: | 888-673-5011 | Springfield, MA: | 800-854-5306 |
| Elkton, MD: | 800-544-7127 | Voorhees, NJ: | 866-315-0235 |

HaleTrailer.com | @haletrailer     

800-232-6535 *FINANCING AVAILABLE



| | | |
|--|--|-------------------------|
| Model | SX3 | SX3-4736 spread triaxle |
| | 102" wide | |
| Frame length | 47' | Gray tub/Black frames |
| Tub Length | 36' | Vin# 1S9SS4731PL476221 |
| Tub Style | SX-Round Bottom | Vin# 1S9SS4733PL476222 |
| Tub Sides | 1/4" AR400 | Vin# 1S9SS4735PL476223 |
| Tub Floor | 1/4" AR400 | |
| Tub Dividers | 0 | Black tub/Black frames |
| Tub Volume: | 36' SX - Water level - 24.1 cubic yards | Vin# 1S9SS4734PL476228 |
| | 36' SX - Heaped - 32 cubic yards | |
| Dolly Legs | Binkley | |
| Hydraulics | 5" Cylinders | |
| Valve on trailer | Hydraulic control valve on trailer (Air/hydraulic) | |
| Suspension | Ridewell RW260 | |
| Axle Spacing | 49"-79" | |
| Lift Axle | 3rd | |
| ABS-Axles | 25K | 1 |
| Non-ABS Axles | 25K | 2 |
| Axle Track | 77.5"-STD | |
| Hubs | Duralite-Std | |
| Brakes | 16-1/2" x 7" | |
| Drums | Cast Steel | |
| Wheel Style | Hub-Piloted U/M | |
| Wheel Type | STL 8.25x22.5 | 12 steel |
| Tires | 11R22.5 H ply | 12 |
| Fenders | All Plastic | |
| Tub Paint # | Black, gray or white | |
| Frame Paint # | Black or gray | |
| Tarp Brand | Aero | |
| Tarp Type | Mesh-Non Sealed | |
| Lock Out Switch | None | |
| W style pushblock - Std | | |
| Large liquid filled air gauge on driver's side - Std | | |
| Grease bank for hydraulic cylinders front and rear - Std | | |
| Note: | | |
| Due to the volatility in steel & component costs, SmithCo reserves the right to adjust trailer pricing up to 45 days prior to start of production. Customer to receive notification if pricing adjustment is required. | | |

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.