

HALE

TRAILER

BRAKE & WHEEL

A014662-A014667

VINS: 35918-35920 &



5924-35926

SALES | RENTALS | PARTS | SERVICE

Allentown, PA: 800-383-8894	Jacksonville, FL: 800-828-3055
Baltimore, MD: 888-601-7500	Little Rock, AR: 833-424-8944
Boston, MA: 800-854-5310	Portland, ME: 800-325-4253
Concord, NC: 800-438-2250	Richmond, VA: 866-839-3495
Delmar, DE: 866-486-1400	Scranton, PA: 800-569-1400
Des Moines, IA: 888-673-5011	Springfield, MA: 800-854-5306
Elkton, MD: 800-544-7127	Voorhees, NJ: 866-315-0235

HaleTrailer.com | @haletrailer

800-232-6535 *FINANCING AVAILABLE

BASE MODEL: DC-48 Drop Deck Combo Flatbed	
components	description
CAPACITY	Standard Beam Pkg - 80,000 GVWR (60,000 in 10' Span)
OVERALL LENGTH	48' - Base Weight 10,640#
UPPER DECK LENGTH	10'
LOWER DECK LENGTH	38'
OVERALL WIDTH	8' 6"
KING PIN SETTING	18" - Squared Front
UPPER COUPLER PLATE	1/4"
UPPER COUPLER HEIGHT	48"
FRONT SKIRT	Aluminum Front and Corners
REAR SKIRT	Aluminum
BULKHEAD	None
MAIN FRAME	26" Fab.-PreCamb.I-Beams-(80K Pkg)
SIDE RAILS	6"-Alum-Extruded W/Double L Track
TOP DECK FLOOR SILLS	4" Steel I-Beam - 18" O.C.
LOWER DECK FLOOR SILLS	4" Steel I-Beam 12" O.C. HD Pkg
COIL HAUL PACKAGE	Single Coil Placement - 5 Extra Stud Sils-Ctr On Trailer
FLOOR DECKING	1-1/8" HD Aluminum W/4 Nailer Boards
WINCHES	12 DOUBLE L (+)#75
WINCH TRACK	Double L Aluminum - Extruded Siderail R/S Only
TIE BAR	Curb Side - Full Length - 3/8" x 2"
STRAPS	None
LANDING GEAR	Two Speed - Jost A500
SUSPENSIONS	Air Ride - Hendrickson Intraax - 23K - 2 Axles
SUSPENSION LOCATION	Set at Rear most Position - 32.5" Center of Rear Axle to Rear of Trailer
AXLES	(2) 22.5K Cap.- Type 30 Chambers - Auto Slacks - ABS - 22.5 Tires (1463#)
AXLE SPACING	10'2" Wide Spread
LIFT AXLE	None
DUMP VALVE	None
SCALES	None
PARKING BRAKES	All Axles
ABS SYSTEM	Wabco ABS System 2S/1M
DUST SHEILDS	None
WHEELS	Disc - Hub Pilot-22.5 (2-AX)-Polish ALUMINUM 4 Outside Wheels(4-Steel Inside) (-
TIRES	255/70R 22.5 - 41" Loaded Deck Height - Double Coin
TIRE INFLATION SYSTEM	None
ANTI-SAIL MUD FLAPS	Behind All Axles
STAKE POCKETS	24" O.C. Sides & 5 Across Rear
SPOOL	Triangular Shaped
RUB BAND ALUM	3/8" x 3" - Aluminum - Recessed for DOT Tape
DOCK BUMPERS	Rubber Inboard
CARGO TIE DOWN	14 Pair of Recessed Chain Ties Evenly Spaced
CONTAINER TWIST LOCKS	None
TIRE CARRIERS	Tire Carrier Positioned In Front of Main Beams Between Landing Gear
DUNNAGE RACK	None
TOOLBOX MATERIAL	Aluminum- Smooth Box & Door(s)
TOOLBOX TYPE	18HX18DX60L-ALUM. TOOLBOX DD SMOOTH-LOCKROD (CAM) STYLE 17-PRT-
TOOLBOX LOCATION	Driver Side- Behind Landing Gear
LIGHTS	Grote Ultra Blue Sealed Wiring Harness- 2 Micros Per Side & Mid Turn-3/3/3 Rear
CUSTOM LIGHTS	None
PAINT	Black - PPG Epoxy Primer and Acrylic Polyurethane - Shot Blasted
CUSTOM 1.	None
CUSTOM 2.	None
CUSTOM 3.	None

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.